


PRODUCTION AREA COOLING PROJECT

FOR


CRANE COMPOSITES, INC

JONESBORO, ARKANSAS

PROJECT LOCATION:
8500 C.W. POST ROAD,
JONESBORO, AR 72402



AREA MAP
NO SCALE





PROJECT LOCATION MAP
NO SCALE

DRAWING LIST

SHEET NO.	DRAWING TITLE
G0.1	TITLE SHEET AND DRAWING LIST
C1.1	CIVIL - CHILLER PAD, ASPHALT, AND GRADING PLAN
S0.1	STRUCTURAL - SYMBOLS AND ABBREVIATIONS
S1.1	STRUCTURAL - OVERALL FIRST FLOOR PLAN
S1.2	STRUCTURAL - MEZZANINE PLAN
S4.1	STRUCTURAL - ENLARGED PLANS - 1
S4.2	STRUCTURAL - ENLARGED PLANS - 2
S4.3	STRUCTURAL - ENLARGED PLANS - 3
S5.1	STRUCTURAL - DETAILS - 1
S5.2	STRUCTURAL - DETAILS - 2
H0.1	HVAC - SYMBOLS AND ABBREVIATIONS
H1.1	HVAC - OVERALL FIRST FLOOR PLAN
H1.2	HVAC - MEZZANINE PLAN
H3.1	HVAC - SECTIONS
H4.1	HVAC - ENLARGED PLAN - 1
H4.2	HVAC - ENLARGED PLAN - 2
H4.3	HVAC - ENLARGED PLANS - 3
H4.4	HVAC - ENLARGED PLANS - 4
H5.1	HVAC - DETAILS - 1
H5.2	HVAC - DETAILS - 2
H6.1	HVAC - SCHEDULES
H7.1	HVAC - PROCESS FLOW DIAGRAM - 1
H7.2	HVAC - PROCESS FLOW DIAGRAM - 2
H8.1	HVAC - CONTROLS DIAGRAMS - 1
H8.2	HVAC - CONTROLS DIAGRAMS - 2
E0.1	ELECTRICAL - SYMBOLS AND ABBREVIATIONS
E1.1	ELECTRICAL - OVERALL FIRST FLOOR PLAN
E1.2	ELECTRICAL - MEZZANINE PLAN
E4.1	ELECTRICAL - ENLARGED UTILITY ROOM PLAN
E4.2	ELECTRICAL - ENLARGED PLAN - 1
E4.3	ELECTRICAL - ENLARGED PLAN - 2
E4.4	ELECTRICAL - ENLARGED PLAN - 3
E4.5	ELECTRICAL - ENLARGED PLAN - 4
E5.1	ELECTRICAL - DETAILS AND ONE-LINE DIAGRAM
E6.1	ELECTRICAL - SCHEDULES

910 West Wingra Drive
Madison, WI 53715
608-251-4843
608-251-8655 fax
www.strand.com

CONTRACT 3-2018



ISSUE FOR BID, 04/05/18





SHEET
1
G0.1


NOT FOR CONSTRUCTION

GENERAL NOTES:




1. FINISHED FLOOR=100'-0"±.
2. MEZZANINE EL = 116'-6"±.

KEY NOTES:


- ① PROVIDE 4" IMP WALL ALONG ENTIRE SOUTH EDGE OF MEZZANINE. SEE DETAILS  .
- ② PROVIDE 7'-0" HIGH OPENING IN IMP WALL FOR STAIR. MATCH OPENING WIDTH TO WIDTH OF STAIR. PROVIDE DOOR FRAME AROUND OPENING PER .
- ③ PROVIDE 7'-0" HIGH OPENING IN IMP WALL AT GATE. MATCH OPENING WIDTH TO GATE. PROVIDE DOOR FRAME PER  AND PLASTIC CURTAIN OVER OPENING.
- ④ INFILL FLOOR OPENING W/CONCRETE. ROUGHEN SIDES OF OPENING TO 1/4" MIN. AMPLITUDE. PROVIDE #4@12"x1'-6" ADHESIVE ANCHOR DOWELS EMBEDDED 6" IN SIDES OF OPENING, CENTERED IN SLAB. PROVIDE BONDING AGENT ON SIDES OF OPENING. MATCH THICKNESS OF INFILL TO EXISTING FLOOR SLAB THICKNESS.



MEZZANINE PLAN



KEY PLAN
NO SCALE



STRUCTURAL
MEZZANINE PLAN

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS


NO.	REVISIONS	DATE:
A	ISSUE FOR BID	04/05/18

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES



SHEET
5
S1.2




ENLARGED PLAN

GENERAL NOTES:

- DESIGN LOADS
LL= 60 PSF
STEEL PLATE = 14 PSF
FCU = 7,860 LBS EACH
- TOP OF PLATFORM = 120'-0".
FINISH FLOOR = 100'-0".
- UNLESS OTHERWISE SHOWN OR NOTED, PROVIDE BOLTED OR WELDED CLIP ANGLE OR SHEAR TAB CONNECTIONS FOR ALL BEAM-TO-BEAM AND BEAM-TO-COLUMN CONNECTIONS. CONNECTION DESIGN AND DETAILS SHALL BE PROVIDED BY CONTRACTOR. CONNECTION DETAILS SHALL CONFORM TO STANDARD FRAMED BEAM CONNECTIONS PROVIDED BY THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION. VERTICAL SHEAR CAPACITY OF CONNECTIONS SHALL EXCEED ONE HALF THE ALLOWABLE UNIFORM LOAD IN KIPS LISTED IN THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION, FOR THE GIVEN BEAM SPAN AND SIZE.
- PLATFORM SHALL BE CONSTRUCTED OF THE FOLLOWING MATERIALS:
WF BEAMS: ASTM A992 GR. 50
HSS MEMBERS: ASTM A500 GR. B
ANGLES AND PLATES: ASTM A36
CONNECTION BOLTS: ASTM A325
WELD: E70 XX ELECTRODES
RAILING: ASTM A53 GR. B
- SHOP PRIME AND FINISH PAINT ALL NEW STEEL TO MATCH EXISTING PER SECTION 09 91 00.
- COORDINATE FINAL FCU SUPPORT STEEL LOCATIONS AND CONNECTIONS BETWEEN UNIT AND SUPPORTS WITH EQUIPMENT MANUFACTURER.
- ALL WORK SHOWN ON THIS SHEET SHALL BE PART OF BID ALTERNATIVE NO. 1.

KEY NOTES:

- STEEL RAILING. TYP. ALL EDGES OF PLATFORM EXCEPT AT AHU'S. SEE DETAIL
- SPIRAL STAIR. SEE DETAILS
- NEW BEAM-TO-EXISTING COLUMN CONNECTION. SEE DETAIL
- 5/16" STEEL CHECKERED FLOOR PLATE .
CONNECT PLATE TO ALL SUPPORTING MEMBERS.
- PROVIDE NEW COLUMN FOOTING. SEE DETAIL .
(TYP. OF 2).
- TYPICAL BEAM-BEAM CONNECTION. SEE DETAIL
- SAFETY GATE. SEE DETAIL
- BRACKET SUPPORT
- CUT OPENING IN METAL WALL PANEL TO CONNECT NEW W24x68 TO EXISTING COLUMN. PATCH WALL PANEL AROUND BEAM. W/FOAM FILL AND METAL CLOSURE PLATE.
- REMOVABLE RAILING
- PROVIDE FALL PROTECTION ANCHOR POST. PROVIDE HSS 4x0.313x2'-0" FULLY WELDED TO TOP FLANGE OF W16x26 BEAM. PROVIDE 1/2" TOP PLATE, FULLY WELDED TO POST. AT TOP OF POST, PROVIDE D-RING W/MINIMUM 5000LB RATING.



KEY PLAN
NO SCALE

NOT FOR
CONSTRUCTION

DATE	04/05/18								
REVISIONS									
NO.	A								

STRUCTURAL
ENLARGED PLANS

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES

SA
STRAND
ASSOCIATES®

SHEET
6
S4.1

1. DESIGN LOADS
FCU = 3,983 LBS EACH

2. TOP OF SUPPORT STEEL = 118'-6".
FINISH FLOOR = 100'-0".


3. ROOF JOIST BEARING
COL LINE Y = 135'-9"±
COL LINE C = 135'-0"±

4. UNLESS OTHERWISE SHOWN OR NOTED, PROVIDE BOLTED OR WELDED CLIP ANGLE OR SHEAR TAB CONNECTIONS FOR ALL BEAM-TO-BEAM AND BEAM-TO-COLUMN CONNECTIONS. CONNECTION DESIGN AND DETAILS SHALL BE PROVIDED BY CONTRACTOR. CONNECTION DETAILS SHALL CONFORM TO STANDARD FRAMED BEAM CONNECTIONS PROVIDED BY THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION, VERTICES. SHEAR CAPACITY OF CONNECTIONS SHALL EXCEED ONE HALF THE ALLOWABLE UNIFORM LOAD IN KIPS LISTED IN THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION, FOR THE GIVEN BEAM SPAN AND SIZE.

5. PLATFORM SHALL BE CONSTRUCTED OF THE FOLLOWING MATERIALS:
WF BEAMS: ASTM A992 GR. 50
HSS MEMBERS: ASTM A500 GR. B
ANGLES AND PLATES: ASTM A36
CONNECTION BOLTS: ASTM A325
WELD E70 XX ELECTRODES
RAILING: ASTM A53 GR. B
6. SHOP PRIME AND FINISH PAINT ALL NEW STEEL TO MATCH
EXISTING PER SECTION 09 91 00.
7. COORDINATE FINAL FCU SUPPORT STEEL LOCATIONS AND
CONNECTIONS BETWEEN UNIT AND SUPPORTS WITH EQUIPMENT
MANUFACTURER.

① EQUIPMENT HANGER. SEE DETAIL

② PROVIDE STRUT ANGLES AT LOCATIONS WHERE
HANGER MEMBERS ARE MORE THAN 6" FROM JOIST
GIRDER PANEL POINT. SEE DETAIL G.



KEY PLAN
NO SCALE

STRUCTURAL ENLARGED PLANS - 2

**PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS**


JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES

The logo for Strand Associates, featuring a stylized 'SA' monogram above the company name 'STRAND ASSOCIATES' in a bold, sans-serif font.

SHEET
7
S4.2

[illegible]



GENERAL NOTES:



- DESIGN LOADS
FCU = 3,983 LBS EACH
- TOP OF SUPPORT STEEL = 126'-5".
FINISH FLOOR = 100'-0".
- ROOF JOIST BEARING
COL LINE Y = 135'-9"±
COL LINE C = 135'-0"±
- UNLESS OTHERWISE SHOWN OR NOTED, PROVIDE BOLTED OR WELDED CLIP ANGLE OR SHEAR TAB CONNECTIONS FOR ALL BEAM-TO-BEAM AND BEAM-TO-COLUMN CONNECTIONS. CONNECTION DESIGN AND DETAILS SHALL BE PROVIDED BY CONTRACTOR. CONNECTION DETAILS SHALL CONFORM TO STANDARD FRAMED BEAM CONNECTIONS PROVIDED BY THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION. VERTICAL SHEAR CAPACITY OF CONNECTIONS SHALL EXCEED ONE HALF THE ALLOWABLE UNIFORM LOAD IN KIPS LISTED IN THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION, FOR THE GIVEN BEAM SPAN AND SIZE.
- PLATFORM SHALL BE CONSTRUCTED OF THE FOLLOWING MATERIALS:
WF BEAMS: ASTM A992 GR. 50
HSS MEMBERS: ASTM A500 GR. B
ANGLES AND PLATES: ASTM A36
CONNECTION BOLTS: ASTM A325
WELD E70 XX ELECTRODES
RAILING: ASTM A53 GR. B
- SHOP PRIME AND FINISH PAINT ALL NEW STEEL TO MATCH EXISTING PER SECTION 09 91 00.
- COORDINATE FINAL FCU SUPPORT STEEL LOCATIONS AND CONNECTIONS BETWEEN UNIT AND SUPPORTS WITH EQUIPMENT MANUFACTURER.

KEY NOTES:

- EQUIPMENT HANGER. SEE DETAIL
- FCU-04 HANGER. SEE DETAIL
- PROVIDE STRUT ANGLES AT LOCATIONS WHERE HANGER MEMBERS ARE MORE THAN 6" FROM JOIST GIRDER PANEL POINT. SEE DETAIL
- PROVIDE L2x2x1/4 DIAGONAL BRACE BETWEEN HSS MEMBERS.

NOT FOR CONSTRUCTION

NO.	DATE	REVISIONS
1	04/05/18	ISSUE FOR BID
2		
3		
4		
5		
6		
7		
8		
9		
10		



STRUCTURAL ENLARGED PLANS - 3





















PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES

SA
STRAND
ASSOCIATES®

SHEET
8
S4.3

[illegible]

STRUCTURAL DETAILS - 1

**PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS**


JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES




STRAND
ASSOCIATES

SHEET
9
S5.1




CONCRETE SHALL HAVE A 28-DAY MINIMUM COMPRESSIVE STRENGTH OF 4,000 PSI, MINIMUM CEMENT CONTENT OF SIX SACKS PER CUBIC YARD, AND A MAXIMUM OF 5.5 GALLONS OF TOTAL WATER PER SACK. THE SLUMP OF THE CONCRETE SHALL BE WITHIN THE RANGE OF 2 TO 3 1/2 INCHES. AN AIR-ENTRAINING ADMIXTURE CONFORMING TO ASTM C260, EQUAL TO "DAREX," SHALL BE USED IN ALL CONCRETE TO OBTAIN 4% TO 7% AIR CONTENT. A WATER REDUCER MEETING ASTM C494 TYPE A REQUIREMENTS SHALL BE INCLUDED IN THE MIX. MIXES SHALL BE DESIGNED TO ACCORDANCE WITH ACI 211.1.


A CHILLER PAD
S5.2 NO SCALE




B PARTITION BASE
S5.2 NO SCALE




C PARTITION EAVE
S5.2 NO SCALE



D DOOR DETAILS
S5.2 NO SCALE




E BRACKET SUPPORT
S5.2 NO SCALE




- NOTES:
1. FIELD VERIFY BOTTOM OF JOIST GIRDER ELEVATION PRIOR TO HANGER FABRICATION.
 2. WHERE HSS CONNECT TO JOIST GIRDER AT A DISTANCE MORE THAN 6" FROM PANEL POINT, PROVIDE STRUT ANGLES PER **G**.

F EQUIPMENT HANGER DETAIL
S5.2 NO SCALE




SECTION A-A




NOTE: WHEN LOADS >100# OCCUR AT A DISTANCE MORE THAN SIX INCHES FROM A PANEL POINT, A STRUT ANGLE(S) MUST BE FURNISHED AND INSTALLED IN THE FIELD TO CARRY THE LOAD TO AN OPPOSITE PANEL POINT AS SHOWN. STRUT ANGLE(S) TO MATCH OR EXCEED SIZE OF ADJACENT JOIST DIAGONAL MEMBERS. PROVIDE TWO STRUT ANGLES (ONE EACH SIDE OF JOIST) IF JOIST DIAGONALS CONSIST OF DOUBLE ANGLES.

G TYPICAL CONCENTRATED LOADS ON JOISTS FOR TRAPEZE HANGERS
S5.2 NO SCALE




- NOTES:
1. SHOP PRIME AND FINISH PAINT GUARDRAIL PER SECTION 09 91 00.

H STEEL FORKLIFT GUARDRAIL
S5.2 NO SCALE



NOTE:
ALL STEEL TO BE CARBON STEEL AND PAINTED PER SPECIFICATION SECTION 09 91 00

J EXTERIOR PIPE SUPPORT
S5.2 NO SCALE



K REMOVABLE RAILING
S5.2 NO SCALE

NOT FOR CONSTRUCTION

DATE:	04/05/16
REVISIONS	
NO.	A

STRUCTURAL DETAILS - 2

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007
PROJECT MGR.
NICHOLAS E. SALES



SHEET
10
S5.2





EQUIPMENT ABBREVIATIONS

ACC	AIR COOLED CHILLER
AHU	AIR HANDLING UNIT
AS	AIR SEPARATOR
BLR	BOILER
BB	BASEBOARD
CONV	CONVECTOR
CD	CEILING DIFFUSER
CHW	CHILLED WATER
CT	COOLING TOWER
CUH	CABINET UNIT HEATER
CWP	CHILLED WATER PUMP
DC	DRY COOLER
DH	DEHUMIDIFIER
DL	DRUM LOUVER
EBB	ELECTRIC BASEBOARD
EDH	ELECTRIC DUCT HEATER
EF	EXHAUST FAN
EG	EXHAUST GRILLE
EJ	EXPANSION JOINT
EL	EXPANSION LOOP
ER	EXHAUST REGISTER
ERC	ELECTRIC REHEAT COIL
ERU	ENERGY RECOVERY UNIT
EUH	ELECTRIC UNIT HEATER
EWB	ELECTRIC WALL HEATER
FCU	FAN COIL UNIT
FD	FIRE DAMPER
FTR	FINNED TUBE RADIATION
FUR	FURNACE
HC	HEATING COIL
HP	HEAT PUMP
HU	HUMIDIFIER
HUH	HOT WATER UNIT HEATER
HWP	HOT WATER PUMP
HX	HEAT EXCHANGER
L	LOUVER
MAU	MAKE-UP AIR UNIT
P	PUMP
PC	PUMPED CONDENSATE
RCP	RADIANT CEILING PANEL
RF	RETURN FAN
RG	RETURN GRILLE
RR	REGISTER
RTU	ROOFTOP UNIT
SD	SUCTION DIFFUSER
SF	SUPPLY FAN
SG	SUPPLY GRILLE
SR	SUPPLY REGISTER
SS	SPLIT SYSTEM
ST	STEAM TRAP
SUH	STEAM UNIT HEATER
TCP	TEMPERATURE CONTROL PANEL
TG	TRANSFER GRILLE
UH	UNIT HEATER
UV	UNIT VENTILATOR
VAV	VARIABLE AIR VOLUME BOX
VD	VOLUME DAMPER
VFD	VARIABLE FREQUENCY DRIVE









GENERAL ABBREVIATIONS

ACH	AIR CHANGES PER HOUR
AFF	ABOVE FINISHED FLOOR
ALT	ALTERATE
AP	ACCESS PANEL
BOD	BOTTOM OF DUCT
BTU	BRITISH THERMAL UNIT
BTUH	BRITISH THERMAL UNIT PER HOUR
CFM	CUBIC FEET PER MINUTE
CLG	CEILING
COND	CONDENSATE
DAT	DISCHARGE AIR TEMPERATURE
DB	DRY BULB TEMPERATURE
DDC	DIRECT DIGITAL CONTROL
DG	DOOR GRILLE
DX	DIRECT EXPANSION
(E)	EXISTING
EA	EXHAUST AIR
EAT	ENTERING AIR TEMPERATURE
EER	ENERGY EFFICIENCY RATIO
EL	ELEVATION
ESP	EXTERNAL STATIC PRESSURE
EWB	ENTERING WATER TEMPERATURE
(F)	FURNISHED BY OWNER
FC	FAIL CLOSED
FD	FLOOR DRAIN
FLA	FULL LOAD AMPS
FO	FAIL OPEN
FPI	FINS PER INCH
FPM	FEET PER MINUTE
FT	FEET
FVNR	FULL VOLTAGE NON REVERSING
GA	GAUGE
GPM	GALLONS PER MINUTE
HHW	HEATING HOT WATER
IPLV	INTEGRATE PART LOAD VALVE
LAT	LEAVING AIR TEMPERATURE
LWT	LEAVING WATER TEMPERATURE
MBH	THOUSANDS OF BTU PER HOUR
MC	MECHANICAL CONTRACTOR
NA	NOT APPLICABLE
NC	NORMALLY CLOSED
NO	NORMALLY OPEN
NPT	NATIONAL PIPE THREAD
NTS	NOT TO SCALE
OA	OUTSIDE AIR
OC	ON CENTER
ODP	OPEN DRIP PROOF
OV	OUTLET VELOCITY
PD	PRESSURE DROP
PSI	POUNDS PER SQUARE INCH
PSIG	POUNDS PER SQUARE INCH GAUGE
RA	RETURN AIR
RPM	REVOLUTIONS PER MINUTE
SA	SUPPLY AIR
SP	STATIC PRESSURE
TEFC	TOTALLY ENCLOSED FAN COOLED
TR	TONS OF REFRIGERATION
WB	WET BULB





EQUIPMENT SYMBOLS

	EQUIPMENT TAG
	INLINE PUMP
	ROOF EXHAUST FAN
	AIR FLOW DIRECTION






























DUCTWORK SYMBOLS

	SUPPLY DUCT (UP OR SECTION)
	SUPPLY OR OUTSIDE AIR DUCT (DOWN/OR AWAY)
	EXHAUST OR RETURN DUCT (UP OR SECTION)
	EXHAUST OR RETURN DUCT (DOWN/OR AWAY)
	ROUND DUCTWORK UP
	ROUND DUCTWORK DOWN
	FLEXIBLE CANVAS CONNECTION
	TURNING VANES

DAMPER SYMBOLS

	MANUAL VOLUME DAMPER
	AUTOMATIC DAMPER
	BACKDRAFT DAMPER
	1-1/2 HR. FIRE DAMPER

PIPING SYMBOLS

	BALL VALVE
	TEE DOWN
	TEE UP
	ELBOW DOWN
	ELBOW UP
	GATE VALVE
	GLOBE VALVE
	2-WAY CONTROL VALVE
	3-WAY CONTROL VALVE
	METER
	GAS SHUTOFF PLUG VALVE
	BALANCING VALVE
	PRESSURE REDUCING VALVE
	STRAINER
	UNION
	BUTTERFLY VALVE
	TEMPERATURE ELEMENT
	TEMPERATURE INDICATOR
	TEMPERATURE TRANSMITTER
	PRESSURE INDICATOR
	PRESSURE TRANSMITTER
	FLOW SWITCH
	MANUAL AIR VENT
	CHECK VALVE
	CONCENTRIC REDUCER
	ECCENTRIC REDUCER
	FLEXIBLE CONNECTOR
	TRIPLE DUTY VALVE
	FLOOR DRAIN

PIPING DESIGNATIONS

CHWR	CHILLED WATER RETURN
CHWS	CHILLED WATER SUPPLY
COND	COOLING COIL CONDENSATE

FIELD MOUNTED CONTROLS

ⓘ	THERMOSTAT
Ⓜ	ROOM HUMIDISTAT
Ⓟ	PRESSURE SENSOR
Ⓢ	ROOM SENSOR
Ⓢ	DUCT SMOKE DETECTOR
Ⓢ	TEMPERATURE ELEMENT

ACTUATORS

M	MOTOR (ELECTRIC)
P	PNEUMATIC
S	SOLENOID

GENERAL NOTES:

- CONTRACT DOCUMENT DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED TO CONVEY SCOPE AND GENERAL ARRANGEMENT ONLY.
- PROVIDE ALL MATERIALS AND EQUIPMENT AND PERFORM ALL LABOR TO INSTALL COMPLETE AND OPERABLE MECHANICAL SYSTEMS AS INDICATED ON THE DRAWINGS, AS SPECIFIED, AND AS REQUIRED BY CODE.
- ALL MECHANICAL WORK SHALL BE COORDINATED WITH ALL TRADES TO ELIMINATE ANY CONFLICTS BETWEEN PIPING, DUCTWORK, ELECTRICAL WORK, ETC. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DUCTWORK AND PIPE OFFSETS REQUIRED FOR COMPLETE SYSTEM INSTALLATION.
- CONTRACTOR SHALL PROVIDE ALL MECHANICAL EQUIPMENT AND APPURTENANCES IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, CONTRACT DOCUMENTS, AND APPLICABLE CODES AND REGULATIONS.
- COORDINATE ALL EQUIPMENT CONNECTIONS WITH MANUFACTURER'S CERTIFIED SHOP DRAWINGS. COORDINATE AND PROVIDE ALL DUCTWORK TRANSITIONS REQUIRED FOR FINAL EQUIPMENT CONNECTIONS. FIELD VERIFY AND COORDINATE ALL DUCTWORK AND PIPING DIMENSIONS PRIOR TO FABRICATION.
- LOCATE ALL TEMPERATURE, PRESSURE, AND FLOW MEASURING DEVICES AND OTHER INSTRUMENTS IN ACCESSIBLE LOCATIONS AND IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ALL EXISTING EQUIPMENT, PIPING, INSTRUMENTATION, STRUCTURE, ETC. ARE SHOWN IN APPROXIMATE LOCATIONS. CONTRACTOR SHALL FIELD VERIFY EXACT LOCATION.
- DUCT AND EQUIPMENT PENETRATIONS SHALL BE COORDINATED AS TO NOT INTERFERE WITH ROOF STRUCTURE.
- CONTRACTOR SHALL COORDINATE ROOFING AND FLASHING REQUIREMENTS FOR ALL VENT PENETRATIONS.
- LOCATE ALL VALVES, STRAINERS, UNIONS, TRAPS, FLANGES AND OTHER APPURTENANCES IN ACCESSIBLE LOCATIONS.
- INSTALL ALL PIPING SYSTEMS TO PROVIDE MINIMUM OF 3" CLEARANCE FROM ADJACENT STRUCTURE.
- ALL PIPE LOCATIONS AND ELEVATIONS ARE APPROXIMATE. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING AND NEW PIPE ROUTING AND ELEVATIONS PRIOR TO FABRICATION AND INSTALLATION.

NOT FOR CONSTRUCTION

HVAC SYMBOLS AND ABBREVIATIONS

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

DATE:	04/05/18						
REVISIONS							
ISSUE FOR BID							
NO.	A						

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES


STRAND ASSOCIATES®

SHEET
11
H0.1

NOT FOR CONSTRUCTION

GENERAL NOTES:

1. SEE SHEET H0.1 FOR ADDITIONAL GENERAL NOTES.

KEY NOTES:

- 1 DRUM LOUVERS ON RECTANGULAR DUCTWORK SHALL HAVE BLADES AT 45° ANGLE. DRUM LOUVERS ON CIRCULAR DUCTWORK SHALL BE INSTALLED AT 45° DOWN FROM HORIZONTAL. BOTTOM MOUNTED DIFFUSERS SHALL BLOW DOWN ONLY.
- 2 PROVIDE NEW MOTORIZED DAMPER, ACTUATOR, AND FILTER BOX ON NEW LOUVER.
- 3 BID ALTERNATIVE NO. 1 INCLUDES ALL FAN COIL UNITS, DUCTWORK, PIPING, VALVES, INSULATION, AND ACCESSORIES FROM BASE BID VALVES TO FAN COIL UNITS ON NEW PLATFORM.
- 4 RELOCATE VACUUM HOSE AND PROP FAN IN FRONT OF LOUVER. COORDINATE WITH OWNER ON FINAL LOCATION OF RELOCATED EQUIPMENT.
- 5 EXTEND DUCTWORK FROM LOUVER TO 3-INCHES BEYOND BRACING FOR INSTALLATION OF DAMPER AND FILTER FRAME. CAULK SEAL AROUND BRACING AND DUCTWORK.
- 6 INSTALL DRUM LOUVERS IN LOCATIONS THAT MAINTAIN DUCT HEIGHT AND DO NOT CONFLICT WITH RACEWAYS, EQUIPMENT, ETC.
- 7 OFFSET CHW PIPING TO AVOID VERTICAL STAINLESS STEEL DUCTWORK.
- 8 ROUTE DUCTWORK AS HIGH AS POSSIBLE BELOW MEZZANINE.
- 9 ROUTE DUCTWORK BELOW BEAMS. OFFSET DUCTWORK UP TO JOISTS ABOVE PROCESS EQUIPMENT AND ROUTE AS HIGH AS POSSIBLE.
- 10 FURNISH AND INSTALL SPLITTER PLATE FULL HEIGHT OF DUCT WITH REINFORCING TO PREVENT VIBRATION.
- 11 ROUTE 24 INCH ROUND DUCTWORK ON EXTERIOR WALL OF MEZZANINE. DUCTWORK ELEVATION SHALL BE EVEN WITH MEZZANINE FLOOR.
- 12 ROUTE 24 INCH DUCTWORK DOWN TO UNDERSIDE OF MEZZANINE. ROUTE DUCTWORK AS HIGH AS POSSIBLE BELOW MEZZANINE.
- 13 THIS EQUIPMENT OR MODIFICATIONS TO FANS NOTED SHALL BE PART OF BID ALTERNATIVE NO. 1.
- 14 PIPING SHALL BE ROUTED TO AVOID INTERFERENCE WITH ROOF HATCH.
- 15 FAN CONTROLS SHALL BE MODIFIED WITH PROJECT. SEE CONTROL SEQUENCES AND SHEET H8.2 FOR DIAGRAM ON CONTROLS.
- 16 MOUNT TE ON COLUMN ON SIDE AWAY FROM OVEN 42" ABOVE FINISHED FLOOR.
- 17 PROVIDE 4'-0" LONG FORKLIFT GUARDRAIL AT LOUVERS (TYP. 9 LOCATIONS).

HVAC
OVERALL FIRST FLOOR PLAN

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007



PROJECT MGR.
NICHOLAS E. SALES




SHEET
12
H1.1

DATE:	04/05/18
REVISIONS	
NO.	A

OVERALL FIRST FLOOR PLAN





GENERAL NOTES:

1. SEE SHEET H0.1 FOR ADDITIONAL GENERAL NOTES.

KEY NOTES:

- 48X24 TO 24 INCH DIAMETER TRANSITION.
- DRUM LOUVERS ON RECTANGULAR DUCTWORK SHALL HAVE BLADES AT 45° ANGLE. DRUM LOUVERS ON CIRCULAR DUCTWORK SHALL BE INSTALLED AT 45° DOWN FROM HORIZONTAL.
- RELOCATE DESK IN FRONT OF LOUVER. COORDINATE FINAL LOCATION OF DESK WITH OWNER.
- EXTEND DUCTWORK FROM LOUVER TO 3-INCHES BEYOND BRACING FOR INSTALLATION OF DAMPER AND FILTER FRAME. CAULK SEAL AROUND BRACING AND DUCTWORK. SEE H8.2 FOR LOUVER SIZES.
- ROUTE 48x24 SUPPLY DUCTWORK AS HIGH AS POSSIBLE. SUPPORT DUCTWORK FROM GIRDERS.
- OFFSET SUPPLY DUCTWORK UP TO JOISTS AND OVER TOP OF OPEN PORTION OF OVEN. SUPPORT DUCTWORK FROM JOISTS.
- OFFSET 24-INCH DIAMETER DUCTWORK UP AND ROUTE ABOVE EXISTING STAINLESS-STEEL DUCTWORK AND OVER OPEN PORTION OF OVEN. SUPPORT DUCTWORK FROM JOISTS.
- INSTALL TOP OF TEMPERATURE CONTROL PANEL 6'-0" FROM MEZZANINE FLOOR.
- PROVIDE NEW MOTORIZED DAMPER, ACTUATOR, AND FILTER BOX ON NEW LOUVER.
- ROUTE COOLING COIL CONDENSATE TO DRAIN LOCATED AT EXISTING CHILLED WATER PUMPING AREA. SEE SHEET H1.2 FOR CONTINUATION.
- FAN CONTROLS SHALL BE MODIFIED WITH PROJECT. SEE CONTROL SEQUENCES AND SHEET H8.1 FOR DIAGRAM ON CONTROLS.
- MOUNT OAT ON WALL 6'-0" ABOVE PLANT FIRST FLOOR.
- MOUNT TE ON COLUMN ON SIDE AWAY FROM OVEN 42" ABOVE FINISHED FLOOR.
- PROVIDE 4'-0" LONG FORKLIFT GUARDRAIL AT LOUVERS (TYP. 4 LOCATIONS).

NOT FOR CONSTRUCTION

HVAC MEZZANINE PLAN


PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES




SHEET
13
H1.2




KEY PLAN
NO SCALE


NOT FOR
CONSTRUCTION



SECTION 1
H3.1
0 1' 2' 4' 8'



SECTION 2
H3.1
0 1' 2' 4' 8'



TYPICAL FAN COIL ISOMETRIC
(3-WAY CONTROL VALVE) (BID ALTERNATIVE NO. 1)
NO SCALE

NO.	REVISIONS	DATE:	
		04/05/18	
A	ISSUE FOR BID		


HVAC
SECTIONS

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007
PROJECT MGR.
NICHOLAS E. SALES



SHEET
14
H3.1



GENERAL NOTES:

1. SEE SHEET H0.1 FOR ADDITIONAL GENERAL NOTES.

KEY NOTES:

- (1) SUPPORT EQUIPMENT SEPARATE FROM PIPING.
- (2) INSTALL CHWP-01 AND CHWP-02 ON FLOOR MOUNTED FRAME 6'-6" AND 3'-0" ABOVE FINISHED FLOOR, RESPECTIVELY.
- (3) PROVIDE FLEXIBLE CONNECTION AND COORDINATE CONNECTION SIZES AND LOCATION WITH CHILLER MANUFACTURER.
- (4) INSTALL OWNER FURNISHED CHILLER ON CONCRETE EQUIPMENT PAD PER MANUFACTURERS REQUIREMENTS. SEE STRUCTURAL PLANS FOR ADDITIONAL INSTALLATION DETAILS. UNLOAD FOR TRUCK. SET IN OWNER PREFERRED LOCATION UNTIL PAD IS PREPARED. PICK UP AND SET IN FINAL LOCATION.
- (5) PROVIDE PIPING SUPPORTS AS NECESSARY. SEE STRUCTURAL PLANS FOR DETAILS.
- (6) INSTALL TOP OF TEMPERATURE CONTROL PANEL 6'-0" ABOVE FINISHED FLOOR.
- (7) FORKLIFT GUARDRAIL (H S5.2).
- (8) EXTERIOR PIPE SUPPORT @ 10'-0" O.C. MAX. (J S5.2).
- (9) FLOW SWITCH PROVIDED BY CHILLER MANUFACTURER.

NOT FOR CONSTRUCTION

HVAC
ENLARGED PLAN - 1


PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES



SHEET
15
H4.1



KEY PLAN
NO SCALE


NOT FOR CONSTRUCTION

GENERAL NOTES:


- SEE SHEET H0.1 FOR ADDITIONAL GENERAL NOTES
- ALL WORK SHOWN ON THIS SHEET SHALL BE PART OF BID ALTERNATIVE NO. 1.

KEY NOTES:

- INSTALL OWNER FURNISHED FAN COIL UNIT ON NEW PLATFORM. SEE STRUCTURAL SHEETS FOR ADDITIONAL PLACEMENT INFORMATION.
- 3" CHW TO FCU. FOUR CONNECTIONS TOTAL.
- SEE SHEET H3.1 FOR CHILLED WATER PIPING CONFIGURATION. PIPING SHALL BE ROUTED IN SUCH A WAY TO ALLOW FULL COIL PULL AREA ACCESS WITH MINIMAL PIPE REMOVAL.
- 4" CHW DOWN TO PLATFORM. SEE SHEET H1.1 FOR CONTINUATION.
- ROUTE CONDENSATE COIL DRAINS FROM FAN COIL UNIT UNDERNEATH PLATFORM. TIE DRAINS TOGETHER AND ROUTE DOWN INSIDE EXTERIOR WALL TO GRADE.
- EXTEND EXISTING FIRE PROTECTION SERVICE BELOW NEW PLATFORM. SEE SPECIFICATION SECTION 21 00 01 FOR DETAILS.
- INSTALL TOP OF TEMPERATURE CONTROL PANEL 6'-0" FROM PLATFORM FLOOR.
- DOOR SWITCH SHALL BE ALLEN BRADLEY MODEL 440G-T47047, OR EQUAL.



ENLARGED PLAN - 2



KEY PLAN
NO SCALE

HVAC
ENLARGED PLAN - 2

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES




SHEET
16
H4.2


GENERAL NOTES:
1. SEE SHEET H0.1 FOR ADDITIONAL GENERAL NOTES.

- KEY NOTES:
- 3" CHW TO FCU. TWO CONNECTIONS TOTAL.
 - EXTEND DUCTWORK FROM LOUVER TO 3-INCHES BEYOND BRACING FOR INSTALLATION OF DAMPER AND FILTER FRAME. CAULK SEAL AROUND BRACING AND DUCTWORK.
 - INSTALL OWNER FURNISHED FCU. BOTTOM OF FCU SHALL BE 18'-6" AFF. PROVIDE VIBRATION ISOLATION.
 - ROUTE 24 INCH ROUND DUCTWORK DOWN BETWEEN STAINLESS STEEL DUCTS TO SPACE UNDERNEATH MEZZANINE. ROUTE DUCTWORK AS HIGH AS POSSIBLE BELOW MEZZANINE.
 - 3-INCH CHW TAPS TO MEZZANINE. CHW TO PENETRATE NEW MEZZANINE WALL 28'-0" ABOVE FINISHED FLOOR. SEAL WALL PENETRATION. SEE SHEET H4.4 FOR CONTINUATION.
 - SEE SHEET H1.1 FOR CONTINUATION.
 - ROUTE COOLING COIL CONDENSATE DRAIN UNDERNEATH UNIT TO WALL. ROUTE DRAIN DOWN AND OUT EXTERIOR WALL TO GRADE.


- KEY NOTES (CONT'D):
- 48x30 TO 48x24 TRANSITION ELBOW. 48x24 DOWN MEZZANINE WALL TO BELOW MEZZANINE. ROUTE DUCTWORK AS HIGH AS POSSIBLE BELOW MEZZANINE.
 - PROVIDE 24-INCH ROUND TAKEOFF TO BOTTOM OF MEZZANINE UPSTREAM OF VERTICAL TRANSITION.
 - 48x24 TO 24 INCH ROUND TRANSITION IN VERTICAL.
 - PROVIDE 3 INCH CHW TAKE OFFS DOWN TO 26'-0" AFF.
 - ROUTE COOLING COIL CONDENSATE DRAIN TO EXISTING DRAIN PIPE LOCATED AT WATER HEATER.
 - PROVIDE NEW MOTORIZED DAMPER, ACTUATOR, AND FILTER BOX ON NEW LOUVER.
 - 3" CHW TAPS DOWN TO 20'-0" ABOVE FINISHED FLOOR. STACK CHW LINES. RETURN LINE SHALL BE ON THE BOTTOM.
 - EXTEND EXISTING FIRE PROTECTION SERVICE BELOW NEW FCU.
 - DOOR SWITCH SHALL BE ALLEN BRADLEY MODEL 440G-T47047, OR EQUAL.



ENLARGED PLAN
0 1' 2' 4' 8'



ENLARGED PLAN
0 1' 2' 4' 8'



KEY PLAN
NO SCALE

HVAC
ENLARGED PLANS - 3
PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007
PROJECT MGR.
NICHOLAS E. SALES




SHEET
17
H4.3

1. SEE SHEET H0.1 FOR ADDITIONAL GENERAL NOTES.



- ① INSTALL OWNER FURNISHED FCU. BOTTOM OF FCU SHALL BE 10'-0" FROM MEZZANINE FLOOR. PROVIDE VIBRATION ISOLATION.
- ② 3" CHW TO FCU. TWO CONNECTIONS TOTAL.
- ③ 3" CHW INTO MEZZANINE FROM MAIN FLOOR. SEE SHEET HA4.3 FOR CONTINUATION.
- ④ CHWR ONLY DOWN TO 6' ABOVE MEZZANINE FLOOR. STACK CHWS (TOP) AND CHWR (BOTTOM) ON WALL.
- ⑤ INSTALL TCV 6'-0" ABOVE MEZZANINE FLOOR.
- ⑥ CHW UP TO 14'-0" ABOVE MEZZANINE FLOOR.
- ⑦ ROUTE COOLING COIL CONDENSATE TO DRAIN LOCATED AT EXISTING CHILLED WATER PUMPING AREA. SEE SHEET H1.2 FOR CONTINUATION.
- ⑧ ROUTE COOLING COIL CONDENSATE DRAIN UNDERNEATH UNIT TO WALL. ROUTE DRAIN DOWN AND OUT EXTERIOR WALL TO GRADE.

- ⑨ EXTEND DUCTWORK FROM LOUVER TO 3-INCHES BEYOND BRACING FOR INSTALLATION OF DAMPER AND FILTER FRAME. CAULK SEAL AROUND BRACING AND DUCTWORK.
- ⑩ 48x30 FROM CONNECTION ON UNIT TO 48x24 TRANSITION.
- ⑪ PROVIDE NEW MOTORIZED DAMPER, ACTUATOR, AND FILTER BOX ON NEW LOUVER.
- ⑫ EXTEND EXISTING FIRE PROTECTION SERVICE BELOW NEW FCU.
- ⑬ DOOR SWITCH SHALL BE ALLEN BRADLEY MODEL 440G-T47047, OR EQUAL.
- ⑭ 48X30 SA FROM UNIT BELOW STRUCTURAL SUPPORT. IMMEDIATELY OFFSET DUCTWORK UP AS HIGH AS POSSIBLE.


NOT FOR CONSTRUCTION



ENLARGED MEZZANINE PLAN



ENLARGED MEZZANINE PLAN



KEY PLAN
NO SCALE

NO.	ISSUE FOR BID	REVISIONS	DATE
A			04/05/18

HVAC ENLARGED PLANS - 4

CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES



SHEET
18
H4.4

AIR COOLED CHILLER SCHEDULE

AIR COOLED CHILLER SCHEDULE																													
UNIT NO. ACC—	LOCATION	SERVICE	YORK MODEL NO.	NOMINAL CAPACITY (TONS)	OUTDOOR FANS			EVAPORATOR SECTION							COMPRESSORS				ELECTRICAL						EER	NPLV	OPERATING WEIGHT (LBS.)	REMARKS	
					NOMINAL AIRFLOW (CFM)	NO. OF FANS	FAN DIA. (IN.)	EWT (°F)	LWT (°F)	COOLING MEDIUM	MAX FLOW (GPM)	MIN. FLOW (GPM)	DESIGN FLOW (GPM)	GLYCOL P.D. (FT. HD.)	CONNECTION SIZE (IN)	NO. OF CIRCUITS	NO. OF COMPRESSORS	COMPRESSOR TYPE	REFRIGERANT TYPE	VOLTAGE	PHASE	FLA	MCA	BREAKER SIZE					DISCONNECT BY
01	EXTERIOR	FAN COILS	YVAA0345EXV46BAVNXX	300	VARIES	20	36	58	42	30% PROPYLENE GLYCOL	1062	269.5	477	19.5	10	2	2	SCREW	R134A	460	3	569	700	700A	MFR	9.797	18.35	21,932	①

① UNIT SHALL BE OWNER FURNISHED, CONTRACTOR INSTALLED.

FAN COIL SCHEDULE

FAN COIL SCHEDULE																							
UNIT NO. FCU—	LOCATION	SERVICE	YORK MODEL NO.	UNIT CONFIGURATION	FAN SECTION			COOLING COIL SECTION								ELECTRICAL				OPERATING WEIGHT (LBS)	REMARKS		
					SUPPLY AIR (CFM)	ESP (IN. W.C.)	MOTOR SIZE (HP)	COOLING MEDIUM	TOTAL CAPACITY (MBH)	SENSIBLE CAPACITY (MBH)	EAT DB/WB (°F)	LAT DB/WB (°F)	EWT (°F)	LWT (°F)	FLOWRATE (GPM)	WPD (FT.)	VOLTS	PHASE	FLA			BREAKER SIZE	
01	FIRST FLOOR NORTH	FIRST FLOOR NORTH	SOLUTION XT	HORIZONTAL	16,000	1.25	15	30% PROPYLENE GLYCOL	520.2	384.7	80/67	57/56.2	42	58.3	67.2	11.2	460	3	23	40A	3,796	①②	
02	FIRST FLOOR NORTH	FIRST FLOOR NORTH	SOLUTION XT	HORIZONTAL	16,000	1.25	15	30% PROPYLENE GLYCOL	520.2	384.7	80/67	57/56.2	42	58.3	67.2	11.2	460	3	23	40A	3,796	①②	
03	MEZZANINE	MEZZANINE	SOLUTION XT	HORIZONTAL	16,000	0.75	15	30% PROPYLENE GLYCOL	520.2	384.7	80/67	57/56.2	42	58.3	67.2	11.2	460	3	23	40A	3,983	①②	
04	MEZZANINE	MEZZANINE	SOLUTION XT	HORIZONTAL	16,000	0.75	15	30% PROPYLENE GLYCOL	520.2	384.7	80/67	57/56.2	42	58.3	67.2	11.2	460	3	23	40A	3,983	①②	
05	PLATFORM	FIRST FLOOR SOUTH	SOLUTION XT	HORIZONTAL	40,000	1.50	50	30% PROPYLENE GLYCOL	1094.5	841.7	80/67	59.9/58.1	42	59.3	133	12.4	460	3	72	125A	7,860	①②③	
06	PLATFORM	FIRST FLOOR SOUTH	SOLUTION XT	HORIZONTAL	40,000	1.50	50	30% PROPYLENE GLYCOL	1094.5	841.7	80/67	59.9/58.1	42	59.3	133	12.4	460	3	72	125A	7,860	①②③	

① STARTER SHALL BE VFD PROVIDED BY MANUFACTURER.

② UNIT SHALL BE OWNER FURNISHED, CONTRACTOR INSTALLED.

③ UNIT SHALL BE PART OF BID ALTERNATIVE NO. 1.

EXPANSION TANK SCHEDULE

UNIT NO. ET—	LOCATION	BELL AND GOSSETT MODEL NO.	CAPACITY (GAL.)	REMARKS
01	STORAGE	B-200	53	

PUMP SCHEDULE

UNIT NO.	LOCATION	SERVICE	TYPE	AURORA MODEL NO.	FLOWRATE (GPM)	TOTAL HEAD (FT. OF WATER)	MOTOR SIZE (HP)	MOTOR SPEED (RPM)	SUCTION SIZE (IN.)	DISCHARGE SIZE (IN.)	TRIPLE DUTY VALVE	ELECTRICAL					REMARKS
												VOLTS	PHASE	STARTER BY	STARTER TYPE	DISCONNECT BY	
CHWP-01	STORAGE	CHW	INLINE	380-4x4x12	550	130	30	1,760	4	4	YES	480	3	DIV. 40	VFD	DIV. 26	①
CHWP-02	STORAGE	CHW	INLINE	380-4x4x12	550	130	30	1,760	4	4	YES	480	3	DIV. 40	VFD	DIV. 26	①

① 30% PROPYLENE GLYCOL.

AIR SEPARATOR SCHEDULE

UNIT NO. AS—	LOCATION	SERVICE	BELL & GOSSETT MODEL NO.	WATER FLOW (GPM)	CONNECTION SIZE (IN.)	STRAINER	REMARKS
01	STORAGE	CHW	ROLAIRTROL RL-6	600	600	NO	

WALL LOUVER SCHEDULE

UNIT NO. L—	LOCATION	SERVICE	GREENHECK MODEL NO.	AIRFLOW (CFM)	WIDTH (IN)	HEIGHT (IN)	BLADE DEPTH (IN)	MAX. APD (IN WG)	MAX. FACE VEL. (FPM)	FREE AREA (SQ. FT.)	SCREEN		TOP ELEVATION	REMARKS
											TYPE	LOCATION		
01	FIRST FLOOR NORTH	FIRST FLOOR NORTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②
02	FIRST FLOOR NORTH	FIRST FLOOR NORTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②
03	FIRST FLOOR NORTH	FIRST FLOOR NORTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②
04	FIRST FLOOR NORTH	FIRST FLOOR NORTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②
05	FIRST FLOOR NORTH	FIRST FLOOR NORTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②
06	MEZZANINE	MEZZANINE	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②
07	MEZZANINE	MEZZANINE	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②
08	MEZZANINE	MEZZANINE	ESD-635	—	60	60	6	—	—	15.02	NONE	—	—	①②
09	MEZZANINE	MEZZANINE	ESD-635	—	60	60	6	—	—	15.02	NONE	—	—	①②
10	MEZZANINE	MEZZANINE	ESD-635	—	60	60	6	—	—	15.02	NONE	—	—	①②
11	FIRST FLOOR SOUTH	FIRST FLOOR SOUTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②③
12	FIRST FLOOR SOUTH	FIRST FLOOR SOUTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②③
13	FIRST FLOOR SOUTH	FIRST FLOOR SOUTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②③
14	FIRST FLOOR SOUTH	FIRST FLOOR SOUTH	ESD-635	—	48	84	6	—	—	17.76	NONE	—	—	①②③

① NEW LOUVER SHALL BE INSTALLED IN EXISTING LOCATION.

② CONTRACTOR TO FIELD VERIFY ALL LOUVER SIZES AND LOCATIONS.

③ UNIT SHALL BE PART OF BID ALTERNATIVE NO. 1.

UNIT SOUND POWER SCHEDULE

UNIT	TYPE	OCTAVE BAND (HZ)								REMARKS
		63	125	250	500	1000	2000	4000	8000	
FCU-01	RADIATED	89	86	92	90	87	83	80	79	
FCU-02	RADIATED	89	86	92	90	87	83	80	79	
FCU-03	RADIATED	91	87	92	89	87	83	80	79	
FCU-04	RADIATED	91	87	92	89	87	83	80	79	
FCU-05	RADIATED	85	84	92	80	79	82	70	57	
FCU-06	RADIATED	85	84	92	80	79	82	70	57	
ACC-01	RADIATED	99	99	100	103	99	94	90	87	

DESIGN CONDITIONS

APPLICABLE BUILDING CODE: 2009 INTERNATIONAL BUILDING CODE				SUMMER EXTERIOR: 97°F DB / 75°F WB WINTER EXTERIOR: 17°F DB		
OCCUPANCY TYPE	VENTILATION		SUMMER INTERIOR (DB/WB)		WINTER INTERIOR (DB)	REMARKS
FIRST FLOOR	COOLING		80/67		80/67	
MEZZANINE	COOLING		80/67		80/67	

NOT FOR
CONSTRUCTION

HVAC
SCHEDULES

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.

3626.007

PROJECT MGR.

NICHOLAS E. SALES



STRAND
ASSOCIATES®

SHEET

21


H6.1

DATE:	04/05/18					
REVISIONS						
NO.	A					
ISSUE FOR BID						

CONSTRUCTION

GENERAL SYSTEM INFORMATION:

1. UTILIZE EXISTING VENTILATION SYSTEM (243,000 CFM, 6.4 ACH) WHEN EXTERIOR CONDITIONS ARE ACCEPTABLE (~6,500 HOURS PER YEAR). ADD NEW FILTERS AND DAMPERS ON INTAKES (243,000 CFM). CLOSE DAMPERS AND SHUT FANS OFF WHEN EXTERIOR CONDITIONS ARE NOT ACCEPTABLE.
2. PROVIDE FAN COIL UNITS COOLING BY AIR COOLED CHILLER FOR GENERAL PRODUCTION FLOOR AREA AND MEZZANINE AREAS WHEN EXTERIOR CONDITIONS EXCEED ECONOMIZING (~2,000 HOURS PER YEAR).
3. FAN COIL UNITS FANS OPERATE ALL YEAR TO CIRCULATE AIR.
4. UTILIZE LOCAL EXISTING PROPELLER FANS ALL YEAR TO CIRCULATE AIR.



HVAC PROCESS FLOW DIAGRAM – FAN COIL UNITS
NO SCALE

HVAC
PROCESS FLOW DIAGRAM
PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007
PROJECT MGR.
NICHOLAS E. SALES



SHEET
22
H7.1

NOT FOR
CONSTRUCTION

DATE:	04/05/18								
REVISIONS									
NO.	A								
ISSUE FOR BID									

HVAC
PROCESS FLOW DIAGRAM


PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES




SHEET
23
H7.2



HVAC PROCESS FLOW DIAGRAM - 2
NO SCALE

NOT FOR
CONSTRUCTION




TYPICAL FCU CONTROL SCHEMATIC

NO SCALE

FCU 01-04 - BASE BID (IN TCP-01)

FCU 05, 06 - BID ALTERNATE #1 (IN TCP-03)



CHILLED WATER CONTROL SCHEMATIC

NO SCALE

HVAC
CONTROLS DIAGRAMS - 1

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

NO.	REVISIONS	DATE:
A	ISSUE FOR BID	04/05/18

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES

SA
STRAND
ASSOCIATES®

SHEET
24
H8.1

ELECTRICAL ABBREVIATIONS














AMPERE	AMPERE
AV	AUDIO VISUAL
AF	AMPERE FRAME
AFM	AIR FLOW METER
AHJ	AUTHORITY HAVING JURISDICTION
AIC	AMPERE INTERRUPTING CAPACITY
AL	ALUMINUM
AT	AMPERE TRIP
ATS	AUTOMATIC TRANSFER SWITCH
AWG	AMERICAN WIRE GAUGE
C	CONDUIT
CATV	CABLE TELEVISION
CB	CIRCUIT BREAKER
CCTV	CLOSED CIRCUIT TELEVISION
CKT	CIRCUIT
CR	CARD READER
CS	CONTROL STATION
CT	CURRENT TRANSFORMER
CU	COPPER
DC	DIRECT CURRENT
DISC	DISCONNECT
DM	DENSITY METER
DO	DISSOLVED OXYGEN DEVICE
DP	DOOR POSITION SWITCH
DT	DIFFERENTIAL PRESSURE TRANSDUCER
E	EMERGENCY
EMS	EMERGENCY STOP
EMT	ELECTRICAL METALLIC TUBING
EOL	END OF LINE DEVICE
ES	ELECTRIC STRIKE
FAAP	FIRE ALARM ANNUNCIATOR PANEL
FACP	FIRE ALARM CONTROL PANEL
FIT	FLOW INDICATING TRANSMITTER
FLA	FULL LOAD AMPERES
FLS	FLOW SWITCH
FM	FLOW METER
FP	FIRE PUMP CONTROL PANEL
FS	FLOAT SWITCH
FT	FEET
FVNR	FULL VOLTAGE NON-REVERSING
FVR	FULL VOLTAGE REVERSING
GFI	GROUND FAULT INTERRUPTER
GFM	GAS FLOW METER
GFP	GROUND FAULT PROTECTION (EQUIPMENT)
GRD	GROUND
GRS	GALVANIZED RIGID STEEL
HOA	HAND OFF AUTO
HP	HORSEPOWER
HV	HIGH VOLTAGE
HZ	HERTZ
IG	ISOLATED GROUND
IMC	INTERMEDIATE METAL CONDUIT
J	JUNCTION BOX
KVA	KILOVOLT AMPERES
KVAR	KILOVOLT AMPERES REACTIVE
KW	KILOWATT
LIT	LEVEL INDICATING TRANSMITTER
LP	LIGHTING PANEL
LTG	LIGHTING
LV	LOW VOLTAGE
MATV	MASTER ANTENNA TELEVISION
MC	METAL CLAD
MCB	MAIN CIRCUIT BREAKER
MCC	MOTOR CONTROL CENTER
MCCB	MOLDED CASE CIRCUIT BREAKER
MCM	THOUSAND CIRCULAR MILS
MCP	MOTOR CIRCUIT PROTECTOR
MDP	MAIN DISTRIBUTION PANELBOARD
MF	MAGNETIC FLOW METER
ML	MAGNETIC LOCK
MLO	MAIN LUGS ONLY
MO	MOTOR OPERATED
MS	MOTION SENSOR
MSB	MAIN SWITCHBOARD
MTS	MANUAL TRANSFER SWITCH
MV	MEDIUM VOLTAGE

ELECTRICAL ABBREVIATIONS

IA	NOT APPLICABLE
NAC	NOTIFICATION APPLIANCE CIRCUIT PANEL
NC	NORMALLY CLOSED
NEC	NATIONAL ELECTRIC CODE
NM	NONMETALLIC
NO	NORMALLY OPEN
NTS	NOT TO SCALE
ø	PHASE
OCB	OIL CIRCUIT BREAKER
OL	OVERLOAD
OS	OCCUPANCY SENSOR
OT	OVERTEMP
P	POLE
PB	PULL BOX
PC	PULL CORD
PH	PH SENSOR
PNL	PANELBOARD
PR	PAIR
PRI	PRIMARY
PS	PRESSING SWITCH
PT	PRESSURE TRANSDUCER
PTF	POTENTIAL TRANSFORMER
PVC	POLYVINYL CHLORIDE
PWR	POWER
RE	REQUEST TO EXIT
RTS	REMOTE TEST SWITCH
RVSS	REDUCED VOLTAGE SOLID STATE
SC	SHORT CIRCUIT
SCADA	SUPERVISORY CONTROL AND DATA ACQUISITION
SCC	SUPERVISORY CONTROL CENTER
SE	SERVICE ENTRANCE
SEC	SECONDARY
SH	SHIELDED
SPD	SURGE PROTECTION DEVICE
SPT	SUBMERSIBLE PRESSURE TRANSDUCER
SS	STAINLESS STEEL
SV	SOLENOID VALVE
SW	SWITCH
TEL	TELEPHONE
T	THERMOSTAT
TS2W	TWO SPEED TWO WINDING
TYP	TYPICAL
UFM	ULTRANSONIC FLOW METER
UG	UNDERGROUND
ULT	ULTRANSONIC LEVEL TRANSMITTER
UPS	UNINTERRUPTIBLE POWER SUPPLY
UTP	UNSHIELDED TWISTED PAIR
V	VOLTS
VFD	VARIABLE FREQUENCY DRIVE
W	WIRE OR WATT
WP	WEATHERPROOF
WT	SCALE
XFMR	TRANSFORMER
XP	EXPLOSION PROOF

ELECTRICAL SYMBOLS







































LIGHTING

	FIXTURE SYMBOL (TYPICAL) A—INDICATES FIXTURE TYPE 2—INDICATES CIRCUIT NUMBER b—INDICATES SWITCHING SOLID CIRCLE INDICATES ALWAYS ON
	INCANDESCENT, LED, HID, SURFACE OR PENDANT
	INCANDESCENT, LED, HID, WALL
	1X4 FLUORESCENT, SURFACE OR PENDANT
	1X8 FLUORESCENT, SURFACE OR PENDANT
	FLUORESCENT, WALL
	1X4 FLUORESCENT, RECESSED
	2X2 FLUORESCENT, RECESSED
	2X4 FLUORESCENT, RECESSED
	CAN, FLUORESCENT, LED, OR HID
	EXIT, SURFACE, PENDANT OR RECESSED
	EXIT, WALL
	EMERGENCY LIGHTING
<u>SWITCHES</u>	
\$	SINGLE POLE
\$ ₂	TWO POLE
\$ ₃	THREE WAY
\$ ₄	FOUR WAY
\$ _K	KEYED
\$ _D	DIMMER
\$ _M	MANUAL MOTOR SWITCH (3 PHASE)
\$ _{WP}	WEATHER PROOF
\$ _P	SWITCH WITH PILOT LIGHT
(LC)	LIGHTING CONTROL STATION
(R3)	LOCKOUT STOP SWITCH
(DP)	DOOR POSITION SWITCH
(PC)	PHOTOCELL











POWER SYMBOLS

	CIRCUIT NUMBER (TYPICAL)
	OTHERWISE SHOWN PANEL DESIGNATION (TYP.)
	DUPLEX, 125 VOLT, WP
	INDICATES WEATHERPROOF
	DUPLEX, 125 VOLT, ABOVE FURNITURE
	DOUBLE DUPLEX, 125 VOLT, ABOVE FURNITURE
	DOUBLE DUPLEX, 125 VOLT
	SINGLE CONVENIENCE, 125 VOLT FOR ELECTRIC WATER COOLER
	EXPLOSION-PROOF, ABOVE FURNITURE
	EXPLOSION-PROOF
	FIXED EQUIPMENT CONNECTION
	POWER OUTLET, VOLTAGE & AMPERAGE AS INDICATED
	AUTOMATIC TRANSFER SWITCH (ONE-LINE DIAGRAM)
	CIRCUIT BREAKER (ONE-LINE DIAGRAM)
	METER (ONE-LINE DIAGRAM)
	PANELBOARD


INSTRUMENTATION EQUIPMENT

	ANALYSIS ELEMENT
 *	ANALYSIS INDICATING TRANSMITTER, *: DO=DISSOLVED OXYGEN, PH=PH, TRB=TURBIDITY, TSS=TOTAL SUSPENDED SOLIDS, GD=GAS DETECTOR, CA=CHLORINE ANALYZER, OP=OXYGEN PURITY, LEL=LOWER EXPLOSIVE LIMIT, PR=PROXIMITY, MST=MOISTURE
 1,2	CONTROL SWITCH DEVICE TYPE (SEE MCC SCHEDULE)
	DENSITY ELEMENT
	DENSITY INDICATING TRANSMITTER
	FLOW ELEMENT
 *	FLOW INDICATING TRANSMITTER, *: M=MAGNETIC, TM= THERMAL MASS DP=DIFFERENTIAL PRESSURE, U=ULTRASONIC
 *	FLOW SWITCH *: P=PADDLE, T=THERMAL, C=CAPACITANCE, A=AIR FLOW
 *	HAND SWITCH *: SS=SAFETY SWITCH
	POWER ELEMENT (CURRENT XFMR, POTENTIAL XFMR)
	CURRENT SWITCH
	POWER INDICATING TRANSMITTER
	TIME SWITCH
	LEVEL ELEMENT
 *	LEVEL INDICATING TRANSMITTER, *: S=SUBMERSIBLE, U=ULTRASONIC, R=RADAR, TL=TANK LEVEL/RING PRESSURE TYPE
 *	LEVEL SWITCH, *: C=CONDUCTANCE, F=BALL FLOAT, V=VIBRATING FORK, B=BUILDING FLOODING
	DIFFERENTIAL PRESSURE INDICATING TRANSMITTER
	PRESSURE ELEMENT
	PRESSURE INDICATING TRANSMITTER
	PRESSURE SWITCH
	SPEED SWITCH
	TEMPERATURE CONTROLLER
 *	TEMPERATURE ELEMENT, *: R=RTD, T=THERMOCOUPLE
	TEMPERATURE INDICATING TRANSMITTER
	TEMPERATURE CONTROL STATION
	TEMPERATURE SWITCH
	TEMPERATURE TRANSMITTER
	VIBRATION ELEMENT
	VIBRATION INDICATING TRANSMITTER
	WEIGHT ELEMENT
	WEIGHT INDICATING TRANSMITTER
	TORQUE SWITCH
	WEIGHT TRANSMITTER (SCALE)
	PRESENCE/ABSENCE DETECTOR
 *	POSITION SWITCH, *: D=DOOR, L=LIMIT, P=PROXIMITY
	SOLENOID VALVE
	GAS DETECTION SYSTEM HORN; WALL MOUNT
	GAS DETECTION SYSTEM STROBE; WALL MOUNT


























EQUIPMENT AND WIRING

	GROUND ROD CONNECTION (ONE-LINE DIAGRAM)
	TRANSFORMER
	DISCONNECT, F=FUSED, B=CIRCUIT BREAKER, BLANK=NON-FUSED
	MOTOR STARTER MAGNETIC
	CIRCUIT BREAKER COMBINATION STARTER
	JUNCTION BOX
	LINE VOLTAGE THERMOSTAT
	LINE VOLTAGE THERMOSTAT W/REMOTE BULB
	480V LOAD, REFER TO MCC SCHEDULE FOR EQUIPMENT NUMBER
	VARIABLE FREQUENCY DRIVE

SITE SYMBOLS

— E —	UNDERGROUND ELECTRIC
— OH —	OVERHEAD ELECTRIC
— C —	CABLE TELEVISION SERVICE
— T —	TELEPHONE SERVICE
— FO —	FIBER OPTIC CABLE
	UTILITY POLE

TECHNOLOGY SYMBOLS

	DATA JACK
	PHONE JACK
	POTS ANALOG PHONE AND DATA JACKS * = # OF JACKS
	WALL MOUNT VOIP PHONE JACK 54" AFF
	WALL MOUNT POTS ANALOG PHONE JACK 54" AFF
	SCADA NETWORK JACK
	DATA RACK
	COAX CABLE
	POWER POLE
	PA SYSTEM HORN SPEAKER; 10'-0" AFF
	PA SYSTEM SPEAKER
	KEY PAD
	GLASS BREAK DETECTOR
	MOTION SENSOR
	PUSH BUTTON
	ELECTRIC STRIKE
	MAGNETIC LOCK
	INTERCOM STATION
	DOOR SWITCH
	OCCUPANCY SENSOR
	SEE SCHEDULE FOR SENSOR TYPE CARD READER
	REMOTE VOLUME CONTROL
	PA SPEAKER; CEILING MOUNT * = SPEAKER TYPE # = WATTAGE TAP
	FIXED SECURITY CAMERA
	PAN, TILT, ZOOM SECURITY CAMERA

SECTION (ONE-LINE

[illegible]

ELECTRICAL SYMBOLS AND ABBREVIATIONS

**PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS**

JOB NO.
3626.007
PROJECT MGR.
NICHOLAS E. SALES



SHEET
26
E0.1


⑫ PROVIDE SINGLE GANG BOX FOR DEVICE.

SHEET
27
E1.1



NOT FOR
CONSTRUCTION

KEY NOTES:

- 1 PROVIDE CAT6 CABLE IN 3/4" CONDUIT FROM TCP-01 TO NETWORK HUB. COORDINATE TERMINATION LOCATION WITH OWNER.
- 2 REFER TO THE TEMPERATURE CONTROLS SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH THIS DEVICE.
- 3 EQUIPMENT PROVIDED AS SPECIFIED IN DIVISION 23 AND WIRED BY DIVISION 26. COORDINATE LOCATION OF EQUIPMENT WITH DIVISION 23.
- 4 PROVIDE SINGLE GANG BOX FOR DEVICE.



MEZZANINE PLAN
0 4' 8' 16' 32'



KEY PLAN
NO SCALE

DATE:	04/05/18
REVISIONS	
NO.	A

ELECTRICAL
MEZZANINE PLAN

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS


JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES





SHEET
28
E1.2

NOT FOR CONSTRUCTION



PARTIAL FIRST FLOOR PLAN



GENERAL NOTES:

1. PROVIDE UPDATED, TYPED PANEL SCHEDULE IN EACH PANELBOARD WHERE WORK IS DONE AS PART OF THIS PROJECT.

KEY NOTES:

- ① PROVIDE 4-20A, SINGLE-POLE CIRCUIT BREAKERS IN EXISTING SPACE WITHIN PANEL L1, FOR 120V POWER TO THE GLYCOL FILL STATION, RECEPTACLES, TCP-02, AND LIGHT FIXTURES AT ACC-01, LOCATED WHERE SHOWN ON DRAWING 4.2. PANEL L1 IS A SIEMENS IIE SERIES, SERIES 8, 120/108V, 100A, 3-PHASE, 4-WIRE PANELBOARD. CATALOG NO. 17-05541-F003, MANUFACTURED 06-1990, LOCATION S.
- ② ACC-01 SHALL BE POWERED FROM MAIN SWITCHGEAR. REFER TO DRAWING 5.1 FOR ADDITIONAL INFORMATION.

[illegible]

ELECTRICAL ENLARGED UTILITY ROOM PLAN


PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007


PROJECT MGR.
NICHOLAS E. SALES




SHEET
29
E4.1



KEY PLAN
NO SCALE





GENERAL NOTES:
1. REFER TO DRAWING E1.1 FOR PANEL L1 LOCATION.

- KEY NOTES:
- 1 REFER TO TEMPERATURE CONTROLS SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH THIS DEVICE.
 - 2 VFD FURNISHED AS SPECIFIED IN DIVISION 40 AND INSTALLED AND WIRED BY DIVISION 26.
 - 3 PROVIDE A NEMA 4X PULL BOX, SIZED AS REQUIRED, FOR FEED TO ACC-01.
 - 4 REFER TO THE FEEDER CONDUIT AND WIRE SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH EQUIPMENT.
 - 5 EQUIPMENT PROVIDED AS SPECIFIED IN DIVISION 23 AND WIRED BY DIVISION 26. COORDINATE LOCATION OF EQUIPMENT WITH DIVISION 23.

NOT FOR CONSTRUCTION

ELECTRICAL
ENLARGED PLAN - 1


PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

NO.	REVISIONS	DATE:
A	ISSUE FOR BID	04/05/18


JOB NO.
3626.007
PROJECT MGR.
NICHOLAS E. SALES



SHEET
30
E4.2




NOT FOR CONSTRUCTION



ENLARGED PLAN
0 1' 2' 4' 8'

- GENERAL NOTES:**
1. ALL WORK AND EQUIPMENT SHOWN ON THIS DRAWING SHALL BE PROVIDED AS PART OF BID ALTERNATIVE NO. 1.
 2. REFER TO DRAWING E1.1 FOR PANEL L5 AND PANEL H5 LOCATIONS.

- KEY NOTES:**
- 1 REFER TO THE FEEDER CONDUIT AND WIRE SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH EQUIPMENT.
 - 2 PROVIDE CONDUIT AND WIRING AS REQUIRED BETWEEN DUCT SMOKE DETECTOR AND REMOTE TEST SWITCH.
 - 3 EQUIPMENT PROVIDED AS SPECIFIED IN DIVISION 23 AND WIRED BY DIVISION 26. COORDINATE LOCATION OF EQUIPMENT WITH DIVISION 23.
 - 4 REFER TO THE TEMPERATURE CONTROLS SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH THIS DEVICE.
 - 5 DUCT SMOKE DETECTOR SHALL BE INSTALLED IN VERTICAL FACE OF DUCT. PROVIDE DETECTOR SAMPLING TUBE SUPPORT HARDWARE AS REQUIRED. PROVIDE ADDRESSABLE RELAY MODULES AS REQUIRED TO INTERFACE WITH ASSOCIATED FAN COIL UNIT. PROVIDE CONDUIT AND WIRING FROM DUCT SMOKE DETECTOR TO TCP-03 AND FROM DUCT SMOKE DETECTOR TO FIRE ALARM CONTROL PANEL LOCATED WHERE SHOWN ON DRAWING E1.1. COORDINATE TERMINATION LOCATION AT FIRE ALARM CONTROL PANEL WITH OWNER.
 - 6 MOUNT DEVICE TO HANDRAIL ON PLATFORM (EL. = 120.00) WITH GALVANIZED STEEL MOUNTING PLATE PER DETAIL C E5.1.
 - 7 RELOCATE EXISTING LIGHT FIXTURE AS REQUIRED TO ACCOMMODATE NEW MECHANICAL EQUIPMENT. ALTER AND EXTEND CONDUIT AND WIRING AS REQUIRED TO MAINTAIN EXISTING FUNCTIONALITY.
 - 8 SUFACE-MOUNT LIGHT FIXTURE TO UNDERSIDE OF PLATFORM.



KEY PLAN
NO SCALE

NO.	REVISIONS	DATE:					
			04/05/18				
A	ISSUE FOR BID						

**ELECTRICAL
ENLARGED PLAN - 2**

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES


SA STRAND ASSOCIATES®

**SHEET
31
E4.3**


NOT FOR
CONSTRUCTION

KEY NOTES:


- 1 PROVIDE CONDUIT AND WIRING AS REQUIRED BETWEEN DUCT SMOKE DETECTOR AND REMOTE TEST SWITCH.
- 2 EQUIPMENT PROVIDED AS SPECIFIED IN DIVISION 23 AND WIRED BY DIVISION 26. COORDINATE LOCATION OF EQUIPMENT WITH DIVISION 23.
- 3 REFER TO THE TEMPERATURE CONTROLS SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH THIS DEVICE.
- 4 DUCT SMOKE DETECTOR SHALL BE INSTALLED IN VERTICAL FACE OF DUCT. PROVIDE DETECTOR SAMPLING TUBE SUPPORT HARDWARE AS REQUIRED. PROVIDE ADDRESSABLE RELAY MODULES AS REQUIRED TO INTERFACE WITH ASSOCIATED FAN COIL UNIT. PROVIDE CONDUIT AND WIRING FROM DUCT SMOKE DETECTOR TO TCP-01 AND FROM DUCT SMOKE DETECTOR TO FIRE ALARM CONTROL PANEL LOCATED WHERE SHOWN ON DRAWING E1.1. COORDINATE TERMINATION LOCATION AT FIRE ALARM CONTROL PANEL WITH OWNER.
- 5 REFER TO THE FEEDER CONDUIT AND WIRE SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH EQUIPMENT.



ENLARGED PLAN
0 1' 2' 4' 8'



ENLARGED PLAN
0 1' 2' 4' 8'



KEY PLAN
NO SCALE

ELECTRICAL
ENLARGED PLANS - 3

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS


JOB NO.
3626.007
PROJECT MGR.
NICHOLAS E. SALES




SHEET
32
E4.4

NOT FOR
CONSTRUCTION


KEY NOTES:

- 1 REFER TO THE FEEDER CONDUIT AND WIRE SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH EQUIPMENT.
- 2 PROVIDE CONDUIT AND WIRING AS REQUIRED BETWEEN DUCT SMOKE DETECTOR AND REMOTE TEST SWITCH.
- 3 PROVIDE 2~40A, THREE-POLE CIRCUIT BREAKERS IN EXISTING SPACE WITHIN PANEL H4 FOR 480V POWER TO FCU-03 AND FCU-04. PANEL H4 IS A SIEMENS ITE SERIES, SERIES 7, 277/480V, 225A, 3-PHASE, 4-WIRE PANELBOARD, CATALOG NO. K442LM4225SBM, S.O. 17-05541-F011. MANUFACTURED 06-1990, LOCATION S.
- 4 EQUIPMENT PROVIDED AS SPECIFIED IN DIVISION 23 AND WIRED BY DIVISION 26. COORDINATE LOCATION OF EQUIPMENT WITH DIVISION 23.
- 5 REFER TO THE TEMPERATURE CONTROLS SCHEDULE ON DRAWING E6.1 FOR CONDUIT AND WIRING ASSOCIATED WITH THIS DEVICE.
- 6 DUCT SMOKE DETECTOR SHALL BE INSTALLED IN VERTICAL FACE OF DUCT. PROVIDE DETECTOR SAMPLING TUBE SUPPORT HARDWARE AS REQUIRED. PROVIDE ADDRESSABLE RELAY MODULES AS REQUIRED TO INTERFACE WITH ASSOCIATED FAN COIL UNIT. PROVIDE CONDUIT AND WIRING FROM DUCT SMOKE DETECTOR TO TCP-01 AND FROM DUCT SMOKE DETECTOR TO FIRE ALARM CONTROL PANEL LOCATED WHERE SHOWN ON DRAWING E1.1. COORDINATE TERMINATION LOCATION AT FIRE ALARM CONTROL PANEL WITH OWNER.
- 7 MOUNT REMOTE TEST SWITCH TO HANDRAIL WITH GALVANIZED STEEL MOUNTING PLATE PER DETAIL .
- 8 RELOCATE EXISTING LIGHT FIXTURE AS REQUIRED TO ACCOMMODATE NEW MECHANICAL EQUIPMENT. ALTER AND EXTEND EXISTING CONDUIT AND WIRING AS REQUIRED TO MAINTAIN EXISTING FUNCTIONALITY.




ENLARGED MEZZANINE PLAN

0 1' 2' 4' 8'



ENLARGED MEZZANINE PLAN

0 1' 2' 4' 8'



KEY PLAN

NO SCALE

ELECTRICAL
ENLARGED PLANS - 4


PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES



SHEET
33
E4.5



4"x6" HANDHOLE

BOLT COVER

WASHERS (TYP.)

NON-SHRINK GROUT

LEVELING NUTS (TYP.)

3/4" CHAMFER

#6 BARE COPPER GROUND WIRE CLAMPED TO GROUND ROD AND POLE SIDE

CONDUIT PROJECTION AS RECOMMENDED BY POLE MFR.

MINIMUM 36" LONG GRADE 105 THREADED ANCHOR BOLTS

HEAVY HEX NUT

#3 HOOP @ 12" O.C. (SEE NOTE 2)

6-#6 VERTICAL REINFORCING

5/8"x10' FT LONG COPPERWELD GROUND ROD W/ CAST BRONZE OR COPPER CLAMP

PVC COATED RIGID CONDUIT BURIED 24" BELOW FINISHED GRADE

2'-0" DIA.

5'-0"

2'-0"

6"

3"

NOTES:

1. TOP 36" TO BE FORMED.
2. PROVIDE 3-#3 TIES @ 3" O.C. AT TOP OF POLE BASE.

1/4" STAINLESS STEEL MOUNTING PLATE ATTACHED W/ STAINLESS STEEL BOLTS

3" SS UNISTRUT

CONCRETE FILL

4'-0"

10" DIA.

Diagram illustrating the components of a steel railing system:

- SS U-BOLTS
- STEEL RAILING
- STAINLESS STEEL BOLTS
- 1/4" GALVANIZED STEEL MOUNTING PLATE SIZED AS REQUIRED

C **HANDRAIL MOUNTING**
E5.1 NO SCALE

[illegible]

ELECTRICAL DETAILS AND ONE-LINE DIAGRAM

**PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS**

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES



SHEET
34
E5.1

FEEDER CONDUIT AND WIRE SCHEDULE						
CONDUIT DESIGNATION	ORIGIN	TERMINATION	OCPD SIZE	CONDUIT SIZE	CONDUCTORS	GROUND
CHWP-01 VFD Power	Panel H2-2	CHWP-01 VFD	80A, 3-Pole Circuit Breaker	1"	3~#4	#8
CHWP-01 Power	CHWP-01 VFD	CHWP-01	N/A	3/4"	3~#8	#8
CHWP-02 VFD Power	Panel H2-2	CHWP-02 VFD	80A, 3-Pole Circuit Breaker	1"	3~#4	#8
CHWP-02 Power	CHWP-02 VFD	CHWP-02	N/A	3/4"	3~#8	#8
FCU-01 Power	Panel H11-2	FCU-01	40A, 3-Pole Circuit Breaker	3/4"	3~#8	#10
FCU-02 Power	Panel H2-2	FCU-02	40A, 3-Pole Circuit Breaker	3/4"	3~#8	#10
FCU-03 Power	Panel H4	FCU-03	40A, 3-Pole Circuit Breaker	3/4"	3~#8	#10
FCU-04 Power	Panel H4	FCU-04	40A, 3-Pole Circuit Breaker	3/4"	3~#8	#10
FCU-05 Power	Panel H10	FCU-05	125A, 3-Pole Circuit Breaker	1 1/2"	3~#1	#6
FCU-06 Power	Panel H10	FCU-06	125A, 3-Pole Circuit Breaker	1 1/2"	3~#1	#6

FIXTURE SCHEDULE					
Fixture Type	Manufacturer(s)	Model Number	Lamp Type	Mounting	Remarks
A	Cree	ARE-EDG-3M-DA-04-E-UL-BZ-350-40K	50W LED	Pole	Provide square straight aluminum pole model SSA14D5-4-BM, as manufactured by Hapco, or equal.
B	Metalux	VT4LED-LD4-23-DR-UNV-L840-ED2-WL-U	204W LED	Surface	

KEY NOTES:
① ALL WIRE TERMINATIONS SHALL BE BY DIVISION 23 UNLESS OTHERWISE NOTED.

TEMPERATURE CONTROLS SCHEDULE				
CONDUIT DESIGNATION	ORIGIN	TERMINATION	CONDUIT SIZE	CONDUCTORS
TCV-01 Control and Power	TCP-01	TCV-01	2~3/4"	2~#12 2~SH.PR.
TCV-02 Control and Power	TCP-01	TCV-02	2~3/4"	2~#12 2~SH.PR.
TCV-03 Control and Power	TCP-01	TCV-03	2~3/4"	2~#12 2~SH.PR.
TCV-04 Control and Power	TCP-01	TCV-04	2~3/4"	2~#12 2~SH.PR.
TCV-05 Control and Power	TCP-03	TCV-05	2~3/4"+	2~#12+ 2~SH.PR. +
TCV-06 Control and Power	TCP-03	TCV-06	2~3/4"+	2~#12+ 2~SH.PR. +
DA-01 Power	TCP-01	DA-01	3/4"	2~#12
DA-02 Power	TCP-01	DA-02	3/4"	2~#12
DA-03 Power	TCP-01	DA-03	3/4"	2~#12
DA-04 Power	TCP-01	DA-04	3/4"	2~#12
DA-05 Power	TCP-01	DA-05	3/4"	2~#12
DA-06 Power	TCP-01	DA-06	3/4"	2~#12
DA-07 Power	TCP-01	DA-07	3/4"	2~#12
DA-08 Power	TCP-01	DA-08	3/4"	2~#12
DA-09 Power	TCP-01	DA-09	3/4"	2~#12
DA-10 Power	TCP-01	DA-10	3/4"	2~#12
DA-11 Power	TCP-01	DA-11	3/4"+	2~#12+
DA-12 Power	TCP-01	DA-12	3/4"+	2~#12+
DA-13 Power	TCP-01	DA-13	3/4"+	2~#12+
DA-14 Power	TCP-01	DA-14	3/4"+	2~#12+
FCU-01 Door Switch	TCP-01	ZS-01	3/4"	2~#14
FCU-02 Door Switch	TCP-01	ZS-02	3/4"	2~#14
FCU-03 Door Switch	TCP-01	ZS-03	3/4"	2~#14
FCU-04 Door Switch	TCP-01	ZS-04	3/4"	2~#14
FCU-05 Door Switch	TCP-03	ZS-05	3/4"+	2~#14+
FCU-06 Door Switch	TCP-03	ZS-06	3/4"+	2~#14+
OAT-01 Outside Air Temperature	TCP-01	OAT-01	3/4"	SH.PR.
TE-01 Supply Air Temperature	TCP-01	TE-01	3/4"	SH.PR.
TE-02 Supply Air Temperature	TCP-01	TE-02	3/4"	SH.PR.
TE-03 Supply Air Temperature	TCP-01	TE-03	3/4"	SH.PR.
TE-04 Supply Air Temperature	TCP-01	TE-04	3/4"	SH.PR.
TE-05 Supply Air Temperature	TCP-03	TE-05	3/4"+	SH.PR. +
TE-06 Supply Air Temperature	TCP-03	TE-06	3/4"+	SH.PR. +
TE-07 Room Air Temperature	TCP-01	TE-07	3/4"	SH.PR.
TE-08 Room Air Temperature	TCP-01	TE-08	3/4"	SH.PR.
TE-09 Room Air Temperature	TCP-01	TE-09	3/4"	SH.PR.
TE-10 Room Air Temperature	TCP-01	TE-10	3/4"	SH.PR.
TE-11 Room Air Temperature	TCP-03	TE-11	3/4"	SH.PR. +
TE-12 Room Air Temperature	TCP-03	TE-12	3/4"	SH.PR. +
CHWP-01 Control and Status	TCP-02	CHWP-01 VFD	2~3/4"	4~#14 SH.PR.
CHWP-02 Control and Status	TCP-02	CHWP-02 VFD	2~3/4"	4~#14 SH.PR.
ACC-01 Control and Status	TCP-02	ACC-01	2~3/4"	4~#14 SH.PR.
TT-01 System Return Temperature	TCP-02	TT-01	3/4"	SH.PR.
TT-02 System Supply Temperature	TCP-02	TT-02	3/4"	SH.PR.
ACC-01 Flow Indication	Control Panel on ACC-01	FS-01	3/4"	2~#14*
PT-01 System Glycol Pressure	TCP-02	PT-01	3/4"	SH.PR.
BACnet Communication Wiring	TCP-01	TCP-02	3/4"	22 AWG/2 conductor, raspberry color, shielded, plenum-rated cable. Windy City Model No. 0043280ALR-S, or equal.
BACnet Communication Wiring	TCP-02	TCP-03	3/4"+	22 AWG/2 conductor, raspberry color, shielded, plenum-rated cable. Windy City Model No. 0043280ALR-S, or equal.+
EF-EX01 Run Status, Start/Stop Signals	EF-EX01 Starter in Exhaust Fans MCC	TCP-01	3/4"	4~#14
EF-EX02 Run Status, Start/Stop Signals	EF-EX02 Starter in Exhaust Fans MCC	TCP-01	3/4"	4~#14
EF-EX03 Run Status, Start/Stop Signals	EF-EX03 Starter in Exhaust Fans MCC	TCP-01	3/4"	4~#14
EF-EX04 Run Status, Start/Stop Signals	EF-EX04 Starter in Exhaust Fans MCC	TCP-01	3/4"	4~#14
EF-EX05 Run Status, Start/Stop Signals	EF-EX05 Starter in Exhaust Fans MCC	TCP-01	3/4"	4~#14
EF-EX06 Run Status, Start/Stop Signals	EF-EX06 Starter in Exhaust Fans MCC	TCP-01	3/4"	4~#14
EF-EX07 Run Status, Start/Stop Signals	EF-EX07 Starter in Exhaust Fans MCC	TCP-01	3/4"+	4~#14+
EF-EX08 Run Status, Start/Stop Signals	EF-EX08 Starter in Exhaust Fans MCC	TCP-01	3/4"+	4~#14+
EF-EX09 Run Status, Start/Stop Signals	EF-EX09 Starter in Exhaust Fans MCC	TCP-01	3/4"+	4~#14+
FCU-01 Fan Control and Status	TCP-01	FCU-01	2~3/4"	4~#14 SH.PR.
FCU-02 Fan Control and Status	TCP-01	FCU-02	2~3/4"	4~#14 SH.PR.
FCU-03 Fan Control and Status	TCP-01	FCU-03	2~3/4"	4~#14 SH.PR.
FCU-04 Fan Control and Status	TCP-01	FCU-04	2~3/4"	4~#14 SH.PR.
FCU-05 Fan Control and Status	TCP-03	FCU-05	2~3/4"+	4~#14+ SH.PR. +
FCU-06 Fan Control and Status	TCP-03	FCU-06	2~3/4"+	4~#14+ SH.PR. +

+Work and equipment shall be provided as part of Bid Alternative No. 1.

*Wire terminations by Division 26

NOT FOR
CONSTRUCTION

DATE:	04/05/18					
NO.	A					
REVISIONS						
ISSUE FOR BID						

ELECTRICAL
SCHEDULES

PRODUCTION AREA COOLING PROJECT
CRANE COMPOSITES, INC.
JONESBORO, ARKANSAS

JOB NO.
3626.007

PROJECT MGR.
NICHOLAS E. SALES


STRAND
ASSOCIATES®

SHEET
35
E6.1