
| | | 1 | | | 2 | | 3 | | 4 | |
|---|--------------|--|----------------|---|---------------|---|-------------------|--|---|---------------|
| | ABB | DESCRIPTION | ABB | DESCRIPTION | ABB | DESCRIPTION | SYMB | OLS | SECTIONS/ SECTIONAL DETAILS | 1_AL |
| | A. | AND | GA GL | GAUGE GLASS OR GLAZING | REQ'D RFG | REQUIRED REFRIGERATOR | | | | 2 TH |
| | < | ANGLE | GRD | GROUND | RG | RANGE | | _ VIEW CALLOUT | CONCRETE BLOCK | 3 TH |
| | @ | AT | GWB | GYPSUM WALL BOARD | RM | ROOM | # SCALE: | | CAST-IN-PLACE-CONCRETE | DC |
| | A/ ACP | ABOVE ACOUSTIC CEILING PANEL | H | HOSE BIBB | RO RTS | ROUGH OPENING RUBBER TRANSITION STRIP | # | | | 4 RC |
| | ADJ | ADJACENT, ADJUSTABLE | HC | HANDICAP(PED) | RWC | RAIN WATER CONDUCTOR | | | STRUCTURAL/MISCELLANEO US STEEL | 5 NC |
| | AED | AUTOMATED EXTERNAL DEFIBRILLATOR | HDW | HARDWARE | S | | | | | TH |
| | AFF | ABOVE FINISHED FLOOR | HM | HOLLOW METAL | S | SOUTH | # | ELEVATIONS | | 6 DC |
| A | AP APPROX | ACCESS PANEL APPROXIMATE(LY) | HOR HP | HORIZONTAL HIGH POINT | SAN SCHD | SANITARY SCHEDULE | INTERIOR EXTERIOR | | GRAVEL/ENGINEERED | 7 AL |
| | ARCH | ARCHITECT OR ARCHITECTURAL | HTR | HEATER | SEC | SECTION | | | FILL STONE, OR NATURAL BUILDING STONE | OF SH |
| | ASTM | AMERICAN SOCIETY FOR TESTING | I | | SF | SQUARE FOOT | # # | BUILDING SECTION | BUILDING STONE | OF |
| | ATTEN | MATERIAL ATTENUATE, ATTENUATION | | INSIDE DIAMETER INCH(ES) | SIM SPKLR | SIMILAR SPRINKLER | # # | | PLASTER OR GYPSUM BOARD, OR EXTERIOR | 8 DE |
| | AVG | AVERAGE | INT | INTERIOR | SQ | SQUARE | | | SHEATHING | 9 DF AN |
| | B. | | J_ | | SQ FT | SQUARE FOOT | # | WALL SECTION | BATT INSULATION | EL |
| | B/C | BOTTOM OF BOTTOM OF CURB | JB JST | JAMB JOIST | SS STD | STAINLESS STEEL STANDARD | # | | ROOF, TAPERED, CAVITY OR | |
| | BC | BASE CABINET | JT | JOINT | STL | STEEL | | | | 10 VE |
| | BD | BOARD | L | | STN | STAINED | (#) | INTERIOR SECTION | FINISHED WOOD TRIM | IF |
| | BIT BLDG | BITUMINOUS BUILDING | LAM | | STOR | STORAGE | Ħ | | | W |
| | BSMT | BASEMENT | LAN LAV | LOCAL AREA NETWORK CONNECTION LAVATORY | SUSP SYS | SUSPEND, SUSPENDED, OR SUSPENSION SYSTEM | # | DETAIL SECTION | PLYWOOD | 11 PF |
| | C | | LB | POUND | T | | # | | CAVITY DRAINAGE MATERIAL | |
| | | CHANNEL CENTER OF | LF | LINEAL FOOT | "T" - | TEE (BAR OR W) | # | | | |
| | C/ CAB | CENTER OF CABINET | LP TI | LOW POINT LINTEL | | TREAD TOP OF | # | | | 12 ST |
| | CC | CENTER TO CENTER | M | | T/C | TOP OF CURB | | CALLOUT PLAN, | PLANS/ PLAN FIRE RATED GRAPHICS | _ ST м |
| | CG | CORNER GUARD CORNER JOINT | m | METERS | TB | TACKBOARD | | SECTION OR DETAIL | SMOKE | |
| B | CL | CENTER LINE | MAS MAX | MASONRY MAXIMUM | TEL | TERRA COTTA TELEPHONE | <u> </u> | COLUMN GRID LABEL - | SMOKE | AF |
| | CLG | CEILING | MDF | MEDIUM DENSITY FIBERBOARD | TEMP | TEMPERED OR TEMPERATURE | (#) | NEW | 1/2 HOUR | W |
| | CLG HT | CEILING HEIGHT | MECH | MECHANICAL | TERM | TERMINATE / TERMINAL | (#) | COLUMN GRID LABEL - | 1 HOUR | CC DE |
| | CLO CLR | CLOSET CLEAR | MEZZ MFR | MEZZANINE MANUFACTURE | THRESH TLT | THRESHOLD | | EXISTING | | 0 |
| | CMU | CONCRETE MASONRY UNIT | MH | MANHOLE | TV | TELEVISION | \longrightarrow | | 2 HOUR | 14 ME |
| | CO | CLEAN OUT | MICRO | MICROWAVE | ТҮР | TYPICAL | | REVISION | 3 HOUR | 15 AL |
| | COL | COLUMN CONCRETE | MIN MISC | MINIMUM MISCELLANEOUS | U U | UNIT HEATER | | | | AF |
| | CONT | CONTINUOUS | mm | MILLIMETERS | UL | UNDERWRITER'S LABORATORY | | | 4 HOUR | AN |
| | CORR CP | CORRIDOR COPIER | MO | MASONRY OPENING | UMCT | UNGLAZED MOSAIC CERAMIC TILE | | | | 17 CC |
| | CT | CERAMIC TILE | MTD MTL | MOUNTED EL METAL | UNO | UNLESS NOTED OTHERWISE | ROOM NAME | ROOM TAG | | M/ |
| | CY | CUBIC YARD | N | | VEST | VESTIBULE | | | PLANS / PLAN DETAIL GRAPHICS | - NC 18 CC |
| | DF | DRINKING FOUNTAIN | N NFPA | NORTH NATIONAL FIRE PROTECTION | VIF | VERIFY IN FIELD | #X#.# | PARTITION TYPE | BRICK WALLS | C |
| | DIA | DIAMETER | | ASSOCIATION | W | / WEST | | | | |
| | DIM | DIMENSION | NIC | NOT IN CONTRACT | W/ | WITH | | DOOR TAG - SEE SCHEDULE | CONCRETE BLOCK WALLS | 19 CC |
| | DW | DOWN DISHWASHER | NOM NTS | NOMINAL NOT TO SCALE | W/O WC | WITHOUT WATER CLOSET | | SUREDULE | | CC AF |
| С | DWG | DRAWING | 0 | | WIN | WINDOW | | | CAST-IN-PLACE- CONCRETE WALLS | OF 00 OF |
| | E. | | 00 | ON CENTER | WP | WATERPROOF(ING) | (##.## | KEYNOTE | STUD WALLS | 20 CC |
| | E EA | EAST EACH | OD OFF | OUTSIDE DIAMETER OFFICE | WSCT WT | WAINSCOT WEIGHT | <u> </u> | | | 21 CC |
| | EB | EDGE BANDING | OPNG | OPENING | WWF | WEIGHT WELDED WIRE REINFORCEMENT | <#> | WINDOW TYPE | NEW CONCRETE SLABS AND/OR CONCRETE SIDEWALKS | 22 CC |
| | EIFS | EXTERIOR INSULATION FINISH SYSTEM EXPANSION JOINT | OPP | OPPOSITE | | | (#) | TOILET ROOM | EXISTING WALLS | CC |
| | ELEC | ELECTRICAL | PART | PARTITION | | | | ACCESSORIES | | 23 CC |
| | ELEV | ELEVATOR | PEMB | PREENGINEERED METAL BUILDING | | | | ELEVATION MARK | EXISTING CONCRETE SLAB | ST AN |
| | EMER ENCL | EMERGENCY ENCLOSE(URE) | PL PLAM | PLATE PLASTIC LAMINATE | | | | | AND/OR SIDEWALKS | 24 CC |
| | EP | ELECTRICAL PANEL | PLAS | PLASTER | | | | DENOTES ABOVE, BELOW, OR BEHIND | DOOR DESIGNATIONS | _ DI |
| | EQ | EQUAL | PLYWD | PLYWOOD | | | Æ | | | |
| | EQUIP EWC | EQUIPMENT ELECTRIC WATER COOLER | PNL POS | PANEL POINT OF SALE | | | UM3 | ACCESSIBLE TOILET STALL | EXISTING DOOR AND/OR FRAME TO | 25 CC |
| | EXIST | EXISTING | PR | PAIR | | | | RECYCLING | REMAIN - SEE DOOR SCHEDULE FOR ANY ADDITIONAL WORK | TC |
| | EXP BLT | EXPANSION BOLT | PRCST | PRECAST | | | | COLLECTION AREA | | SE SE |
| | EXT | EXTERIOR | PREFAB PROP | PREFABRICATED PROPERTY | | | PLAN | | | 26 CC |
| | < | FABRIC | PSI | POUNDS PER SQUARE INCH | | | NORTH | NORTH ARROW | NEW DOOR AND/OR FRAME TO BE PROVIDED - SEE DOOR SCHEDULE | LC EX |
| | F/F | FACE TO FACE | PSIG | POUNDS PER SQUARE INCH GAUGE | | | | | | EX |
| D | FAX FE | FACSIMILE FIRE EXTINGUISHER | PTD | POINT PAINTED | | | Ę | CENTER LINE | | I OF |
| | FEC | FIRE EXTINGUISHER CABINET | Q | | | | - ×- | FLOOR TRANSITION | EXISTING DOOR AND/OR FRAME TO BE REMOVED - SEE DEMO PLAN/NOTES | 27 RE |
| | FHC | FIRE HOSE CABINET | QTY | QUANTITY | | | | | | AF 28 AL |
| | FL FL CO | FLOOR FLOOR CLEANOUT | RR | RISER OR RADIUS | | | | ROOF SLOPE ARROW | | IN |
| | FP | FIRE PROTECTION | RCP | REFLECTED CEILING PLAN | | | | | | 29 C |
| | FPRF FR | FIREPROOF(ING) FIRE RATED OR FRAME | RD REF | ROOF DRAIN REFER / REFERENCE | | | — — — | LEVEL LINE | | RE |
| | FR | FOOT/FEET | REG | REGISTER | | | | SPOT ELEVATION | | 30 CC |
| | G | | REINF | REINFORCING | | | $\mathbf{\nabla}$ | | | FA |
| | | | | | | | | 1 | | <u> </u> |
| | | | | I I | | | | | | |

| | 5 | | |
|---|---|--------------------------------|-------------|
| | NOTES - GENERAL ALL DIMENSIONS ARE IN FEET / INCHES UNLESS NOTED OTHERWISE | Michael Ba | ker |
| | THESE GENERAL NOTES ARE NOT INTENDED TO REPLACE SPECIFICATIONS - REFER | | |
| | TO SPECIFICATIONS FOR REQUIREMENTS IN ADDITION TO GENERAL NOTES THE TERMS RENOVATE AND REHABILITATE ARE USED INTERCHANGEABLY IN THESE | 1501 LBJ FREEWAY, SUITE 650 | |
| | DOCUMENTS. | DALLAS, TX 75234 | |
| | ROOM AREAS AND PERIMETERS ARE APPROXIMATE AND FOR REFERENCE ONLY. VERIFY QUANTITIES AND DIMENSIONS IN FIELD. | | |
| | NO DEVIATIONS FROM THESE CONTRACT DOCUMENTS SHALL BE MADE WITHOUT THE PRIOR WRITTEN APPROVAL OF THE ARCHITECT | | |
| | DO NOT SCALE DIMENSIONS FROM DRAWINGS - THE CONTRACTOR SHALL REQUEST | | |
| | NECESSARY DIMENSIONS NOT SHOWN ON THE DRAWINGS FROM THE ARCHITECT ALL DIMENSIONS ARE TO FACE OF PARTITION OR EDGE OF DOORS, WINDOWS AND | | |
| | OPENINGS UNLESS NOTED OTHERWISE - ALL NON-DIMENSIONED DOOR LOCATIONS SHALL BE OFFSET 4" FROM THE ADJACENT WALL TO THE HINGE SIDE OF THE DOOR | | |
| | OPENING. | Consultant | |
| | DETAILS SHOWN ON DRAWINGS ARE TYPICAL FOR ALL SIMILAR CONDITIONS. DRAWING NOTES AND SPECIFICATIONS ARE INSTRUCTIONS TO THE CONTRACTOR | CONSULANT | |
| | AND APPLY TO ALL THE WORK UNLESS MORE SPECIFIC INFORMATION IS SHOWN ELSEWHERE ON THE DRAWINGS OR WRITTEN IN THE SPECIFICATIONS - IN THE | CHARLES M. | TEC |
| | EVENT OF CONFLICTING INSTRUCTIONS, THE ARCHITECT SHALL DETERMINE WHAT CONTROLS | POPOVICH, JR. |)]] |
|) | VERIFY ALL DIMENSIONS IN THE FIELD AND COORDINATE DIMENSIONS SHOWN ON | PF ARKANSP | 3 |
| | THE CONTRACT DRAWINGS WITH FABRICATION AND FIELD CONDITIONS AND REPORT ANY INCONSISTENCIES TO THE ARCHITECT BEFORE PROCEEDING WITH | SEAL 02/05/20 | 12/ |
| | WORK PRINCIPAL OPENINGS IN THE STRUCTURE ARE SHOWN ON THESE DRAWINGS - THE | | |
| | GENERAL CONTRACTOR SHALL EXAMINE THE ARCHITECTURAL, MECHANICAL, | | |
| | ELECTRICAL, AND PLUMBING DRAWINGS FOR REQUIRED OPENINGS GENERAL CONTRACTOR SHALL VERIFY SIZE AND LOCATION OF ALL OPENINGS WITH ALL | | |
| | SUB-CONTRACTORS PRIOR TO CONSTRUCTION STRUCTURAL DRAWINGS AND SPECIFICATIONS REPRESENT THE FINISHED | | NO |
| - | STRUCTURE, AND, EXCEPT WHERE SPECIFICALLY SHOWN, DO NOT INDICATE THE METHOD OR MEANS OF CONSTRUCTION - THE CONTRACTOR SHALL SUPERVISE | | SCRIP I ION |
| | CONSTRUCTION MEANS, METHODS, PROCEDURES, TECHNIQUES, SEQUENCE, AND | | IS SCH |
| | APPLICABLE SAFETY REGULATIONS TO BE FOLLOWED CONTRACTOR SHALL BE RESPONSIBLE FOR SCHEDULING AND COORDINATING THE | | EVISIONS |
| | WORK OF THE SUB-CONTRACTORS - THE CONTRACTOR SHALL BE RESPONSIBLE TO COORDINATE WITH THE BUILDING OWNER, TENANT OR HIS REPRESENTATIVES THE | | REVI |
| | DELIVERY AND INSTALLATION OF ITEMS BEING PROVIDED AND INSTALLED BY OTHERS | | |
| | MECHANICAL, PLUMBING AND ELECTRICAL WORK RELATED TO DEMOLITION AND | | |
| | NEW INSTALLATION OF COMPONENTS SHALL COMPLY WITH ALL APPLICABLE CODES ALL MATERIALS, FABRICATION AND INSTALLATION SHALL COMPLY WITH THE | | Ц |
| | APPLICABLE REQUIREMENTS AND SPECIFICATIONS FOR EACH DIVISION OF WORK | | DA |
|) | CONSTRUCTION MUST COMPLY WITH APPLICABLE CODES AND ORDINANCES, LAWS AND SAFETY ORDERS AS DIRECTED BY LOCAL JURISDICTION | | O |
| , | CONTRACTOR SHALL BE RESPONSIBLE FOR THE TIMELY ORDERING OF MATERIALS INCLUDED IN THESE CONTRACT DOCUMENTS - SOME ITEMS IN THESE DOCUMENTS | | Z |
| | MAY REQUIRE LONG LEAD TIMES OR SPECIAL COORDINATION SUBSTITUTIONS WILL NOT BE ALLOWED FOR MATERIAL NOT ORDERED IN A TIMELY FASHION | | ð |
| } | CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS AND GRADE | | LEGEND |
| | CONDITIONS, (BOTH NEW AND EXISTING) REPORTING ANY DISCREPANCIES TO THE ARCHITECT PRIOR TO ORDERING MATERIALS OR PROCEEDING WITH ANY PHASE OF | | L L N |
|) | THE WORK CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS PRIOR TO COMMENCING | | - |
| | CONSTRUCTION - ALL DISCREPANCIES SHALL BE NOTED AND SENT TO THE ARCHITECT WITH ADEQUATE TIME TO REVIEW PRIOR TO STARTING THAT PORTION | | ANNOTATIO |
| | OF THE WORK IN ORDER TO AVOID PROJECT DELAYS | | NN NN |
|) | CONTRACTOR SHALL CLEAN, PATCH AND REPAIR ALL SURFACES DAMAGED BY DEMOLITION, ALTERATION OR INSTALLATION OF THE WORK | | |
| | CONTRACTOR SHALL PREPARE ALL WALLS AND PARTITIONS AS REQUIRED BY THE FINISH MANUFACTURER TO RECEIVE THE FINISHES SPECIFIED | 401 1VE | AND |
| | CONTRACTOR SHALL PROTECT ALL MONUMENTS, IRON PINS, AND PROPERTY | | |
| | CORNERS DURING CONSTRUCTION CONTRACTOR SHALL PROVIDE ADDITIONAL FURRING (THE ENTIRE LENGTH OF THE | AR AR | MATERIAL |
| | WALL) TO FULLY CONCEAL ALL MECHANICAL, ELECTRICAL, PLUMBING AND STRUCTURAL ITEMS THAT PROJECT FROM THE FACE OF THE WALL OR PARTITION | 0, , O | MAT |
| | AND ARE NOT SPECIFICALLY NOTED TO BE SURFACE MOUNTED CONTRACTOR SHALL REFER TO ARCHITECTURAL PLANS FOR BUILDING | | ທົ |
| • | DIMENSIONS, BUILDING UTILITY ENTRANCE LOCATIONS AND EXACT LOCATIONS AND | GAR LINE ESB(| NOTE |
| | DIMENSIONS OF EXITS, CANOPIES, RAMPS, DOWNSPOUTS, GRAVEL AREAS ADJACENT TO BUILDING WALLS, UTILITY ENTRANCE LOCATIONS AND BOLLARDS IN | | |
| | BUILDING WALKWAYS CONTRACTOR SHALL VISIT THE SITE AND VERIFY ALL EXISTING CONDITIONS PRIOR | HAN 3901 JON | GENERAL |
| | TO COMMENCING CONSTRUCTION - ALL DISCREPANCIES SHALL BE NOTED AND SENT TO THE ARCHITECT WITH ADEQUATE TIME TO REVIEW PRIOR TO STARTING | | Ш И И |
| | THAT PORTION OF THE WORK IN ORDER TO AVOID PROJECT DELAYS | | _ |
|) | CONTRACTOR TO PROVIDE PORTABLE FIRE EXTINGUISHERS IN ACCORDANCE WITH LOCAL JURISDICTION AND NFPA 10. MAXIMUM TRAVEL DISTANCE TO NEAREST FIRE | | CTURAL |
| | EXTINGUISHER FROM ANY POINT IN THE BUILDING SHALL NOT EXCEED 75 FEET. EXISTING FIRE EXTINGUISHERS SHALL BE TESTED AND RE-USED IF FULLY | | ECT |
| | OPERATIONAL. FIRE EXTINGUISHERS SHALL BE SIZED FOR NO LESS THAN ORDINARY HAZARD. | | ШЦЩ |
| , | REMOVE AND REINSTALL PICTURES, TV'S, BULLETIN BOARDS ETC, PRIOR TO AND AFTER PAINTING | | ARCH |
| 5 | ALL REQUESTS FROM INFORMATION PROMPTED BY THE BUILDING OFFICIALS SHALL | | ∢ |
| | INCLUDE A COPY OF THE BUILDING OFFICIALS COMMENTS AND THE BUILDING INSPECTORS FIELD REPORT TO ENSURE AN ACCURATE AND TIMELY RESPONSE | Project Number: 181261 | |
|) | CONTRACTOR AND SUBCONTRACTOR SHALL ALL BE LICENSED TO PERFORM THEIR REQUESTED DUTIES AS REQUIRED IN ACCORDANCE WITH LOCAL STANDARDS | Date: 02-05-2021 | |
|) | CONTRACTOR SHALL COMPARE STRUCTURAL SECTIONS WITH ARCHITECTURAL | Scale: | |
| | SECTIONS AND REPORT ANY DISCREPANCY TO THE ARCHITECT PRIOR TO FABRICATION OR INSTALLATION OF STRUCTURAL MEMBERS | AS NOTED | |
| | | A-001 | |
| _ | 5 | © Baker 2021 | |

<u>S</u>


















| | 5 | |
|---|---|--|
| | FLOOR PLAN - NOTES 1 REFER TO SHEET A-001 FOR ARCHITECTURAL GENERAL NOTES, & ANNOTATION LEGEND. 2 REFER TO A-400 SERIES ENLARGED PLANS AND INTERIOR ELEVATIONS FOR ADDITIONAL INFORMATION. 3 REFER TO SHEET A-601 FOR PARTITION TYPES 4 REFER TO SHEET A-602 FOR SIGN TYPES, DETAILS, AND SHEDULE 5 RESTROOM WALLS AND CEILINGS TO RECEIVE SOUND BATT INSULATION 6 REFER TO MECHANICAL, ELECTRICAL, PLUMBING, AND FIRE PROTECTION SHEETS FOR EQUIPMENT LOCATIONS AND REQUIREMENTS. 7 DIMENSIONS MARKED AS "CLEAR" DICTATES THE CLEAR DIMENSION FROM FINISH TO FINISH 8 WHERE FIRE RATED PARTITIONS INTERSECT WITH LESSER RATED PARTITIONS OR NON-RATED PARTITIONS, THE HIGHER RATED PARTITION IS TO CONTINUE THROUGH THE INTERSECTION TO MAINTAIN THE HIGHER RATING LEGEND MASONRY CONTROL JOINTS 15'-0" O.C. SEALED WITH FIRE SEALANT | Michael Baker I N T E R N A T I O N A L 1501 LBJ FREEWAY, SUITE 650 DALLAS, TX 75234 |
| | | NO. DATE DESCRIPTION |
| WITH RUBBER BUMPER STOP, PER HANGAR MANUFACTUER | | HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 FLOOR PLAN |
| PLAN NORTH | 0 4' - 0" 8' - 0" 16' - 0" SCALE: 1/8" = 1' - 0" 5 | Project Number: 181261 Date: 02-05-2021 Scale: AS NOTED Sheet # A-110 © Baker 2021 |




| | | 5 ROOF PLAN - NOTES | | |
|------------|---------------|--|--|--------------------------|
| | | ROOF PLAN - NOTES | Michael Ba I N T E R N A T I 1501 LBJ FREEWAY SUITE 650 DALLAS, TX 75234 | ONAL |
| | | | Consultant | |
| | | | | DESCRIPTION REVISIONS |
| 1 A-202 | | | | DATE |
| | | | | Ö |
| | | | HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 | ROOF PLAN |
| | PLAN NORTH | 0 4'-0" 8'-0" 16'-0" SCALE: 1/8" = 1'-0" 5 | Project Number: 181261 Date: 02-05-2021 Scale: AS NOTED Sheet # A-130 © Baker 2021 | |







SCALE: 1/8" = 1'-0" REF: A-110



А


В



D

| | INTERNATIONA 1501 LBJ FREEWAY, SUITE 650 DALLAS, TX 75234 | L |
|--|--|------------------|
| O. <u>STEEL (HIGH BAY)</u> 31' - 0" METAL GUTTER (PEMB) METAL DOWNSPOUT | Consultant | |
| $\frac{10. \text{ STEEL (LOW BAY)}}{13' - 9"} \textcircled$ NEW CONCRETE SPLASH BLOCK $ \frac{\text{FLOOR PLAN}}{0"} \textcircled$ THRU WALL SCUPPER | DESCRIPTION | |
| METAL GUTTER (PEMB) | NO. DATE | |
| STEEL (HIGH BAY) 31' - 0'' METAL DOWNSPOUT WINDOW (TYP) HM DOOR $12' \times 8' \text{ OH DOOR}$ STEEL (LOW BAY) 13' - 9'' METAL GUTTER (PEMB) METAL DOWNSPOUT CANOPY (PEMB) FLOOR PLAN 0'' | HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 EXTERIOR ELEVATIONS | |
| MECHANICAL EQUIPMENT REF: MECHANICAL $\underbrace{0 4' - 0" 8' - 0" 16' - 0"}_{\text{SCALE: }1/8" = 1' - 0"}$ | Project Number: 181261 Date: 02-05-2021 Scale: AS NOTED Sheet # A-201 © Baker 2021 | CONSTRUCTION SET |

Michael Baker



1


3

4

| HANGAR REPLACEMENT 3901 LINDBERGH DRIVE 3001 LINDBE |
|---|
| NO. DATE REVISI |
| |
| HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 EXTERIOR ELEVATIONS |
| 1 1 |

4' - 0" 8' - 0"

SCALE: 1/8" = 1' - 0"




В

С


D


| 3 | 4 (4) (4) (4) (4) (4) | 5 | 6 | 7 |
|--|--------------------------------------|-------------------|------------------------|---|
| CABLES SUPPORT (TYP) INDUSTRIAL FAN (TYP) | | 1 1 1 1 | | |
| | | | | GWB L GWB L GWB L COLUM FLC |
| NDATION REF; STRUCTURAL | BOLLARD | 12' X 12' OH DOOR | NEW FOUNDATION REF; ST | |
| | | | | |

| | | 5 | |
|--|--|---|--|
| | | KEYNOTES | Michael Baker |
| | | | Consultant |
| | | | DATE DESCRIPTION REVISIONS |
| | | | |
| DO B & JC - (L HA M ; LI ; LI | $\frac{1GH BAY}{31' - 0''} $ $W (TYP)$ $\frac{OW BAY}{13' - 9''} $ $NICAL EQUIPMENTECHANICAL$ $NER PANELS$ $NER PANELS$ $N WRAP$ $OR PLAN$ $0'' $ | | HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 BUILDING SECTIONS |
| | | 0 4' - 0" 8' - 0" 16' - 0" SCALE: 1/8" = 1' - 0" | Project Number: 181261 Date: 02-05-2021 Scale: AS NOTED Sheet # A-301 |
| | | 5 | © Baker 2021 |



| | | 1 | 2 |
|---|---|---|---|
| | | | |
| | | | |
| | | | |
| A | | | |
| ~ | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| В | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| С | | | |
| | | | |
| | | | |
| | | | |
| | - | | |
| | | | |
| | | | |
| | | | |
| D | | | |
| | | | |
| | | | |
| | | | |
| | | 1 | 2 |







| | TOILET ACCESSO |
|-------|--|
| A01 | SOLID SURFACE SINK |
| A02 | FRAMED GLASS TILTED MIRROR |
| A03 | SOAP DISPENSER |
| A04 | SOLID SURFACE COUNTERTOP |
| A05 | COMBINATION PAPER TOWEL DISPENSER/WASTE RECEPTAC |
| A06 | TOILET PARTITION W/ SSTL BOOT & MOUNTING HARDWARE |
| A07 | COAT HOOK |
| A08-A | COMBINATION UNIT: TOILET TISSUE (2-ROLL) DISPENSER AND |
| A08-B | COMBINATION UNIT: TOILET TISSUE (2-ROLL) DISPENSER AND |
| A09 | BABY CHANGING STATION |
| A10 | ADA FLOOR MOUNTED TOILET |
| A11 | FLOOR MOUNTED TOILET |
| A12 | ADA URINAL |
| A13 | MOP SINK |
| A14 | MOP RACK & UTILITY SHELF |
| A15 | DOOR BUMPER |
| A16 | SANITARY NAPKIN VENDOR |
| A17 | ADA APRON |
| A18 | HAND SANITIZER |
| A19 | GRAB BAR |
| | |


WATER DRINKING FOUNTAINS (HI/LO)

ADA MOUNTING HEIGHTS AND DIMENSIONS




















В


С


D











А

В


С

D

1

PARTITION TYPE 1A0

| TYPE | FIRE RATED | CORE WIDTH | overall Width | STC RATED | UL LISTING | STC TEST |
|---------|------------|---------------|------------------|-----------|------------|----------|
| 1A0.3.c | NON-RATED | 3 5/8" | 4 7/8" | 45 | N/A | NGC 2391 |




PARTITION TYPE 6A2

| TYPE | FIRE RATED | CORE WIDTH | overall Width | STC RATED | UL LISTING | STC TEST |
|-------|------------|---------------|------------------|-----------|------------|----------|
| 6A2.8 | 2 HOUR | 8" | 7 5/8" | NON-RATED | U905 | N/A |











PARTITION TYPE 1A1

| TYPE | FIRE RATED | CORE WIDTH | overall Width | STC RATED | UL LISTING | STC TEST |
|-------|------------|---------------|------------------|-----------|------------|----------|
| 1A1.3 | 1 HOUR | 3 5/8" | 4 7/8" | NON-RATED | U419 | N/A |




PARTITION TYPE 8D0


| TYPE | FIRE RATING | CORE WIDTH | overall Width | UL LISTING | STC TEST |
|-------|-------------|---------------|------------------|------------|----------|
| 8D0.2 | NON-RATED | 2 1/2" | 4 5/8" | N/A | N/A |



| | | 4 | | 5 | | |
|----------------------------------|------------------------------|-------------|---|---|--|--------------------------|
| | 6" MINIMUM | 4 | ROOF OR FLOOR DECK BRACE TO STRUCTURE AT 48" ON CENTER IN ALTERNATING DIRECTIONS CEILING AS SCHEDULED WHERE OCCURS 5/8" GYPSUM BOARD METAL STUDS AS SCHEDULED BELOW AT 16" ON CENTER (SPACING OF STUDS IS TYPICAL UNLESS NOTED OTHERWISE ON PLANS) 5/8" GYPSUM BOARD FLOOR SYSTEM | 5 NOTES - PARTITION ALL PARTITIONS IN RESTROOMS TO RECEIVE MOISTURE RESISTANT GYPSUM BOARD IN PLACE OF GYPSUM WALL BOARD. WHERE WALLS ARE TO RECEIVE TILE, 5/8" CEMENT BOARD IS TO BE USED IN PLACE OF GYPSUM WALL BOARD. ALL PERIMETER WALLS AROUND RESTROOMS THAT ARE NOT ALREADY REQUIRED TO RECEIVE AND STC RATING WILL RECEIVE SOUND ATTENUATING BATT INSULATION AND ACOUSTICAL SEALANT AT THE TOP AND BOTTOM OF THE WALL. THE SOUND ATTENUATING BATT INSULATION WILL BE CONTINUOUS THEN ENTIRE HEIGHT OF THE WALL. FILL VOIDS AROUND WALL PENETRATIONS WITH FIRE STOPPING TO AVOID REDUCTION OF FIRE RATING. ALL FIRE RATED PARTITIONS TO RECEIVE TYPE "X" GYPSUM BOARD. | Consultant | CHITECT |
| TYPE 1B0.3 | FIRE RATI NON-RAT | CC NG WI | RTITION TYPE 1B0DRE DTHOVERALL WIDTHSTC RATEDUL LISTINGSTC TEST5/8"4 7/8"NON-RATEDN/AN/A | | | DESCRIPTION REVISIONS |
| JRLIN LINE | SPACES | | TOP OF PURLINS TOP TRACK ADJACENT WALL OR STRUCTURE, REF. PLANS AND WALL SECTIONS CEILING WHERE OCCURS | LEGEND - PARTITION TYPES CORE TYPE CORE HEIGHT RATING 1 A 2 . 3 a | | NO. DATE |
| TO TOP OF STRUCTURAL PURLIN LINE | FOR LOW BAY IN ADMIN SPACES | | 5/8" GYPSUM BOARD 1 1/2" CONTINUOUS INSULATION AIR BARRIER 2 1/2" METAL STUDS AT 16" O.C. TYP, UNO BASE AS SCHEDULED FLOOR SYSTEM | CORE TYPE 1 METAL STUD WALL 2 METAL STUD SHAFT WALL 3 METAL STUD SHAFT WALL 3 METAL STUD (1 SIDED GYP BD) 4 WOOD STUD WALL 5 WOOD STUD (1 SIDED GYP BD) 6 CMU 7 CONCRETE 8 FURRING CORE HEIGHT A FULL HEIGHT (TO UNDERSIDE OF STRUCTURE) B 6" ABOVE HIGHEST ADJACENT CEILING | EMENT DRIVE 72401 | S |
| TYPE 8A0.2 | PAR FIRE RATI NON-RATI | NG WI | DRE OVERALL DTH UL LISTING 1/2" 3 1/8" | C TO CEILING D (D-Z) USER DEFINED (SPECIAL CONDITIONS) RATING 0 NON-RATED 1 1 HOUR 2 2 HOUR 3 3 HOUR 4 4 HOUR H 1/2 HOUR S SMOKE RATED CORE WIDTH .1 METAL STUD (1 5/8") .2 METAL STUD (2 1/2") 0 METAL STUD (2 5/0") | HANGAR REPLACE 3901 LINDBERGH I JONESBORO, AR | PARTITION TYPES |
| | | | | .3 METAL STUD (3 5/8") .4 METAL STUD (4") WOOD STUD (3 1/2") CMU/CONCRETE (3 5/8") .6 METAL STUD (6") WOOD STUD (5 1/2") CMU/CONCRETE (5 5/8") .8 METAL STUD (8") WOOD STUD (7 1/4") CMU/CONCRETE (7 5/8") .10 METAL STUD (10") WOOD STUD (9 1/4") CMU/CONCRETE (9 5/8") .12 WOOD STUD (11 1/4") CMU/CONCRETE (11 5/8") STC CLASSIFICATION .a STC 35 .b STC 40 .c STC 45 .d STC 50 | Project Number: 181261 Date: 02-05-202 Scale: AS NOTEI Sheet # A-60 | |
| | | 4 | | .e STC 55 5 | © Baker 2021 | ŭ |



| 4 | 5 | | |
|--|--|---|-----------|
| | NOTES - PARTITION1ALL PARTITIONS IN RESTROOMS TO RECEIVE MOISTURE RESISTANT GYPSUM BOARD IN PLACE OF GYPSUM WALL BOARD.2WHERE WALLS ARE TO RECEIVE TILE, 5/8" | Michael Bak | |
| | CEMENT BOARD IS TO BE USED IN PLACE OF GYPSUM WALL BOARD. | DALLAS, TX 75234 | |
| BRACE TO STRUCTURE AT 48" ON CENTER IN ALTERNATING DIRECTIONS | 3 ALL PERIMETER WALLS AROUND RESTROOMS THAT ARE NOT ALREADY REQUIRED TO RECEIVE AND STC RATING WILL RECEIVE SOUND ATTENUATING BATT INSULATION AND ACOUSTICAL SEALANT AT THE TOP AND BOTTOM OF THE WALL. THE SOUND ATTENUATING BATT INSULATION WILL BE CONTINUOUS THEN ENTIRE | | |
| CEILING AS SCHEDULED WHERE OCCURS | HEIGHT OF THE WALL. FILL VOIDS AROUND WALL PENETRATIONS WITH FIRE STOPPING TO AVOID REDUCTION OF FIRE RATING. | Consultant | |
| METAL STUDS AS SCHEDULED BELOW AT 16" ON CENTER (SPACING OF STUDS IS TYPICAL UNLESS NOTED OTHERWISE ON PLANS) | 5 ALL FIRE RATED PARTITIONS TO RECEIVE TYPE "X" GYPSUM BOARD. | CHARLES M. POPOVICH, JR. Uconse Number 9683 | |
| 5/8" GYPSUM BOARD | | SEAL 02/05/202 | / |
| PARTITION TYPE 1B0 | | | |
| TYPEFIRE RATINGCORE WIDTHOVERALL WIDTHSTC RATEDUL LISTINGSTC TEST1B0.3NON-RATED3 5/8"4 7/8"NON-RATEDN/AN/A | | DESCRIPTION | REVISIONS |
| TOP OF PURLINS | | | RE |
| ADJACENT WALL OR STRUCTURE, REF. PLANS AND WALL SECTIONS | LEGEND - PARTITION TYPES | DATE | |
| SECURITING WHERE OCCURS | CORE TYPE CORE HEIGHT RATING 1 A 2 . 3 a STC CLASSIFICATION | ġ Ż | |
| SECURATION AIR BARRIER | CORE TYPE 1 METAL STUD WALL 2 METAL STUD SHAFT WALL 3 METAL STUD (1 SIDED GYP BD) 4 WOOD STUD WALL | | |
| 2 1/2" METAL STUDS AT 16" O.C. TYP, UNO | 5 WOOD STUD (1 SIDED GYP BD) 6 CMU 7 CONCRETE 8 FURRING | | |
| BASE AS SCHEDULED FLOOR SYSTEM | CORE HEIGHT A FULL HEIGHT (TO UNDERSIDE OF STRUCTURE) B 6" ABOVE HIGHEST ADJACENT CEILING C TO CEILING | ACEMENT GH DRIVE AR 72401 TVDES | 2 |
| PARTITION TYPE 8A0 | D (D-Z) USER DEFINED (SPECIAL CONDITIONS) RATING 0 NON-RATED 1 1 HOUR 0 0 0 0 0 0 0 0 | REPI DBER ORO, | |
| TYPEFIRE RATINGCORE WIDTHOVERALL WIDTHUL LISTINGSTC TEST8A0.2NON-RATED2 1/2"3 1/8"N/AN/A | 2 2 HOUR 3 3 HOUR 4 4 HOUR H 1/2 HOUR S SMOKE RATED CORE WIDTH | HANGAR 3901 LINI JONESB | |
| | .1 METAL STUD (1 5/8") .2 METAL STUD (2 1/2") .3 METAL STUD (3 5/8") .4 METAL STUD (4") WOOD STUD (3 1/2") | | |
| | CMU/CONCRETE (3 5/8") .6 METAL STUD (6") WOOD STUD (5 1/2") CMU/CONCRETE (5 5/8") .8 METAL STUD (8") WOOD STUD (7 1/4") | | |
| | CMU/CONCRETE (7 5/8") .10 METAL STUD (10") WOOD STUD (9 1/4") CMU/CONCRETE (9 5/8") | | |
| | CMU/CONCRETE (9 5/8") .12 WOOD STUD (11 1/4") CMU/CONCRETE (11 5/8") STC CLASSIFICATION | Project Number: 181261 Date: | t |
| | .a STC 35 .b STC 40 | 02-05-2021 Scale: | C |
| | .c STC 45 .d STC 50 | AS NOTED | |
| 4 | .e STC 55 5 | © Baker 2021 | |



3

| RO | OM FINISH | SCHEDU | E | | |
|--------|--------------|--------------|------------|---------|---|
| | WALL MATER | IAL - FINISH | | | |
| RTH | EAST | SOUTH | WEST | CEILING | REMARKS |
| / | LP & VI | LP & VI | LP & CMU-P | STR-P | GWB LINER PANEL, REF WALL SECTIONS |
| | CMU-P | GB-P | GB-P | ACT | |
| | GB-P | GB-P | GB-P | ACT | |
| | GB-P & CMU-P | GB-P | GB-P | ACT | |
| | GB-P | GB-P | GB-P | ACT | |
| | GB-P | GB-P | GB-P | ACT | |
| & CT-1 | CMU-P | GB-P & CT-1 | GB-P | GB-P | CEMENT BOARD @ TILE LOCATIONS / MOISTURE RESISTANT GWB |
| & CT-1 | CMU-P | GB-P & CT-1 | GB-P | GB-P | CEMENT BOARD @ TILE LOCATIONS / MOISTURE RESISTANT GWB |
| | CMU-P | GB-P | GB-P | STR-P | |
| | GB-P | GB-P | GB-P | STR-P | |
| | CMU-P | GB-P | GB-P | ACT | |
| | CMU-P | GB-P | GB-P | GB-P | MOISTURE RESISTANT GWB |
| | CMU-P | GB-P | GB-P | GB-P | MOISTURE RESISTANT GWB |


| | | | | | OM FINISH | | L- L- | | |
|--------|------------------|--------|-----------|-------------|--------------|-------------|--------------|---------|---|
| | ROOM | _ | | | WALL MATER | | | | |
| NUMBER | NAME | FLOOR | BASE | NORTH | EAST | SOUTH | WEST | CEILING | REMARKS |
| 100 | HANGAR HIGH BAY | CONC-S | NONE | LP & VI | LP & VI | LP & VI | LP & CMU-P | STR-P | GWB LINER PANEL, REF WALL SECTIONS |
| 101 | OFFICE | CARPET | VB | GB-P | CMU-P | GB-P | GB-P | ACT | |
| 102 | OFFICE | CARPET | VB | GB-P | GB-P | GB-P | GB-P | ACT | |
| 103 | LOBBY | CARPET | VB | GB-P | GB-P & CMU-P | GB-P | GB-P | ACT | |
| 104 | TEST | CARPET | VB | GB-P | GB-P | GB-P | GB-P | ACT | |
| 105 | PARTS | CONC-S | VB | GB-P | GB-P | GB-P | GB-P | ACT | |
| 106 | WOMEN'S RESTROOM | VCT | VB & CT-1 | GB-P & CT-1 | CMU-P | GB-P & CT-1 | GB-P | GB-P | CEMENT BOARD @ TILE LOCATIONS / MOISTURE RESISTANT GWB |
| 107 | MEN'S RESTROOM | VCT | VB & CT-1 | GB-P & CT-1 | CMU-P | GB-P & CT-1 | GB-P | GB-P | CEMENT BOARD @ TILE LOCATIONS / MOISTURE RESISTANT GWB |
| 108 | SHOP | CONC-S | VB | GB-P | CMU-P | GB-P | GB-P | STR-P | |
| 109 | MECH. | CONC-S | NONE | GB-P | GB-P | GB-P | GB-P | STR-P | |
| 110 | CLOSET | CARPET | VB | GB-P | CMU-P | GB-P | GB-P | ACT | |
| 111 | JAN | CONC-S | NONE | GB-P | CMU-P | GB-P | GB-P | GB-P | MOISTURE RESISTANT GWB |
| 112 | JAN | CONC-S | NONE | GB-P | CMU-P | GB-P | GB-P | GB-P | MOISTURE RESISTANT GWB |

| | LEGEND - FINISH |
|--------|-----------------------------|
| ACT | ACOUSTICAL CEILING TILE |
| CMU-P | CMU PAINTED |
| CONC-S | CONCRETE - SEALED |
| CPT | CARPET |
| CT-1 | CERAMIC TILE |
| LP | LINER PANEL |
| Р | PAINTED |
| STR | EXPOSED STRUCTURE |
| STR-P | EXPOSED STRUCTURE - PAINTED |
| VB | 4" VINYL BASE |
| VCT | VINYL COMPOSITION TILE |
| VI | VINYL INSULATION |

NOTES: 1.

- BRUSHED ALUM.

3" WHITE TACTILE ROOM NUMBER WITH HELVETICA NEUE 55 ROMAN




5

REFER TO WALL TYPES AND CEILING PLAN FOR SOUND BATT INSULATION REQUIREMENTS

| Michael E INTERNAT 1501 LBJ FREEW/ SUITE 650 DALLAS, TX 75234 | ional Ay, |
|---|--|
| Consultant | JR. 9683 |
| | DESCRIPTION REVISIONS |
| | NO. DATE |
| HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 | ROOM FINISH SCHEDULE & SIGNAGE DETAILS |
| Project Number: 181261 Date: 02-05-202 Scale: AS NOTE Sheet # A-60 | D |

| | | | | | | | | | SCHEDU | JLE - DOO | R - ALL | | | | |
|------|---|----------|----------|----------|--------|----------------------------------|--------|------|--------------|-----------------|----------|-----------------|------|-----------------|---|
| | | | SIZ | Ξ | | DOOR | | | FRAME | | DET | TAILS RA | TING | | |
| DOOR | | HEIGHT | WIDTH | THICKNES | S TYPE | DESCRIPTION | FINISH | TYPE | DESCRIPTION | FRAME FINISH | HEAD | JAMB FIRE | STC | HARDWARE SET | COMMENTS |
| 100A | | | 85' - 0" | 1' - 0" | D | HANGAR DOOR SLIDING | CSI | - | - | - | 2/A-611 | 3/A-611 | | 9 | INSULATED PEMB WALL PANELS AND LINER PANELS |
| 100B | 3 | 12' - 0" | 12' - 0" | | С | OVERHEAD SECTIONAL STEEL | CSI | - | - | - | 7/A-612 | 8/A-612 | | 10 | INSULATED, VERTICAL LIFT |
| 100C | 2 | 7' - 0" | 3' - 0" | 1 3/4" | A | EXTERIOR | PTD | F1 | HOLLOW METAL | PTD | 1/A-612 | 2/A-612 | | 11 | INSULATED |
| 100D |) | 7' - 0" | 3' - 0" | 1 3/4" | A | EXTERIOR | PTD | F1 | HOLLOW METAL | PTD | 1/A-612 | 2/A-612 | | 11 | INSULATED |
| 101 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR WOOD FLUSH (SOLID CORE) | WD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 2 | |
| 102 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR WOOD FLUSH (SOLID CORE) | WD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 2 | |
| 103A | 4 | 7' - 0" | 3' - 0" | 1 3/4" | В | EXTERIOR STOREFRONT | ALUM | F1 | PER MANUF | ALUM | 4/A-611 | 5/A-611 | | 1 | INSULATED |
| 103B | 3 | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR HOLLOW METAL RATED | PTD | F2 | HOLLOW METAL | PTD | 10/A-612 | 11/A-612 90 MIN | | 4 | |
| 103C |) | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR HOLLOW METAL RATED | PTD | F2 | HOLLOW METAL | PTD | 10/A-612 | 11/A-612 90 MIN | | 4 | |
| 103D |) | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR HOLLOW METAL RATED | PTD | F2 | HOLLOW METAL | PTD | 10/A-612 | 11/A-612 90 MIN | | 4 | |
| 104 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR WOOD FLUSH (SOLID CORE) | WD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 5 | |
| 105 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR WOOD FLUSH (SOLID CORE) | WD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 3 | |
| 106 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR WOOD FLUSH (SOLID CORE) | WD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 8 | |
| 107 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR WOOD FLUSH (SOLID CORE) | WD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 8 | |
| 108A | 4 | 8' - 0" | 12' - 0" | 2" | С | OVERHEAD SECTIONAL STEEL | CSI | - | - | - | 7/A-612 | 8/A-612 | | 9 | INSULATED, STANDARD LIFT |
| 108B | 3 | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR HOLLOW METAL | PTD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 3 | |
| 108C |) | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR HOLLOW METAL RATED | PTD | F2 | HOLLOW METAL | PTD | 10/A-612 | 11/A-612 90 MIN | | 4 | |
| 109 | | 7' - 0" | 6' - 0" | 1 3/4" | AA | INTERIOR HOLLOW METAL RATED | PTD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 45 MIN | | 6 | |
| 110 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR WOOD FLUSH (SOLID CORE) | WD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 7 | |
| 111 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR HOLLOW METAL RATED | PTD | F2 | HOLLOW METAL | PTD | 10/A-612 | 11/A-612 90 MIN | | 7 | |
| 112 | | 7' - 0" | 3' - 0" | 1 3/4" | A | INTERIOR HOLLOW METAL | PTD | F1 | HOLLOW METAL | PTD | 4/A-612 | 5/A-612 | | 7 | |




A

| 1 | |
|---|--|
| | |
| | |

5

| | LEGEND - DOOR FRAME | |
|------|---|---------------------|
| TYP | E DESCRIPTION | 1501 LBJ FREEWAY, |
| - | NONE | SUITE 650 |
| AC | ACCESS | DALLAS, TX 75234 |
| AL | ALUMINUM | |
| CS | CUSTOM STEEL | |
| HM | HOLLOW METAL | |
| MSS | METAL SCREEN AND STORM | |
| PAM | PRE-ASSEMBLED METAL | |
| SS | STANDARD STEEL | |
| WD | WOOD | |
| | LEGEND - DOOR LEAF | Consultant |
| TYPE | DESCRIPTION | |
| AC | ACCESS | POPOVICH, JR. |
| AE | AUTOMATIC ENTRANCE | License Number 9683 |
| AFE | ALUMINUM-FRAMED ENTRANCE | and a second second |
| AGE | ALL-GLASS ENTRANCE | PF ARKANST |
| CL | CHAIN LINK | SEAL 02/05/202/ |
| CS | CUSTOM STEEL | |
| CSI | CUSTOM STEEL (INSULATED) | |
| FD | FOLDING | |
| HM | HOLLOW METAL | |
| HMI | HOLLOW METAL (INSULATED) | |
| MSS | METAL SCREEN AND STORM | |
| 00 | OVERHEAD COILING | |
| OCI | OVERHEAD COILING (INSULATED) | |
| OSA | OVERHEAD SECTIONAL ALUMINUM | |
| OSAI | OVERHEAD SECTIONAL ALUMINUM (INSULATED) | DESCRIPTION |
| OSS | OVERHEAD SECTIONAL STEEL | |
| OSSI | OVERHEAD SECTIONAL STEEL (INSULATED) | |
| OSW | OVERHEAD SECTIONAL WOOD | |
| PAM | PRE-ASSEMBLED METAL | |
| PAMI | PRE-ASSEMBLED METAL (INSULATED) | |
| RE | REVOLVING ENTRANCE | |
| SAF | SLIDING ALUMINUM-FRAMED GLASS | DATE |
| SPF | SLIDING PLASTIC-FRAMED GLASS | |
| SRW | STILE AND RAIL WOOD | |
| SS | STANDARD STEEL | o |
| SWF | SLIDING WOOD-FRAMED GLASS | |
| WC | WOOD CLOSET | |
| WDHC | WOOD FLUSH (HOLLOW CORE) | |
| WDSC | WOOD FLUSH (SOLID CORE) | |
| | | |

| | SCHEDULE - WINDOW |
|----|-------------------|
| W1 | FIXED WINDOW |
| W2 | FIXED WINDOW |
| W3 | FIXED WINDOW |



1. REFERENCE ELEVATIONS FOR CLERESTORY WINDOW HEIGHTS. 2. ALL WINDOWS ADJACENT TO DOORS OR INTEGRAL WITH DOOR

TO HAVE TEMP GLASS.

3. ALL WINDOWS TO HAVE SILL FLASHING & END DAMS SET IN


FULL BED OF SEALANT. 4. HORIZONTAL LOUVERS & BLINDS COORDINATE WITH OWNER.

WINDOW TYPES

SCALE:NTS

SCALE: 1" = 1' - 0"


5





Sheet #

© Baker 2021


A-611








| | 5 | | | |
|---------------|--|--|--------------------------|------------------|
| | | Michael B | ONAL | |
| AB TO REMAIN | | SUITE 650 DALLAS, TX 75234 | | |
| EWALK AND | | | | |
| IOLISHED | | | | |
| BE DEMOLISHED | | Consultant | | |
| | | | DESCRIPTION REVISIONS | |
| | | | NO. DATE | |
| | | HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 | DEMOLITION FLOOR PLAN | |
| PLAN NORTH | <u>0 4'-0" 8'-0" 16'-</u> 0" SCALE: 1/8" = 1'-0" 5 | Project Number: 181261 Date: 02-05-2021 Scale: AS NOTED Sheet # AD-11 © Baker 2021 |) | CONSTRUCTION SET |



| | 5 | | |
|--------------------|--|--|--|
| | NOTES - RCP ALL ELEVATIONS ARE ABOVE FINISHED FLOOR. REFER TO ELECTRICAL DRAWINGS FOR POWER AND LIGHTING INFORMATION REFER TO MECHANICAL DRAWINGS FOR VENTILATION AND HEATING VENTILATION AND AIR CONDITIONING INFORMATION ALL CEILING GRIDS TO BE CENTERED IN ROOMS - TYPICAL UNLESS NOTED OR DIMENSIONED OTHERWISE LIGHT FIXTURES IN GWB CEILINGS SHALL BE CENTERED IN ROOMS - REF; ELECTRICAL DRAWINGS FOR LOCATION. ALL EXPOSED DUCTWORK, PIPES, CONDUIT AND STRUCTURE SHALL BE CLEAN AND FREE OF ANY MANUFACTURER OR CONSTRUCTION DEFECTS THE SUSPENDED CEILING SYSTEM, MECHANICAL DUCTWORK AND LIGHTING FIXTURES SHALL BE POSITIVELY ATTACHED TO THE STRUCTURE ABOVE | Consultant | |
| 1 A-202 | | DATE DESCRIPTION REVISIONS | |
| | RCP LEGEND 2x2' ACOUSTICAL CEILING PANEL 2x4 ACOUSTICAL CEILING PANEL 3x4 ACOUSTICAL SEE E-SERIES 3x4 MECHANICAL GRILLE SEE M-SERIES 3x4 MECHANICAL FIXTURES SEE E-SERIES 3x4 MECHANICAL SIGN SEE E-SERIES 3x5 MECHANICAL SIGN SEE E-SERIES </th <th>HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 REFLECTED CEILING PLAN</th> <th></th> | HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 REFLECTED CEILING PLAN | |
| PLAN NORTH N | 0 4'-0" 8'-0" 16'-0" SCALE: 1/8" = 1'-0" | Project Number: 181261 Date: 02-05-2021 Scale: AS NOTED Sheet # AR110 © Baker 2021 | |




5

| MATERIAL LEGEND | | | | | | |
|-----------------|--|--|--|--|--|--|
| | EXISTING CONCRETE SLAB TO REMAIN | | | | | |
| | NEW CONCRETE REF; STRUCTURAL AND DEMOLITION DRAWINGS | | | | | |

NOTES:


1. PROVIDE NEW CONCRETE AS NEEDED FOR INSTALLATION OF BOLLARDS, DRAINS, PIPING, AND MISC. REFERENCE OTHER DISCIPLINES FOR MORE INFORMATION.



- SLOPE FLOOR TO 1/8" / 1'-0" SCUPPER AND PROVIDE SLOT @ TRACK TO DRAIN

- DRAINAGE THROUGH WALL SCUPPER





5

SCALE: 1/8" = 1' - 0"

© Baker 2021

| 1 | | 2 |
|---|-----|--|
| | I | |
| | | ELECTRICAL GENERAL NOTES |
| | 1. | CONTRACTOR IS RESPONSIBLE FOR COORDINATING ALL INSTALLATION WITH THE WORK OF OTHER TRADES. FIELD MODIFICATIONS NEEDED DUE TO OBSTRUCTIONS OR INTERFERENCES SHALL BE PROVIDED AT NO ADDITIONAL COST. |
| | 2. | ALL WORK SHALL BE PERFORMED IN A NEAT AND WORKMANLIKE MANNER WITHIN STANDARD OF CARE FOR PROFESSION. ALL LABOR, MATERIAL, TOOLS, PERMITS, INSPECTIONS, TESTING, CERTIFICATION, ETC. REQUIRED FOR A COMPLETE AND SATISFACTORY INSTALLATION TO DESIGN INTENT SHALL BE FURNISHED BY CONTRACTOR. PROVIDE, AT NO ADDITIONAL COST, INCLUDING INCIDENTAL ITEMS NOT SHOWN WHEN REQUIRED FOR TYPICAL COMPLETION OF WORK. |
| | 3. | DRAWINGS NOT BEARING THE STAMP OR SEAL AND SIGNATURE OF A REGISTERED PROFESSIONAL ENGINEER SHALL NOT BE USED FOR BIDDING OR CONSTRUCTION PURPOSES UNLESS EXPRESSLY APPROVED IN WRITING BY THE ARCHITECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL DRAWINGS AND SPECIFICATIONS BEING USED FOR BIDDING AND CONSTRUCTION PURPOSES ARE OF THE LATEST REVISION AVAILABLE AND ALL ADDENDUM DOCUMENTS HAVE BEEN INCORPORATED EITHER BY REVISION RELEASE OF DRAWINGS/SPECIFICATIONS OR ATTACHMENT OF SKETCHES OR OTHER ADDENDUM INFORMATION. |
| | 4. | THE CONTRACTOR SHALL FURNISH AND INSTALL NEW PRODUCTS OF ESTABLISHED AND REPUTABLE MANUFACTURERS. NO EQUIPMENT SUBSTITUTIONS SHALL BE MADE THAT WOULD LEAVE INADEQUATE OPERATING OR SERVICE SPACE. EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDED INSTALLATION PROCEDURES AND IN AN ARRANGEMENT THAT WILL GIVE THE GREATEST PRACTICAL EASE OF OPERATION AND SERVICE TO THE OWNER. |
| | 5. | ALL EQUIPMENT WHICH IS INDICATED TO BE FURNISHED AND/OR INSTALLED BY OTHERS OR BY OWNER IS INCLUDED FOR REFERENCE ONLY UNLESS NOTED OTHERWISE. CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING AND VERIFYING INSTALLATION REQUIREMENTS OF THIS EQUIPMENT WITH THE APPLICABLE SUPPLIER OR THE OWNER. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER. |
| | 6. | ALL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF ALL APPLICABLE CODES AND REGULATIONS INCLUDING BUT NOT LIMITED TO NATIONAL, CITY, STATE, LOCAL ORDINANCES, AND UTILITY COMPANY REGULATIONS. ALL PLUMBING MATERIALS, INSTALLATION PROCEDURES, AND SYSTEM LAYOUTS SHALL BE APPROVED BY ALL APPLICABLE AUTHORITIES HAVING JURISDICTION. THE CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR NECESSARY TO COMPLY WITH THESE RULES, REGULATIONS, AND ORDINANCES. THESE CODES REPRESENT THE MINIMUM ACCEPTABLE REQUIREMENTS, THEREFORE, WHERE DRAWINGS AND/OR SPECIFICATIONS INDICATE MATERIALS OR CONSTRUCTION MORE STRINGENT THAT CODE REQUIREMENTS, THE DRAWINGS AND/OR SPECIFICATIONS SHALL GOVERN. |
| | 7. | IF COMPLIANCE WITH STANDARDS, CODES, REGULATIONS AND CONTRACT DOCUMENTS ESTABLISH DIFFERENT OR CONFLICTING REQUIREMENTS FOR MINIMUM QUANTITIES OR QUALITY LEVELS, REFER CONFLICTING REQUIREMENTS TO ENGINEER FOR A DECISION BEFORE PROCEEDING. |
| | 8. | WHERE CONTRACT DOCUMENTS NAME A SINGLE MANUFACTURER AND PRODUCT, PROVIDE THE NAMED PRODUCT THAT COMPLIES WITH REQUIREMENTS. COMPARABLE PRODUCTS OR SUBSTITUTIONS FOR CONTRACTOR'S CONVENIENCE WILL BE CONSIDERED. |
| | 9. | THE PROJECT CLOSEOUT SUBMITTALS SHALL INCLUDE, BUT NOT LIMITED TO, OPERATION AND MAINTENANCE MANUALS AND RECORD DRAWINGS. |
| | 10. | THE CONTRACTOR SHALL VISIT THE SITE OF THE BUILDING BEFORE SUBMITTING A PROPOSAL ON THIS WORK AND SHALL THOROUGHLY FAMILIARIZE HIMSELF WITH THE EXISTING CONDITIONS AND OPERATIONS. FAILURE ON HIS PART TO DO THIS WILL NOT BE CAUSE OF EXTRAS AFTER THE CONTRACT IS SIGNED, BY REASON OF UNFORESEEN CONDITIONS. |
| | 11. | NO PERSON SHALL PERFORM ELECTRICAL WORK ON THE CONTRACT WITHOUT POSSESSING A MASTER'S OR JOURNEYMAN'S LICENSE FROM THE STATE ELECTRICAL EXAMINERS BOARD. ALL ELECTRICAL WORK AND APPRENTICE ELECTRICIANS SHALL BE SUPERVISED BY A MASTER JOURNEYMAN ELECTRICIAN ON A ONE TO ONE RATIO. |
| | 12. | PREPARE AND SUBMIT SUBMITTALS TO ARCHITECT. |
| | 13. | ALL AREAS USED AS RETURN AIR PLENUMS SHALL BE CONSTRUCTED WITH FIRE RESISTANT MATERIALS AND SHALL ONLY CONTAIN MATERIALS WHICH HAVE SMOKE DEVELOPED RATINGS NOT GREATER THAN 50 AND FLAME SPREAD RATINGS NOT GREATER THAN 25. |
| | 14. | ALL ELECTRICAL EQUIPMENT, SUCH AS SWITCHES, CIRCUIT BREAKERS, ETC. SHALL BE TESTED BY OPERATING THE DEVICE TO VERIFY THAT THE MECHANICAL PORTIONS OF THE DEVICE ARE FUNCTIONING. |
| | 15. | THE CONTRACT SHALL ASSIST ALL OTHER TRADES IN PERFORMING ROTATIONAL TESTS ON ALL MOTORS PROVIDED UNDER THIS CONTRACT. |
| | 16. | ALL EXPOSED CONDUIT SHALL BE GALVANIZED RIGID STEEL, SIZED AS SCHEDULED. |
| | 17. | WIRE SIZE PER CODE UNLESS NOTED ELSEWHERE: |
| | | WIRE SIZE 120V WIRE SIZE 277V |
| | | A. #12 LESS THAN 75 FEETLESS THAN 150 FEETB. #10 BETWEEN 75-150 FEETBETWEEN 150-300 FEETC. #8 BETWEEN 150-250 FEETBETWEEN 300-450 FEETD. #6 BETWEEN 250-375 FEETBETWEEN 450-700 FEET |
| | | |

D

1

А

В

С

3

| Image: Source of the second | | LEG | GEND | |
|---|----------------------|--|--------------------|---|
| ID- WALL PACK LEART TRUBUE. ID- PL-ASTER INC. INC. ID- ID- RECESSED DOWN LIGHT. ID- CONSTRUE OF INT. THE ANNUE OF INC. ID- ID- XALLED TROFFER. ID- WALLED TROFFER. ID- ID- XALLED TROFFER. ID- MANUAE PULL BY TROFFER. ID- ID- XALLED TROFFER. ID- MANUAE PULL BY TROFFER. ID- ID- WALLED TROFFER. ID- MANUAE PULL BY TROFFER. ID- ID- WALLED TROFFER. ID- MANUAE PULL BY TROFFER. ID- ID- WALLED TROFFER. ID- ID- ID- ID- WALLED TROFFER. ID- ID- ID- ID- WALLED TROF | | WALL MOUNT STRIP LIGHT. | | |
| Indexage Down Lott: Content of the Property Lott: Content of the Property Content of | | WALL PACK LIGHT FIXTURE. | ∇ | PLASTER RING, AND 1" C. ST |
| 2041 FD TROPERE ON ENERGENCY ROWER. Production of the second of the | D | RECESSED DOWN LIGHT. | | |
| 2X1_LD TIOPPER ON EXPERION EVENONER. NUMBER ENDOTS: CAMPA XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCY POWER. XX1_ED TOOPPER ON EMERGENCE POWER. XX1_ED TOOPPER ON EMERGENCE POWER ON EXCLUSION TO PER PRINT POWER POWER ON EXCLUSION TO PER PRINT POWER POWER PRINT POWER POWER PRINT POWER POWER PRINT | | 2X4 LED TROFFER. | E | |
| EI EI <td< td=""><td></td><td>2X4 LED TROFFER ON EMERGENCY POWER.</td><td></td><td>NUMBER DENOTES CANDEL</td></td<> | | 2X4 LED TROFFER ON EMERGENCY POWER. | | NUMBER DENOTES CANDEL |
| Image: Set LED TROPPER ON PARENCY POWER. Image: Set LED TROPPER ON PARENCY POWER. Image: Set LED TROPPER ON PARENCY POWER. Image: Set LED TROPPER ON PARENCY POWER. Image: Set LED TROPPER ON PARENCY POWER. Image: Set LED TROPPER ON PARENCY POWER. Image: Set LED TROPPER ON PARENCY POWER. Image: Set LED TROPPER ON PARENCY LIGHT Image: Set LED TROPPER ON PARENCY LIGHT Image: Set LED TROPPER ON PARENCY LIGHT Image: Set LED TROPPER ON PARENCY LIGHT Image: Set LED TROPPER ON PARENCY LIGHT Image: Set LED TROPPER ON PARENCY LIGHT POY DE CONTROL PARENCY LIGHT POY PARENCY LIGHT POWER PARCNY LIGHT POWER PARENCY LIGHT | | 2X2 LED TROFFER. | FK | |
| WALL LIGHT (s) CELLING MOUNTED PHOTO CELLING MOUNTED FLORT (e) GELING MOUNTED FLORT SINGLE POLE SWITCH TYPE 121, CP DENOTES DIMMER, '2" SWAY, '4', 4 (f) GELING MOUNTED FLORT MALL LIGHT (f) GELING MOUNTED FLORT (f) GELING MOUNTED FLORT GELING MOUNTED FLORT (f) (f) | (D) _{ID} | 2X2 LED TROFFER ON EMERGENCY POWER. | | NUMBER DENOTES CANDEL |
| EMERGENCY LIGHT ENERGENCY LIGHT Image: Strain S | | 4' LED STRIP | K | MANUAL PULL STATION MOL |
| ENERGENCY LIGHT IS GELING MOUNTED HEAT LIST SINGLE POLE SWITCH TYPE 121. D' DENOTES DIMMER, '3' S-WAY, '4' - 4 IS IS SPRINKLER SYSTEM FLOW MOUNTED LIST AFF UNESCHOPEN. WAL COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. WO COORDINATE WITH HEXTURES AND TYPE AND CIRCUIT WATTAGE. COORDINATE WITH HEXTURE AND CIRCUIT WATTAGE. COORDINATE CIRCUIT WATTAGE. COORDINATE WITH HEXTURE AND CIRCUIT WATTAGE. COORDINATE WATTAGE. | D | WALL LIGHT | (\mathbf{S}) | CEILING MOUNTED PHOTOEI |
| EMERGENCY DATA EMERGENCY DATA SINCLE POLE SWITCHERT PROTECTED DAMAGE, "Y 3WAY, "A' 4 MOUNT OF COLORANTE WITCHERT ALL AND "YTE MOUTED DAMAGE, "Y 3WAY, "A' 4 MOUNT DATA FUELES ON EXCOMPENDATION END CARCIUM WATTAGE." MOUNT DATA FUELESS OTHERWISE MOTED. WALL MOUNTED BALTECH MOTION SENSOR SWITCH WIRE PER MOUNT PER ALARM ANNUNCIATO FIRE FIRE ANNUNCIA CONTROL FIRE FIRE ANNUNCIATON FIRE FIRE ALARM ANNUNCIATO FIRE FIRE ALARM ANNUNCIATO FIRE FIRE FIRE ALARM ANNUNCIATO FIRE FIRE FIRE FIRE FIRE FIRE FIRE FIRE | | | _ | CEILING MOUNTED HEAT DE |
| SINGLE POLE SWITCH TYPE Tay. "D' DENOTES DIMMER, "3" 3" XXX, "4".4 Image: Coordinate Switch Type Type And Control Wart Set. MOUNT IS AFF UNLESS OTHERWISE NOTED. Image: Type Type And Control Park Type Type Type Type Type Type Type Type | 17 | EMERGENCY LIGHT | <u> </u> | SPRINKLER SYSTEM FLOW |
| MOUNT SF AFF UNLESS OF INTERMISE NOTED. COORDINATE OUNTED AND SENSOR SWITCH WIRE PER MANUFACTURED SAUSTER FAW WITH LUSTS. IFRE ALARM CONTROL PAGE PRE ALARM ANNUCATO PRE ALARM CONTROL PAGE PRE ALARM ANNUCATO PRE ALARM CONTROL PAGE PRE ALARM CONTROL PAGE PRE ALARM ANNUCATO PRE ALARM CONTROL PAGE PRE ALARM CONTROL PAGE PRE ALARM ANNUCATO PRE ALARM | \$ \$0 6 | WAY. COORDINATE WITH FIXTURE/LAMP TYPE AND CIRCUIT WATTAGE. | | |
| ALL MANUFACTURERS RECOMMENDATION. PROVIDE CONTACTORS TO PHER ALARM MUNICATO PHER ALARM MU | Ф3 \$4 | | | COORDINATE QUANTITY AND |
| LogITAL TIMER SWITCH, EQUAL TO WATTSTOPPER. PUSEDNON-INCIDENT Lin PHASED SWITCH, USED FOR EQUIPMENT DISCONNECTING MEANS, SINGLE PHEF PHEFMONINGATION FOR THE RECOMMENDATION STATER WITH THERMAL OVERLOAD RELAYS SIZED PER MOTOR LOAD. REAMCH CIRCUIT HOMERUN, PANEL AND CIRCUIT NUMBER INDICATED. PC COMBINATION MACINETCO: Common Person Provide ADD Common Person Pe | \$00 | MANUFACTURERS RECOMMENDATION. PROVIDE CONTACTORS TO | | FIRE ALARM CONTROL PANE |
| MOTOR RATED SWITCH USED FOR EQUIPMENT DISCONNECTING MEANS SINGLE IFF RECOMBINATION PART SIZED FER MOTOR LOAD. IFF RECOMBINATION PART IFF RECOMBINATION PART SWITCH 199 AFF. IFF RECOMBINATION PART IFF IFF RECOMBINATION PART SWITCH 199 AFF. IFF RECOMBINITY WITH 199 AFF. IFF IFF RECOMBINITY WITH 199 AFF. IFF IFF RECOMPART SWITCH 199 AFF. IFF RECOMPART IFF IFF <t< td=""><td>\$at</td><td></td><td></td><td></td></t<> | \$at | | | |
| Control of the field of the field of the provide and the p | | MOTOR RATED SWITCH USED FOR EQUIPMENT DISCONNECTING MEANS. SINGLE PHASE: PROVIDE MANUAL MOTOR STARTER WITH THERMAL OVERLOAD RELAYS | | FUSED/NON-FUSED DISCONI RECOMMENDATION FOR THE THE KITCHEN. MOUNT DISCO SWITCH AT 36" A.F.F. |
| CELLING MOUNTED DUAL TECH. OCCUPANCY SENSOR. PROVIDE AND INSTALL TIME CLOCK OR LIGHTING APPROPRIATE POWER PACK. COORDINATE SWITCHING, LOCATION AND OUNTITY WITH IC CONTROL APPLICATIONS. PROVIDE CONTROL'S SENSOR USED. WIER PER MANUPACTURERS RECOMMENDATION. IC CONTROL APPLICATIONS. PROVIDE CONTROL'S SENSOR USED. IL IC CONTROL APPLICATIONS. PROVIDE CONTROL'S SENSOR USED. IL IL CONTROL APPLICATIONS. CC WALL MOUNTED DUAL TECH. OCCUPANCY SENSOR. PROVIDE AND INSTALL IL IL OWNER'S REPRESENTATION CC WALL MOUNTED DUAL TECH. OCCUPANCY SENSOR USED. IL IL IL OWNER'S REPRESENTATION CC WALL MOUNTED DUAL TECH. OCCUPANCY SENSOR USED. IL IL IL OWNER'S REPRESENTATION CC WALL MOUNTED DUAL TECH. OCCUPANCY SENSOR USED. IL IL IL OWNER'S REPORTS TO WITH INSTALL IL IL IL IL IUNCTION ROX. VERIFY MUTH INSTALL IUNCTION ROX. VERI | | BRANCH CIRCUIT HOMERUN. PANEL AND CIRCUIT NUMBER INDICATED. | $\vdash \boxtimes$ | COMBINATION MAGNETIC ST EQUIPMENT FURNISHED. |
| WALL MOUNTED DUAL TECH OCCUPANCY SENSOR PROVIDE AND INSTALL OWNERS REPRESENTATIN WALL MOUNTED DUAL TECH OCCUPANCY SENSOR PROVIDE AND INSTALL OWNERS REPRESENTATIN ACTUAL OCCUPANCY SENSOR USED. WIRE PER MANUFACTURERS RECOMMENDATION. OWNERS REPRESENTATIN ACTUAL OCCUPANCY SENSOR USED. WIRE PER MANUFACTURERS RECOMMENDATION. OWNERS REPRESENTATIN ACTUAL OCCUPANCY SENSOR EQUAL TO WATTSTOPPER. EXIT SIGN/COMBINATION EXIT ACTUAL OCCUPANCY SENSOR EQUAL TO WATTSTOPPER. EXIT SIGN/COMBINATION EXIT/EMERGENCY LIGHT (WITH DIRECTIONAL ARROWS). ACTUAL SIGN/COMBINATION EXIT/EMERGENCY LIGHT (WITH STROBES). EXIT SIGN/COMBINATION EXIT/EMERGENCY LIGHT (WITH STROBES). ACTUAL RECEPTACLE (TYPE 5362). MOUNT 18' AFF UNLESS OTHERWISE NOTED. EXIT SIGN/COMBINATION EXIT/EMERGENCY LIGHT. DUPLEX RECEPTACLE (TYPE 5362). MOUNT 18' AFF UNLESS OTHERWISE NOTED. EXIT SIGN/COMDINERCUP FAULT TYPE GF5362. DUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. EXIT SIGN/COMPLEX RECEPTACLE MOUNTED ABOVE COUNTER. CUADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. EXIT SIGN/COMPLEX RECEPTACLE AS NOTED ON THE PLANS. ACTUAL RECEPTACLE AS NOTED ON THE PLANS. ELECTRICAL PANEL. Image: Special RECEPTACLE AS NOTED ON THE PLANS. Image: Special RECEPTACLE AS NOTED ON THE PLANS. Image: Special RECEPTACLE AS NOTED ON THE PLANS. Image: Special RECEPTACLE AS NOTED ON THE PLANS. Image: | 00 | APPROPRIATE POWER PACK. COORDINATE SWITCHING, LOCATION AND QUANTITY WITH ACTUAL OCCUPANCY SENSOR USED. WIRE PER MANUFACTURERS RECOMMENDATION. PROVIDE OCCUPANCY SENSOR EQUAL TO WATTSTOPPER. | | TIME CLOCK OR LIGHTING CONTROL APPLICATIONS. IN CONTACTOR: SQUARE D #89 |
| Image: A stripped bit stri | 2 | APPROPRIATE POWER PACK. COORDINATE SWITCHING, LOCATION AND NUMBER WITH ACTUAL OCCUPANCY SENSOR USED. WIRE PER MANUFACTURERS RECOMMENDATION. | | JUNCTION BOX. VERIFY MOU OWNER'S REPRESENTATIVE WITH THE EQUIPMENT INSTA |
| Image: State Sign/Combination Exit/Emergency Light (with Strobes). Image: State Sign/Combination Exit/Emergencombinatingence Imag | A | EXIT SIGN/COMBINATION EXIT | | |
| WALL MOUNTED EXIT SIGN/COMBINATION EXIT/EMERGENCY LIGHT. UPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. UADRUPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. UPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UADRUPLEX RECEPTACLE. EMERGENCY RECEPTACLE. EMERGENCY RECEPTACLE. ELECTRICAL PANEL. ILEPHONE TERMINAL BOARD ILEPHONE TERMINAL BOARD | ØA | EXIT SIGN/COMBINATION EXIT/EMERGENCY LIGHT (WITH DIRECTIONAL ARROWS). | | |
| DUPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. UADRUPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. UPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UDUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UDUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UDUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. EMERGENCY RECEPTACLE. SPECIAL RECEPTACLE AS NOTED ON THE PLANS. Image: Special RECEPTACLE AS NOTED AS NOT | A | EXIT SIGN/COMBINATION EXIT/EMERGENCY LIGHT (WITH STROBES). | | |
| DUPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. UADRUPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. UPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UDUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UDUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UDUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UDUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UDUPLEX RECEPTACLE. UDUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UDUPLEX RECEPTACLE. UDUPLEX RECEPTACLE AS NOTED ON THE PLANS. Image: Duplex Particle Panel. Image: Duplex Panel. | | WALL MOUNTED EXIT SIGN/COMBINATION EXIT/EMERGENCY LIGHT. | | |
| DUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UADRUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UPLEX RECEPTACLE GROUND FAULT TYPE GF5362. UPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UADRUPLEX RECEPTACLE. UADRUPLEX RECEPTACLE. UPLEX RECEPTACLE AS NOTED ON THE PLANS. | ⇐ | DUPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. | | |
| Image: Constraint of the constraint o | ⊕= | QUADRUPLEX RECEPTACLE (TYPE 5362). MOUNT 18" AFF UNLESS OTHERWISE NOTED. | | |
| DUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. UADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. Harden Bergency Receptacle Mounted Above Counter. Precial Receptacle Mounted Above Counter. Bergency Receptacle Mounted Above Counter. Bergency Receptacle. Bergency Receptacle As NOTED ON THE PLANS. Image: Deleta Receptacle As NOTED | \ominus | DUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. | | |
| QUADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. EMERGENCY RECEPTACLE. SPECIAL RECEPTACLE AS NOTED ON THE PLANS. Image: | ⊕= | QUADRUPLEX RECEPTACLE GROUND FAULT TYPE GF5362. | | |
| EMERGENCY RECEPTACLE. SPECIAL RECEPTACLE AS NOTED ON THE PLANS. Image: transform of the plane in | \ominus | DUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. | | |
| SPECIAL RECEPTACLE AS NOTED ON THE PLANS. Image: special receptacle as noted on the | \rightleftharpoons | QUADRUPLEX RECEPTACLE MOUNTED ABOVE COUNTER. | | |
| Image: Image | ⊖= | EMERGENCY RECEPTACLE. | | |
| Image: Telephone terminal board Image: Telephone terminal board Image: Telephone terminal board Image: Telephone terminal board <td>\ominus-</td> <td>SPECIAL RECEPTACLE AS NOTED ON THE PLANS.</td> <td></td> <td></td> | \ominus - | SPECIAL RECEPTACLE AS NOTED ON THE PLANS. | | |
| 1 REVISION DELTA. | | ELECTRICAL PANEL. | | |
| | -3 | TELEPHONE TERMINAL BOARD | | |
| | | | | |

SUBSCRIPTS: GFI = GROUND FAULT CIRCUIT INTERRUPTER. WP = WEATHER RESISTANT RECEPTACLES ARE "GFI", WITH

METAL WEATHER RESISTANT "WHILE-IN-USE" COVERS. GD = GARBAGE DISPOSER. EM = FIXTURE CONTAINS EMERGENCY BATTERY PACK. NL = UNSWITCHED EMERGENCY FIXTURE. AFF = ABOVE FINISHED FLOOR

AFG = ABOVE FINISHED GRADE

EWC = ELECTRIC WATER COOLER

EWH = ELECTRIC WATER HEATER GWH = GAS WATER HEATER

NTS = NOT TO SCALE

3

4

| PHONE/DATA: REQUIRES 4" SQUARE OUTLET BOX, APPROPRIATE | |
|--|--|
|) 1" C. STUBBED TO AN ACCESSIBLE LOCATION ABOVE A | |
| G TILE. BOX AND CONDUIT ONLY. MOUNT 18" AFF UNLESS | |

LARM VISUAL STROBE-WP DENOTES WEATHER RESISTANT. E BOX WITH B" CONDUIT STUBBED ABOVE ACCESSIBLE CEILING. ANDELA RATING. MOUNT 80" AFF UNLESS OTHERWISE NOTED.

LARM HORN/STROBE-WP DENOTES WEATHER RESISTANT. RE BOX WITH B" CONDUIT STUBBED ABOVE ACCESSIBLE CEILING. ANDELA RATING. MOUNT 80" AFF UNLESS OTHERWISE NOTED.

ON MOUNTED MINIMUM OF 42"; MAXIMUM OF 48" A.F.F.

HOTOELECTRIC SMOKE DETECTOR.

EAT DETECTOR.

FLOW AND TAMPER SWITCHES.

JRNISHED AND INSTALLED BY THE FIRE ALARM CONTRACTOR. TITY AND LOCATION WITH MECHANICAL PLANS.

DL PANEL MOUNTED 50" A.F.F.

CIATOR PANEL MOUNTED 52" A.F.F.


DISCONNECT-FUSE ALL EQUIPMENT PER MANUFACTURER FOR THE ACTUAL EQUIPMENT FURNISHED. FURNISH NEMA-4X IN T DISCONNECT FOR HVAC CONDENSER UNITS WITH TOP OF

ETIC STARTER/FUSIBLE DISCONNECT SWITCH; FUSE PER


ITING CONTACTOR: INTERMATIC #ET8215C FOR LIGHTING ONS. INTERMATIC #T2005 FOR CIRCULATION PUMPS. LIGHTING RE D #8903.


FY MOUNTING HEIGHT WITH MILLWORK DETAILS AND/OR THE NTATIVE. AT EQUIPMENT LOCATIONS VERIFY THE EXACT LOCATION

| SEAL | STATE | OF ISAS ERED IONAL 822 TON | REVISIONS |
|--------------------|---------------------|---|-----------|
| | | NO. DATE | REVIS |
| HANGAR REPLACEMENT | JONESBORO, AR 72401 | ELECTRICAL GENERAL NOTES AND LEGEND | |











D

В

С


3








| / | |
|---|---|
| FIRE ALARM MANUAL PULL STATION | |
| | |
| | |
| + | |
| | |
| | |
| ↑ ↑ ↑ | |
| RECEPTACLE | |
| DATA OUTLET | |
| 48" MAXIMUM UNLESS LOCATED ABOVE "OBSTRUCTION" SUCH AS A COUNTER," | |
| MAXIMUM, UNLESS NOTED ON PLANS | |
| | |
| | ł |
| t | |
| RECEPTACLE | |
| PHONE OUTLET | |
| EINISHED ELOOR | |





JUNCTION BOX GROUNDING DETAIL NOT TO SCALE: 2

CONTRACTOR TO VERIFY LOCATION OF EXISTING UTILITY TRANSFORMER PRIOR TO BID.

ELECTRICAL CONTRACTOR SHALL COORDINATE WITH LOCAL UTILITY PRIOR TO BID.

ALL COSTS AND FEES FOR SERVICE AND TEMPORARY SERVICE TO THE BUILDING SHALL BE BY THE ELECTRICAL CONTRACTOR.

DATA / VOICE RISER KEYED NOTES:

(1) TYPICAL OUTLET. BOX AND CONDUIT ONLY.

(2) MINIMUM CONDUIT DROP SIZE TO ALL DATA AND VOICE OUTLETS SHALL BE 1" AND SHALL EXTEND FROM OUTLET BOX TO ACCESSIBLE CEILING.

(3) 2-3"C WITH PULL STRING, STUB OUT 5'-0" FROM BUILDING

3



-5

E201

Sheet #

2

| TYPE | MANUFACTURER | CATALOG NUMBER | VOLTAGE | LAMP | COLOR | MOUNTING | NOTES |
|------|--------------|---|---------|------|-------|----------|--|
| А | COLUMBIA | LJT24-35MLG-FS12125-EDU | UNV | LED | 35K | GRID | 2X4 TROFFER |
| AE | COLUMBIA | LJT24-35MLG-FS12125-EDU-ELL14 | UNV | LED | 35K | GRID | 2X4 TROFFER WITH EMERGENCY |
| В | COLUMBIA | LJT22-35MLG-FS-A12125-EDU | UNV | LED | 35K | GRID | 2X2 TROFFER |
| BE | COLUMBIA | LJT22-35MLG-FS-A12125-EDU-ELL14 | UNV | LED | 35K | GRID | 2X2 TROFFER WITH EMERGENCY |
| С | BROWNLEE | 5180-37-CBA-H25-35K-BBI | UNV | LED | 35K | WALL | WALL MOUNTED LINEAR WITH EMERGENCY |
| D | COLUMBIA | CSL4-4035-GLH5 | UNV | LED | 35K | SURFACE | LED STRIP |
| F | BROWNLEE | 7037-C37-40 | UNV | LED | 40K | WALL | WALL PACK |
| FE | BROWNLEE | 7037-C37-40-BBC | UNV | LED | 40K | WALL | WALL PACK WITH EMERGENCY |
| G | BROWNLEE | 5180-49-CBA-H32-BBI | UNV | LED | 35K | WALL | WALL MOUNTED LINEAR WITH EMERGENCY |
| J | COLUMBIA | UTB2-735MM-EDU-WW16-N-CBA-C6HL-DLR-SCL | UNV | LED | 40K | PENDANT | HIGH BAY LIGHTING W/ OCC SENSOR |
| JE | COLUMBIA | UTB2-735MM-EDU-WW16-N-CBA-C6HL-ELL14-DLRSCL | UNV | LED | 40K | PENDANT | HIGH BAY LIGHTING WITH EMERGENCY &OCC SENSOR |
| EX2 | DUAL-LITE | LED-1-EM-R-WW | UNV | LED | NA | WALL | EXIT LIGHT |

NOTES: ALL FIXTURE COLORS TO BE SELECTED FROM MANUFACTURERS LIST OF STANDARD COLORS.

D

1

3

Notes:

Branch Panel: "A"

Location: SHOP 108 Supply From: Mounting: SURFACE Enclosure: NEMA 1

Volts: 120/240 Single Phase Phases: 1 Wires: 3

| | 1 | | | | | | | 1 | | | |
|----------|---|-------------|---------|------|----------|------|----------|--------|-------------|--|-----|
| | | | | | | | | | | | |
| скт | Circuit Description | Trip (A) | Poles | | 4 | | в | Poles | Trip (A) | Circuit Description | скт |
| 1 | RECEPTACLES - GFI BREAKER | 20 | 1 | 600 | 600 | | | 1 | | RECEPTACLES - GFI BREAKER | 2 |
| 3 | RECEPTACLES - GFI BREAKER | 20 | 1 | 000 | 000 | 1200 | 1000 | 1 | 20 | RECEPTACLES | 4 |
| 5 | RECEPTACLES | 20 | 1 | 1200 | 200 | 1200 | 1000 | 1 | | EWC - GFI BREAKER | 6 |
| 7 | RECEPTACLES | 20 | 1 | | | 1200 | 600 | 1 | | RECEPTACLES | 8 |
| 9 | RECEPTACLES | 20 | 1 | 1200 | 800 | | | 1 | | RECEPTACLES | 10 |
| 11 | RECEPTACLES - GFI BREAKER | 20 | 1 | | | 1200 | 1200 | 1 | | RECEPTACLES - GFI BREAKER | 12 |
| 13 | H-3 | 20 | 1 | 500 | 500 | | | 1 | 20 | H-2 | 14 |
| 15 | LIGHTING - GFI BREAKER | 20 | 1 | | | 1528 | 1518 | 1 | | LIGHTING - GFI BREAKER | 16 |
| 17 | LIGHTING - GFI BREAKER | 20 | 1 | 1518 | 1518 | | | 1 | | LIGHTING - GFI BREAKER | 18 |
| 19 | LIGHTING - GFI BREAKER | 20 | 1 | | | 1518 | 1528 | 1 | 20 | LIGHTING - GFI BREAKER | 20 |
| 21 | LIGHTING - GFI BREAKER | 20 | 1 | 972 | 586 | | | 1 | | LIGHTING | 22 |
| 23 | H-1 | 20 | 1 | - | | 500 | 7600 | 2 | | AIR COMPRESSOR VERIFY BREAKER WITH EQUIP | 24 |
| 25 | CU-1 | 50 | 2 | 3720 | 7600 | | | | | | 26 |
| 27 | | | | | | 3720 | 256 | 1 | 20 | EXTERIOR LIGHTING | 28 |
| 29 | EWC - GFI BREAKER | 20 | 1 | 200 | 500 | | | 1 | | GAS WATER HEATER | 30 |
| 31 | GRP-1 | 30 | 2 | | | 1380 | 1500 | 1 | | FACP | 32 |
| 33 | | | | 1380 | 7600 | | | 2 | | AIR COMPRESSOR VERIFY BREAKER WITH EQUIP | 34 |
| 35 | F-1 | 20 | 1 | | | 500 | 7600 | | | | 36 |
| 37 | EWC - GFI BREAKER | 20 | 1 | 200 | 200 | | | 1 | 20 | EWC - GFI BREAKER | 38 |
| 39 | EF-1 | 20 | 1 | | | 500 | 1200 | 1 | | RECEPTACLES - GFI BREAKER | 40 |
| 41 | HVLS-1 - GFI BREAKER | 20 | 1 | 500 | 500 | 000 | 1200 | 1 | 20 | HVLS-2 - GFI BREAKER | 42 |
| 43 | EF-5 | 25 | 2 | 500 | 500 | 1150 | 0 | 1 | 20 | TORK TIMECLOCK/PHOTECELL | 44 |
| 45 | | | | 1150 | 200 | 1150 | 0 | 1 | | TELEPHONE TERMINAL BOARD | 46 |
| 47 | HANGAR DOOR | 20 | 2 | 1150 | 200 | 2760 | 2760 | 2 | 20 | HANGAR DOOR | 48 |
| 49 | | | | 2760 | 2760 | 2700 | 2700 | | | | 50 |
| 49 51 | 240V WELDER | 75 | 2 | 2700 | 2700 | 4500 | 0 | 1 | | Spare | 52 |
| 53 | | | | 4500 | 0 | 4300 | 0 | 1 | | Spare | 52 |
| 55 | Spare | 20 | 1 | 4300 | 0 | 0 | 0 | 1 | | Spare | 56 |
| 57 | Spare | 20 | 1 | 0 | 0 | 0 | 0 | 1 | | Spare | 58 |
| 59 | Spare | 20 | 1 | 0 | 0 | 0 | 0 | 1 | | Spare | 60 |
| 61 | | 20 | | | | 0 | 0 | | 20 | Opare | 62 |
| 63 | | | | | | | | | | | 64 |
| 65 | | | | | | | | | | | 66 |
| 67 | | | | | | | | | | | 68 |
| 69 | | | | | | | | | | | 70 |
| 71 | | | | | | | | | | | 72 |
| 73 | | | | | | | | | | | 74 |
| 75 | | | | | | | | | | | 76 |
| 77 | | | | | | | | | | | 78 |
| 79 | | | | | | | | | | | 80 |
| 81 | | | | | | | | | | | 82 |
| 83 | | | | | | | | | | | 84 |
| | | Tota | I Load: | 4396 | 4 VA | 484 | 18 VA | | | | |
| | | | Amps: | | 6 A | | 03 A | | | | |
| Load | Classification | Connect | ed Load | | emand Fa | ctor | Estimate | d Dema | nd | Panel Totals | |
| Lightin | | 9108 | | | 100.00% | | | 8 VA | | | |
| Other | ع ــــــــــــــــــــــــــــــــــــ | | 4 VA | | 100.00% | | | 34 VA | | Total Conn. Load: 92382 VA | |
| HVAC | | 2300 | | | 100.00% | | | 0 VA | | Total Est. Demand: 36442 VA | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |


3

4

5

A.I.C. Rating: 22KAIC Bus Rating: 400 A MCB Rating: MLO

| ACEMENT | G DRIVE | HEDULES NO. DATE DESCRIPTION | REVISIONS |
|--------------------|---------------------|------------------------------|-----------|
| HANGAR REPLACEMENT | 3901 LINDBURG DRIVE | ELECTRICAL SCHEDULES | |



В

D








3

| ECTION | GEN | NERAL NOTES | Michael B | |
|--|------------|--|---|--|
| | GLI | | INTERNATI 1501 LBJ FREEWAY | |
| IMINARY I OF RESSED BY LIST BY THE | 17. | PROVIDE AND INSTALL QUICK RESPONSE SPRINKLERS FOR LIGHT HAZARD AND ORDINARY HAZARD AREAS, UNLESS OTHERWISE NOTED. | SUITE 650 DALLAS, TX 75234 | |
| LIST BY THE Y COMPLY AVING TALL ALL | 18. | ALL NEW CEILING MOUNTED SPRINKLER HEADS SHALL BE CHROME PENDENTS WITH CHROME RECESSED ESCUTCHEONS, UNLESS NOTED OTHERWISE ON FIRE PROTECTION PLANSOR SPECIFICATIONS. EXERCISE CAUTION AROUND CEILING MOUNTED DEVICES OR OPERABLE DOORS. INSTALL CONCEALED SPRINKLERS AS NEEDED TO ELIMINATE SPRINKLERSBEING AN | INSIGHT ENGINEERING, PLL No. 3523 | A CHARTON |
| ONS FOR RAL AND | 19. | OBSTRUCTION ISSUE WITH OTHER EQUIPMENT. ALL NEW WALL MOUNTED SPRINKLER HEADS SHALL BE CHROME HORIZONTAL SIDEWALLS WITH CHROME | The SS25 | C HONNING |
| S. RAL D AREAS OF | 20. | RECESSED ESCUTCHEONS, UNLESS NOTED OTHERWISE ON FIRE PROTECTION PLANS OR SPECIFICATIONS. ALL NEW SPRINKLER HEADS INSTALLED IN EXPOSED STRUCTURE SHALL BE BRASS UPRIGHT, UNLESS NOTED | Consultant | S . |
| PRINKLER THE | 01 | OTHERWISE ON FIRE PROTECTION PLANS OR SPECIFICATIONS. | REGISTERI PROPESSION ENGINEEI | NAL |
| PRM ABLE NFPA PROVIDE NEW | 21. 22. | PROVIDE AND INSTALL ALL CEILING MOUNTED SPRINKLER HEADS IN THE CENTER OF CEILING TILES. PROVIDE AUXILIARY DRAINS FOR ALL TRAPPED PIPING | NÖ. 19764 | Bassing |
| TRONIC REQUIRED. FOR | 23. | SECTIONS IN ACCORDANCE WITH NFPA 13. | SEAL 02-05-202 | .1 |
| HE SCOPE OF | 24. | WALLS AND CEILINGS. ALL NEW GROOVED PIPING SHALL BE BLACK SCHEDULE 10 | | |
| RE FEET PER REAS. RE FEET PER Y-2 AREAS. | 24. | OR BLACK SCHEDULE 40 WITH GROOVED AND WELDED OUTLETS. FITTINGS ANDCOUPLINGS SHALL BE STANDARD GROOVED. | | |
| W CTRICAL AND | 25. | ALL NEW THREADED PIPING SHALL BE BLACK SCHEDULE 40. FITTINGS SHALL BE STANDARD "BLACK" GRADE. | | NOIT |
| INED, PRIOR FOR PIPE | 26. | DO NOT INSTALL ALTERNATIVE STEEL PIPE SCHEDULES ALLOWED BY NFPA 13. | | DESCRIPTION |
| H COMPLETE OF EACH ND IEADS (OVER T, TO OBTAIN | 27. | PROVIDE PROTECTION FOR SPRINKLER HEADS IN AREAS WHERE THE CEILING AND SURROUNDING AREAS ARE TO BE PAINTED. REMOVE SPRINKLER PROTECTION AFTER PAINTINGWORK IS COMPLETE. REPLACE, AT NO ADDITIONAL EXPENSE TO THE OWNER, ANY SPRINKLER HEAD WITH PAINT OR TEXTURE OVERSPRAY. | | DES |
| /ITH RVISION AND HORITIES | 28. | PROVIDE HEAD GUARDS ON ALL SPRINKLER HEADS AT OR BELOW AN ELEVATION OF 7'-0" AFF, OR THAT OTHERWISE MAY BE SUBJECT TO MECHANICAL DAMAGE, SUCH AS IN THE MECHANICAL ROOMS. | | |
| ABLISHED BY | 29. | SEISMIC BRACING/ RESTRAINT IS REQUIRED FOR THIS PROJECT. | | DATE |
| DNTRACTORS ED FOR M.E.P. TEM. ANY ED FOR HE | 30. | FIRE PROTECTION PLANS SHALL BE SUBMITTED AND RECEIVED APPROVAL PRIOR TO FABRICATION BY AND ALL REQUIRED LOCAL AND STATE AUTHORITIES. | | D O |
| ECTURAL UCT, AND | | | | |
| OW TEST FLOW TEST ST IS NOT R TO INIMUM OF 10 INIMUM OF 10 INIMUM OF 10 RMATIONAL HED BY THE | | | | TAILS |
| BUILDING FIRE | | | | D DE |
| FOR ALL | | | 16N1 1VE 401 | S AN |
| OUGHOUT S, RAISED | | | ACEMEN (G DRIVE AR 72401 | IOTE |
| HAT FER TO ING PLANS | | | ЧЦ Ó | FIRE PROTECTION GENERAL NOTES AND DETA |
| | | | INDB BOR | GENE |
| | | | HANGAR 3901 LIN JONESB | NOI |
| | | | HANG/ 3901 [JONE(| ECT |
| | | | | ROI |
| | | | | REP |
| | | | | |
| | | | | |
| | | | | |
| | | | Project Number: 181261 | |
| | | | Date: 02-05-2021 | |
| | | | Scale: AS NOTED |) |
| | | | Sheet # FP00 ⁻ | 1 |




Α


В

С

D

1





JONESBORO MUNICIPAL AIRPORT

JONESBORO <u>MUNICIPAL</u> <u>AIRPORT</u> 3901 LINDBERGH DRIVE JONESBORO, AR 72401

HANGAR REPLACEMENT

3901 LINDBERGH DRIVE JONESBORO, AR 72401

JONESBORO MUNICIPAL AIRPORT

| SCHEDULE - SHEET INDEX | | | | | |
|------------------------|--------|----------------------------------|---------------------|--|--|
| SHEET INFORMATION SUE | | | | | |
| DISCIPLINE | NUMBER | NAME | CONSTRUCTION SET | | |
| GENERAL | | | , | | |
| GENERAL | G-001 | COVER SHEET | X | | |
| GENERAL | G-101 | GENERAL NOTES | Х | | |
| GENERAL | G-102 | CODE SCHEDULE & LIFE SAFETY PLAN | Х | | |

STRUCTURAL

| STRUCTURAL | S-001 | GENERAL NOTES | Х |
|------------|-------|---------------------------------|---|
| STRUCTURAL | S-101 | FOUNDATION AND SLAB PLAN | Х |
| STRUCTURAL | S-201 | FOUNDATION SECTIONS AND DETAILS | Х |

| ARCH | TFC | TURF |
|------|-----|------|

| ARCHITECTURE | | | |
|--------------|--------|---|---|
| ARCHITECTURE | A-001 | ARCHITECTURAL GENERAL NOTES, MATERIAL AND ANNOTATION LEGEND | Х |
| ARCHITECTURE | A-002 | TYPICAL ADA DETAILS | Х |
| ARCHITECTURE | AD-110 | DEMOLITION FLOOR PLAN | Х |
| ARCHITECTURE | AS-101 | ARCHITECTURAL - SITE PLAN | Х |
| ARCHITECTURE | A-110 | FLOOR PLAN | Х |
| ARCHITECTURE | A-130 | ROOF PLAN | Х |
| ARCHITECTURE | AR110 | REFLECTED CEILING PLAN | Х |
| ARCHITECTURE | A-201 | EXTERIOR ELEVATIONS | Х |
| ARCHITECTURE | A-202 | EXTERIOR ELEVATIONS | Х |
| ARCHITECTURE | A-301 | BUILDING SECTIONS | Х |
| ARCHITECTURE | A-311 | WALL SECTIONS | Х |
| ARCHITECTURE | A-312 | WALL SECTIONS | Х |
| ARCHITECTURE | A-401 | ENLARGED TOILET ROOMS | Х |
| ARCHITECTURE | A-501 | DETAIL SECTION VIEWS | Х |
| ARCHITECTURE | A-502 | DETAIL PLAN VIEWS | Х |
| ARCHITECTURE | A-601 | PARTITION TYPES | Х |
| ARCHITECTURE | A-602 | ROOM FINISH SCHEDULE & SIGNAGE DETAILS | Х |
| ARCHITECTURE | A-611 | DOOR SCHEDULE, DOOR AND WINDOW ELEVATIONS | Х |
| ARCHITECTURE | A-612 | DOOR HEAD, JAMB, AND SEAL DETAILS | Х |
| ARCHITECTURE | A-613 | WINDOW HEAD, JAMB, AND SILL DETAILS | Х |
| | | | |


NTS

| DISCIPLINE | N |
|-----------------|----|
| | |
| FIRE PROTECTION | |
| FIRE PROTECTION | FI |
| FIRE PROTECTION | FI |
| | |
| PLUMBING | |

| PLUMBING | |
|----------|----|
| PLUMBING | PO |
| PLUMBING | P1 |
| PLUMBING | P1 |
| PLUMBING | P1 |
| PLUMBING | P2 |
| PLUMBING | P2 |
| PLUMBING | P2 |
| PLUMBING | P3 |
| PLUMBING | P4 |
| | |

| MECHANICAL | |
|------------|---|
| MECHANICAL | Ν |
| MECHANICAL | Ν |
| MECHANICAL | N |
| MECHANICAL | N |
| MECHANICAL | Ν |
| MECHANICAL | N |
| | |

| ELECTRICAL | |
|------------|---|
| ELECTRICAL | E |
| | |



© Baker 2021

| <u>G</u> | ENERAL NOTES (TYP. ALL SHEETS) | | |
|-----------------|--|-----|---|
| CO | E CONTRACT DOCUMENTS SHALL INCLUDE ALL DRAWINGS, SPECIFICATIONS, AND NTRACT REQUIREMENTS FOR THE CONSTRUCTION OF THE PROPOSED HANGAR AND _ATED WORK. | 20. | THE NEW BUILDI 13. SUBMIT SIGN THE AUTHORITY INSTALLATION. |
| BAS SUI | E CONTRACT DOCUMENTS (DRAWINGS AND SPECIFICATIONS) SHALL ESTABLISH THE SE LINE STANDARD FOR THE PROJECT. THE CONTRACTOR MAY SUBMIT BSTITUTIONS FOR CONSIDERATION BY THE OWNER AND THE ARCHITECT AS TLINED IN THE SPECIFICATIONS AND THE PROCUREMENT DOCUMENTS. | 21. | IT IS THE OWNER CONSTRUCTION QUANTITY, QUAL THE OWNERS SP |
| AR AR SYS | E DRAWINGS INDICATE THE GENERAL SCOPE OF THE PROJECT IN TERMS OF AN CHITECTURAL DESIGN CONCEPT. THE DIMENSIONS OF THE BUILDING, THE MAJOR CHITECTURAL ELEMENTS, THE TYPE OF STRUCTURAL SYSTEM & THE MEP & FP STEMS ARE BEING ISSUED AS SCOPE DOCUMENTS, THE DRAWINGS DO NOT CESSARILY INDICATE OR DESCRIBE ALL OF THE WORK REQUIRED FOR FULL RFORMANCE AND COMPLETION OF THE REQUIREMENTS OF THE CONTRACT | 22. | ALL NEW CONCR TREATMENT. |
| DO & A | CUMENTS, FOR THE GENERAL SCOPE INDICATED OR DESCRIBED, THE CONTRACTOR PPLICABLE SUB-CONTRACTORS SHALL FURNISH ALL WORK ITEMS REQUIRED FOR E PROPER EXECUTION AND COMPLETION OF THE WORK. | | PARTITIC |
| | E PROPER EXECUTION AND COMPLETION OF THE WORK. | | INSTALL GYPSUM OF UNITED STATE C754 AND ASTM 8 |
| 1. | THE CONTRACTOR SHALL VISIT THE JOB SITE AND BE KNOWLEDGEABLE OF ALL CONDITIONS THEREOF. THE CONTRACTOR SHALL INVESTIGATE, VERIFY AND BE RESPONSIBLE FOR ALL CONDITIONS OF THE PROJECT AND NOTIFY THE ARCHITECT AND OWNER OF ANY CONDITIONS REQUIRING MODIFICATION BEFORE PROCEEDING WITH THE WORK. | | ALL PARTITIONS SMOOTH SO THE AT WALLS, LEVEI CONCEALED SPA ARE SPECIFIED. |
| 2. | ALL WORK SHALL COMPLY WITH FEDERAL, STATE AND LOCAL CODES OR ORDINANCES. | | VERIFY PARTITIC ARCHITECT OF A |
| 3. | DO NOT SCALE DRAWINGS. WRITTEN DIMENSIONS HAVE PRECEDENCE. | | PARTITION THICK |
| 4. | THE CONTRACT DOCUMENTS ARE COMPLEMENTARY, WHAT IS REQUIRED OF ONE IS REQUIRED BY ALL. THERE IS NO PRECEDENCE BASED ON SCALE OR SPECIFICATIONS VERSUS DRAWINGS.THE CONTRACT DOCUMENTS ESTABLISH THE MINIMUM REQUIREMENTS; SUBSTITUTION REQUESTS SHALL BE SUBMITTED FOR ALL | | PARTITIONS ARE HEIGHTS ARE DIN OTHERWISE. VE |
| 5. | VARIANCES. WHERE ONE DETAIL IS SHOWN FOR ONE CONDITION IT SHALL APPLY TO ALL LIKE OR | | INSTALL WATER- TO MOISTURE. IN |
| 6. | SIMILAR CONDITIONS THOUGH NOT SPECIFICALLY MARKED. IF AT ANY TIME A CONFLICT OR ERROR IS FOUND WITHIN THESE DOCUMENTS PRIOR TO OR DURING CONSTRUCTION THAT MAY BE CRITICAL TO THE INTEGRITY OF THIS | | PROVIDE ALL ME EXPOSED EDGES INTO ADJACENT S |
| | PROJECT, THE CONTRACTOR SHALL CONTACT THE ARCHITECT AND THE OWNER IMMEDIATELY TO RESOLVE THE ERROR PRIOR TO PROCEEDING WITH THE AFFECTED WORK. | | PROVIDE EXPANS WHERE REQUIRE MANUFACTURER |
| 7. | THE COORDINATION OF ALL MATERIALS, LABOR AND THE SUB CONTRACTORS WORKMANSHIP IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR. | | IN-WALL BLOCKIN |
| 8. | THE CONTRACTOR IS RESPONSIBLE FOR CONTACTING LOCAL BUILDING OFFICIALS AND INSPECTORS FOR PERMITS AND INSPECTIONS. | | ACCESSORIES IN MOUNTING BRAC |
| 9. | THE CONTRACTOR SHALL BE RESPONSIBLE FOR BRACING ALL WORK DURING CONSTRUCTION AND IMPLEMENTATION OF ALL SAFETY PROCEDURES IN | | CONTROL JOINTS |
| 10. | ACCORDANCE WITH APPLICABLE CODES. ALL FIXTURES, EQUIPMENT AND MATERIALS SHALL BE INSTALLED PER THE MANUFACTURER'S SPECIFICATIONS, RECOMMENDATIONS AND | | PROVIDE A CONT PERIMETER OF A THEY MEET WALI |
| | SUGGESTED INSTRUCTIONS. | | THE CONTRACTO |
| 11. | ALL WORK SHALL BE IN ACCORDANCE WITH THE QUALITY STANDARDS OF THE TRADE AND SHALL BE INSTALLED IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES AND MANUFACTURERS RECOMMENDATIONS. | | WITH EACH OF T AND FIRE PROTE |
| 12. | ITEMS NOTED AS "N.I.C" (NOT IN CONTRACT), "BY OWNER" OR "EXISTING" SHALL NOT BE INCLUDED IN THE CONTRACT. HOWEVER, PROVISIONS SHALL BE MADE BY RESPECTIVE | | ALL PARTITION P VERIFIED. PARTI |
| | SUB-CONTRACTOR TRADES TO ALLOW FOR THE INSTALLATION OF ITEMS NOTED. ALL FINISHES OF FLOORS, BASES, WAINSCOTS, WALLS AND CEILINGS BEHIND, UNDER AND/ OR OVER THESE ITEMS SHALL BE INCLUDED IN THE GENERAL CONTRACT UNLESS NOTED OTHERWISE (U.N.O.) | | CENTERED BETW FACE OF AN ADJ |
| 13. | THE JOB SITE SHALL BE KEPT "BROOM CLEAN" AND FREE OF EXCESSIVE DEBRIS. | | CAULK GAPS WH |
| | ALL REFUSE CREATED IN THE EXECUTION OF THE CONTRACT FOR CONSTRUCTION IS THE RESPONSIBILITY OF THE CONTRACTOR . TRANSPORT TRASH, RUBBISH AND DEBRIS FROM THE SITE AND DISPOSE OF LEGALLY. THE MANNER OF THE REMOVAL SHALL BE CONFIRMED WITH AN OWNER'S REPRESENTATIVE AND SHALL MEET CITY, COUNTY AND STATE REGULATIONS. | | ALL RATED PART TO STRUCTURE / USE U.L. LISTED COMPLY WITH UI |
| 14. | DIMENSIONS ARE NOMINAL AND ARE TAKEN FROM FACE OF BLOCK WALL, CENTERLINE OF COLUMN AND FACE OF STUD U.N.O. | | ALL FIRE AND / C PERMANENTLY II DECORATIVE CE |
| 15. | ALL UNIT MASONRY SHALL CONFORM TO ASTM C-90. MASONRY CONSTRUCTION SHALL COMPLY WITH THE SPECIFICATION FOR CONCRETE MASONRY STRUCTURES (ACI-530. 1-95/ ASCE 6-95/TMS 602-95) AND THE BUILDING CODE. | | OF 2 INCHES HIG OF 12 FEET ON C THE HOURLY RA ^T WALLS. SUGGES |
| 16. | ALL MASONRY WALLS SHALL BE REINFORCED WITH HORIZONTAL JOINT REINFORCING AT 16 INCHES ON CENTER VERTICALLY. JOINT REINFORCING SHALL HAVE PERFORMED CORNERS AND "T" SECTIONS | | PROTECT ALL OF |
| 17 | MORTAR SHALL CONFORM TO ASTM C-270 TYPE S MORTAR AND TYPE M BELOW GRADE | | |

- 17. MORTAR SHALL CONFORM TO ASTM C-270. TYPE S MORTAR AND TYPE M BELOW GRADE.
- 18. THE CONTRACTOR SHALL COORDINATE ALL LIGHTING LOCATIONS WITH THE DUCTWORK AND SPRINKLER LAYOUT. ANY VARIATIONS WITH LAYOUT OR CEILING HEIGHT SHALL BE REVIEWED WITH THE ARCHITECT PRIOR TO INSTALLATION.
- 19. THE CONTRACTOR SHALL PROVIDE A GENTLE SLOPE AT ALL NEW GRADE ENTRANCES AND EXITS; AVOID ABRUPT CHANGES IN ELEVATION AND COMPLY WITH SLOPED WALKWAY REQUIREMENTS, PER FBC & ADA.

- SPECIAL EQUIPMENT LAYOUT USE OR FUNCTION.

ION NOTES (TYP. ALL SHEETS)

JM WALLBOARD IN ACCORDANCE WITH THE CURRENT VERSION TES GYPSUM-GYPSUM CONSTRUCTION HANDBOOK, ASTM 1840; THE MOST STRINGENT REQUIREMENTS PREVAIL.

S SHALL BE INSTALLED PLUMB AND TAPED AND SANDED HERE ARE NO VISIBLE JOINTS. GYPSUM FINISH LEVEL 4 EL 4 AT CEILINGS ADD SOFFITS AND LEVEL 2 IN PACES. USE LEVEL 5 FINISH WHEN WALL COVERINGS

ION THICKNESS FOR INTERNAL INCLUSIONS. NOTIFY ANY DISCREPANCIES BETWEEN SCHEDULED CKNESS AND INTERNAL INCLUSION.

RE DIMENSIONED NOMINALLY, UNLESS NOTIFIED OTHERWISE.

DIMENSIONED FROM THE TOP OF SLAB, UNLESS NOTED ERIFY CONDITION OF SLAB AND SLAB ELEVATION.

R-RESISTANT GYPSUM BOARD IN AREAS SUBJECT INSTALL CEMENT BOARD AT ALL TILED WALLS.

IETAL CORNER AND FINISH BEADS AND / OR TRIM FOR ALL ES AND CORNERS. SPACKLE, BLEND AND SAND SMOOTH SURFACES.

NSION JOINTS IN GYPSUM WALLBOARD (FIRE RATED, RED) AS RECOMMENDED BY GYPSUM WALLBOARD R AND CENTERED ABOVE ALL DOORS.

KING SHALL BE INSTALLED IN STUD WALLS, BEHIND ALL INCLUDING BUT NOT LIMITED TO: FIRE EXTINGUISHER ACKETS, SIGNAGE ETC. WOOD BLOCKING SHALL BE TREATED

TS IN MASONRY WALLS SHALL BE A MAXIMUM OF 4 FEET S AND 20 FEET ON CENTER.

ITINUOUS BEAD OF SEALANT WITH BACKER ROD AT THE ALL EXTERIOR DOOR AND WINDOW FRAMES WHERE IIS

TOR SHALL COORDINATE AND VERIEV THE EXACT SIZE AND ALL FLOOR, WALL AND CEILING PENETRATIONS / OPENINGS THE RESPECTIVE MECHANICAL. PLUMBING. ELECTRICAL FECTION DRAWINGS.

PENETRATIONS SUCH AS DUCTWORK, SHALL BE FIELD TITIONS SHALL BE BRACED AND OPENINGS REINFORCED.

GS NOT DIMENSIONALLY LOCATED SHALL BE WEEN WALLS OR LOCATED WITHIN 4" OF THE FINISH JACENT WALL OR COLUMN AS SHOWN ON PLANS.

HERE INTERSECTIONS OF ELEMENTS ARE NOT CRISP NT

RTITIONS OR SMOKE BARRIERS SHALL EXTEND FROM FLOOR ABOVE, UNLESS NOTED OTHERWISE., AND SEALED AIRTIGHT. D HEAD OF WALL INSULATION OR UL APPROVED SEALANT. UL RATED ASSEMBLY REQUIREMENTS FOR ALL RATED WALLS.

OR SMOKE BARRIERS OR WALLS SHALL BE EFFECTIVELY AND IDENTIFIED WITH SIGNS OR STENCILING ABOVE ANY EILING AND IN CONCEALED SPACES WITH LETTERS A MINIMUM IGH ON A CONTRASTING BACKGROUND SPACED A MAXIMUM CENTER WITH A MINIMUM OF ONE PER WALL OR BARRIER. ATING SHALL BE INCLUDED ON ALL RATED BARRIERS OR STED WORDING "() - HOUR RATED FIRE AND SMOKE BARRIER, OPENINGS". THIS SHOULD APPLY TO ALL RATED WALLS.

B

ER'S AND / OR TENANT'S RESPONSIBILITY TO CHECK THE N DOCUMENTS AND VERIFY ANY AND ALL LOCATIONS, SIZE ALITY AND SPECIFIC MATERIALS USED IN CONJUNCTION WITH

RETE TO BE ON COMPACT TREATED FILL WITH TERMITE

FINISH NOTES

VERIFY FINISH WITH OWNER'S REPRESENTATIVE & ARCHITECT PRIOR TO FINISH APPLICATION

SURFACES ARE TO BE FREE OF IMPERFECTIONS AND MARKINGS SUBJECT TO BLEED-THROUGH

PAINT DIFFUSERS AND RETURN GRILLES AT CEILING TO MATCH ADJACENT CEILING FINISHES, UNLESS NOTED OTHERWISE. INTERIOR OF DUCT WORK VISIBLE FROM FINISHED SPACES SHALL BE PAINTED BLACK 12" FROM THE DIFFUSER.

INSTALL FLOORING PURSUANT TO MANUFACTURERS INSTRUCTIONS AND MOISTURE REQUIREMENTS, UNLESS NOTED OTHERWISE.

RESILIENT BASE IS COVED AT VINYL FLOORING AND STRAIGHT AT CARPET

REF REFLECTED CEILING PLANS AND NOTES, FOR MORE INFORMATION.

CARPET OF THE SAME SPECIFICATION SHALL COME FROM THE SAME DYE LOT AND MEET THE CARPET AND RUG INSTITUTE MODEL SPECIFICATION AND INDUSTRY STANDARDS FOR SIDE-TO-SIDE MATCH. THE CONTRACTOR SHALL USE LOW OR NO VOC ADHESIVE AS RECOMMENDED BY THE MANUFACTURER.

REPAIR, REFINISH AND PREPARE, AS APPLICABLE, EXISTING SURFACES TO RECEIVE NEW MATERIALS. VERIFY COMPATIBILITY OF ADHESIVES & COATINGS WITH SUBSTRATES PRIOR TO APPLICATION.

FINISH REQUIREMENTS SHALL BE DIRECTED BY OWNER AND AS FOLLOWS:

ALL FINISHES SHALL COMPLY WITH THE FOLLOWING MINIMUM REQUIREMENTS:

| EXIT FINISHES, WALLS AND CEILINGS EXIT FINISHES, FLOORS | CLASS B CLASS II |
|---|------------------------------|
| ALL OTHER SPACES, WALLS AND CEILINGS ALL OTHER SPACES, FLOORS | S CLASS B NO REQUIREMENTS |
| CLASS A INTERIOR WALL AND CEILING FINISH SMOKE DEVELOPED 0-450 | FLAME SPREAD 0-25, |
| CLASS B INTERIOR WALL AND CEILING FINISH SMOKE DEVELOPED 0-450 | FLAME SPREAD 26-75, |
| CLASS I INTERIOR FLOOR FINISH | MINIMUM 0.45 WATTS PER |
| CLASS II INTERIOR FLOOR FINISH | MINIMUM 0.22. WATTS PER |

ALL STUCCO CONTROL JOINTS SHALL COMPLY WITH FBC AREA AND SPACING REQUIREMENTS AND SHALL NOT EXCEED 144 SF IN AREA ENCOMPASSED BY THE CONTROL JOINTS.

REFLECTED CEILING NOTES

VERIFY FIELD CONDITIONS AND LOCATIONS OF ALL PLUMBING, MECHANICAL STRUCTURAL, FIRE PROTECTION, ELECTRICAL, COMMUNICATION AND LIFE SAFETY AND ANY AND ALL OTHER APPLICABLE ITEMS. INSTALL PLUMBING, FIRE PROTECTION, MECHANICAL FANS, DUCTS, CONDUITS AND OTHER RELATED AND APPURTENANT ITEMS SO AS NOT TO CONFLICT WITH LUMINARIES AND ANY AND ALL FIELD CONDITIONS. THE CONTRACTOR IS RESPONSIBLE FOR COORDINATION OF PLENUM ELEMENTS. ARRANGE OR MODIFY NON-VISIBLE ITEMS TO FIT CONDITIONS OF THE REFLECTED CEILING PLAN LAYOUT

CONTRACTOR SHALL PROVIDE FULLY COORDINATED DRAWINGS INDICATING ALL CEILING COMPONENTS, ACCESS PANELS & DEVICES (I.E. ARCHITECTURAL, MECHANICAL, ELECTRICAL, PLUMBING & FIRE PROTECTION). EACH DISCIPLINE SHALL BE INDICATED SUCH THAT THEY ARE OVERLAID AND IDENTIFIABLE INDIVIDUALLY ON ONE DRAWING. ANY DISCREPANCIES NOTED SHALL BE BROUGHT TO THE ARCHITECT AND THE OWNER'S ATTENTION PRIOR TO INSTALLATION. ANY WORK INSTALLED REQUIRING CORRECTION NOT BROUGHT TO THE ARCHITECT'S ATTENTION AND WITHOUT SUCH NOTIFICATION SHALL BE CORRECTED BY THE CONTRACTOR WITH NO ADDITIONAL COST TO THE OWNER.

CONTRACTOR TO PROVIDE AND LOCATE ALL CEILING ACCESS PANELS IN GYPSUM, PLASTER AND CEMENT BOARD CEILINGS. CONTRACTOR SHALL PROVIDE THE ARCHITECT WITH LOCATIONS / COORDINATION DRAWINGS OF ALL REQUIRED ACCESS PANELS PRIOR TO THE INSTALLATION OF CEILING ELEMENTS, INCLUDING REQUIRED ACCESS PANELS; VALVES OR EQUIPMENT REQUIRING ACCESS PANELS ABOVE METAL SLAT OR DECORATIVE WOOD CEILINGS WILL NOT BE ACCEPTABLE. RATED ACCESS PANELS SHALL BE PROVIDED IN RATED ASSEMBLIES.

CEILING ACCESS PANELS SHALL BE PROVIDED IN NON-ACCESSIBLE CEILINGS BELOW THE FOLLOWING THE MECHANICAL AND PLUMBING DEVICES

- VALVES FLOW MEASURING DEVICES MIXING BOXES POWER OPERATED DAMPERS ACCESS PANEL IN DUCTWORK
- VOLUME AND BALANCING DEVICES
- WATER FLOW SWITCHES
- SPRINKLER SYSTEM DRAINS AND TEST CONNECTIONS PRESSURE SWITCHES
- OTHER DEVICES LOCATED ON DRAWINGS

MECHANICAL, ELECTRICAL, COMMUNICATION AND LIGHTING PLAN ELEMENTS ARE SHOWN FOR LOCATION PURPOSES ONLY. REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR MORE INFORMATION.

INSTALL FULLY RECESSED FIXTURES ONLY, INCLUDING BUT NOT LIMITED TO DIFFUSERS, GRILLES, ETC. UNLESS NOTED OTHERWISE.

INSTALL UNDERWRITERS LABORATORIES (U.L.) LABELED DEVICES

INSTALL SPRINKLER HEADS WITH TRIM RINGS INSTALLED TIGHT TO FINISH CEILING.

SITE NOTES

PROVIDE SUBTERRANEAN TERMITE PREVENTION IN SOIL AREAS SCHEDULED TO RECEIVE NEW CONSTRUCTION. THE CONTRACTOR INSTALLER SHALL SUBMIT A CERTIFICATE STATING THAT THE TREATMENT HAS BEEN APPLIED IN ACCORDANCE WITH THE APPLICABLE GOVERNING REGULATIONS FOR THE LOCATION OF THE PROJECT. RETREAT AREAS DISTURBED BY EXCAVATION AFTER INITIAL TREATMENT HAS BEEN IMPLEMENTED.

ADVISE UTILITY LOCATION COMPANY OF EXCAVATION ACTIVITIES (4)-FOUR WEEKS PRIOR TO EXCAVATION ACTIVITIES. LOCATE, DENTIFY AND MARK UNDERGROUND UTILITIES PASSING THROUGH THE AREA OF CONSTRUCTION BEFORE COMMENCING WITH WORK.

REMOVE ANY MATERIAL NOT REQUIRED FOR USE ON THE PROJECT (INCLUDING UNSATISFACTORY SOILS, EXCESS SATISFACTORY SOILS, TRASH AND DEBRIS) AND LEGALLY DISPOSE OF IT OFF OF THE OWNERS PROPERTY.

BURNING SHALL NOT BE PERMITTED.

PROVIDE AN APPROVED CONSTRUCTION ENTRANCE AS REQUIRED BY THE AUTHORITY HAVING JURISDICTION.

IMPACT RESISTANT VAPOR BARRIER TO BE PROVIDED BELOW ALL SLAB-ON-GRADE FLOORS. COMPLY WITH MFR'S PATCHES, LAPS AND JOINT SEAL REQUIREMENTS.

ROOF NOTES

SQ CM

SQ CM

ALL FASTENERS AT METAL ROOF AREAS TO BE FULLY CONCEALED. ALL WOOD BLOCKING @ ROOF AND PARAPETS TO BE FIRE RETARDANT AND PRESSURE TREATED.

POWER SECURITY AND COMMUNICATION NOTES

INSTALL UNDERWRITERS LABORATORIES (U.L.) LABELED DEVICES

INSTALL SWITCHES 48 INCHES ABOVE THE FINISH FLOOR SLAB UNLESS NOTED OTHERWISE. HEIGHTS ARE DETERMINED FROM TOP OF FLOOR SLAB TO CENTERLINE OF COVER PLATE, MOUNTED VERTICALLY LENGTHWISE, U.N.O. GANG-SWITCH COVER PLATES SHALL BE ONE PIECE TYPE, QUANTITY OF SWITCHES AS APPLICABLE AND AS REQUIRED. DEVICES AND COVER PLATES TO BE LEVITON, WHITE.

RECEPTACLES MOUNTED AT COUNTER HEIGHT SHALL BE INSTALLED HORIZONTALLY ABOVE THE COUNTER OR WHERE A BACKSPLASH OCCURS, ABOVE THE BACKSPLASH OF THE COUNTER.

INSTALL WALL MOUNTED OUTLETS, POWER, COMMUNICATIONS, DATA, ETC. 18 INCHES ABOVE FLOOR SLAB TO CENTERLINE OF COVER PLATE MOUNTED VERTICALLY LENGTHWISE, UNLESS NOTED OTHERWISE (U.N.O.)

DO NOT MOUNT OUTLETS BACK TO BACK

VERIFY ALL EQUIPMENT MOUNTING REQUIREMENTS OF ALL ELECTRICAL, COMMUNICATIONS AND OTHER EQUIPMENT REQUIRING SPECIAL PLUG CONFIGURATIONS.

PROVIDE POWER AND OTHER FITTINGS FOR APPLIANCES AND OTHER DEVICES AS REQUIRED FOR PROPER OPERATION

VERIFY OR ACQUIRE EQUIPMENT SPECIFICATIONS FROM OWNER FOR PROPER FIT AND POWER REQUIREMENTS.

COORDINATE OWNER'S TELEPHONE, CABLING AND SECURITY INSTALLATIONS AS REQUIRED.

THE ELECTRICAL CONTRACTOR SHALL PROVIDE A COMPLETE ELECTRICAL, DATA AND COMMUNICATION SYSTEM INSTALLATION INCLUDING ALL WORK CUSTOMARILY INCLUDED IF NOT SPECIFICALLY CALLED OUT FOR.

ALL DOORS DESIGNATED AS SECURED, OR SHOWN TO HAVE "CR" (CARD READERS) SHALL BE FURNISHED AND INSTALLED WITH ELECTRICAL LOCKS/LATCHES. ALL WIRING SHALL BE CONCEALED WITHIN THE FRAME POWER FOR TRANSFORMERS & LOCK CONTROLS SHALL BE PROVIDED AS **REQUIRED FOR FULLY FUNCTION SYSTEM.**

FURNISH AND INSTALL ELECTRIC LOCK PANIC RELEASE BUTTONS AT INTERIOR SIDE OF DOORS WITH ELECTRIC LOCKS @ EGRESS DOORS AND OCCUPANCY/MOTION SENSORS @ NON EGRESS DOORS.

FURNISH AND INSTALL DELAYED EGRESS HARDWARE AT ALL SIDA (APRON ACCESS) EGRESS DOORS.

THE CONTRACTOR SHALL COORDINATE WITH THE OWNER'S SECURITY CONTRACTOR FOR INSTALLATION AND WIRING CHASE WAYS, AND CONTROL INTERFACE FOR POWER OPERATED DOORS.

CERTIFICATION:

I HEREBY CERTIFY THAT THESE PLANS AND SPECIFICATIONS HAVE BEEN PREPARED BY ME, OR UNDER MY SUPERVISION. I FURTHER CERTIFY THAT TO THE BEST OF MY KNOWLEDGE THESE PLANS AND SPECIFICATIONS ARE AS REQUIRED BY LAW AND IN COMPLIANCE WITH THE ARKANSAS FIRE PREVENTION CODE FOR THE STATE OF ARKANSAS.

CHARLES POPOVICH. ARCHITECT #9683




| HANGAR REPLACEMENT 3901 LINDBERGH DRIVE 3901 LINDBERGH DRIVE 3901 LINDBERGH DRIVE 3901 LINDBERGH DRIVE JONESBORO, AR 72401 NOI DATE BESCRIPTION REVISIONS |
|---|
| NO. DATE REVISI |
| |
| HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 GENERAL NOTES |
| |

G-101

| | 1 | | | | | | 2 |
|---|---|-----------------------|----------|---|-------------------------------------|--------------------------------------|----------|
| | Code Compliance Schedule | | INTEF | RIOR FINISHES (IB | C Chapter 8. Table | 803.9 | |
| | International Building Code (IBC) | 2012 | Lobbies | and Corridors | | Class C | |
| | International Existing Building Code | 2012 | | ess Corridors | | Class C | |
| | Arkansas Fire Prevention Code Vol. I: Fire Arkansas Fire Prevention Code Vol. II: Building | 2012 2012 | Other Sp | Daces | | Class C | |
| | AMC: Arkansas Mechanical Codes | 2010 | FIRE SU | IPPRESSION SYST | EMS (IFC Chapte | r 9): | |
| | Arkansas Energy Code APC: Arkansas Plumbing Codes | 2014 2006 | Sprinkle | red (NFPA 13) | | Yes | |
| | NEC: National Electric Code | 2011 | Standpip | , | | N/A | |
| | AFGC: Arkansas Fuel and Gas Codes | 2006 | | Fire Alarm | | Yes | G |
| | ADA (ADAAG) ICC/ANSI A117.1 | 2010 2009 | | ic Fire Alarm nguishers (IFC Tabl | e 906.3) | 165 | (F) |
| A | NFPA 101 Life Safety Code | 2015 | | m Travel Distance | 0.00.0 | <75 FT | |
| | NFPA 13 Fire Sprinkler Code NFPA 10 Portable Fire Extinguishers | 2013 2013 | Quantity | Required = 5 | | Yes (6 Provided) | |
| | NFPA 72 Fire Alarm Code | 2013 | | | | | |
| | ASHRAE 90.1 | 2013 | | ANT LOAD (IBC Tal | ble 1004.1.2): | 2,567 SF | |
| | Project Information | | | s Occupancy ess @ 100 SF Gross | s / Occupant | 2,507 SF 26 Occupants | |
| | Project Location: | | | Space (S-1) | | 10,316 SF | |
| | JONESBORO MUNICIPAL AIRPORT | | | e @ 300 SF Gross/ | Occupant | 35 Occupants | |
| | 3901 LINDBURG DRIVE, JONESBORO, AR 72401 | | TOTAL | OCCUPANT LOAD | | 61 OCCUPANTS | |
| | Owner: JONESBORO MUNICIPAL AIRPORT | | | | | | |
| | CONTACT: GEORGE JACKSON | | | | | | (E) |
| | PHONE: 870-932-1052 | | | | | | |
| | | | | | | | |
| | MICHAEL BAKER INTERNATIONAL 1501 LBJ FREEWAY, SUITE 650 | | | | | | |
| | DALLAS, TX 75234 CONTACT: CHARLES POPOVICH | | | | | | |
| | PHONE: 469-801-8509 | | | | | | |
| | | | | | | | |
| | Zaning/Eland Informations | | | PACITY - Factor = | | BC Table 1005.3.2) | |
| В | Zoning/Flood Information: Zoning Classification: I-2 | | EXITS | Min Clr. Width in inches | Actual Clr. Width in inches | Occupant Capacity | |
| | Food Zone: Zone X | | | 32 | | 226 | |
| | Finish Floor Elevation (MIN) = EL 262'-0" ABOVE SEA | LEVEL. | E1 E2 | 32 | 34 | 226 | |
| | Cada Camplianaa Information | | E3 | 32 | 34 | 226 | |
| | Code Compliance Information | | - | | | | |
| | USE GROUP / OCCUPANCY CLASSIFICATION: SEPARATED MIXED USE | | | | | | |
| | (2012 IBC - Table 508.4) | | | | | | |
| | CONSTRUCTION TYPE: | | | | | | |
| | Type II B. Automatic Sprinklered (2012 IBC - Table 601) | | EGRES | S REQUIREMENTS | (IBC Ch 10): | | |
| | | | Minimun | n Number of Exits (1 | Table 1019.1) | 2 Exits | |
| | BUILDING DATA: | | Dead Er | d Corridor (IBC 101 | 8.4) | 50 Feet (Max.) | |
| | B, S-1 - Automatic Sprinklered: Allowed | Dosignod | | istance for Exit (B) (| | 250 Feet (Max.) | |
| | B - Number of Floors 3 | Designed 1 | | istance for Exit (S-1 / Aisle Width (Table | / \ / | 250 Feet (Max.) | E3 22 |
| | S-1 Number of Floors 2 | 1 | | r Clear Opening Wid | , | 44 Inches (Min.) 32 Inches (Min.) | (C)-(3 |
| | | | | oor Hardware Requi | | | |
| | ALLOWABLE AREA B Business Area 23,000 SF | 2 F67 OF | | v/ >50 Occupants | , 0 | | |
| | B Business Area23,000 SFS-2 Storage Area17,500 SF | 2,567 SF 10,316 SF | - | | | | |
| • | Total Floor Area (Most Restringent) 17,050 SF | 12,883 SF | - | | | | |
| С | | | | e Plan Legen | d | | |
| | | | | Space E | gress Tag | | |
| | Devenet Lleicht N/A | | | XX - Max Numl | ber of Occupants Th | ru Opening | |
| | Parapet Height - N/A Design Wind Speed = 115 mph | | - | (XX ^{••}) Direction Clear Wid | of Travel th of Door in Inches | | |
| | • | | - | Building | Egress Tag | | |
| | <u>"R" / "U" Values: Per 2014 Arkansas Energy Code:</u> Craighead County Climate Zone: 3 | | | XX — Max Num | ber of Occupants Th | ru Opening | D D |
| | Craighead County Climate Zone: 3 Entirely above Roof Deck: R20ci | | - | (XX ²) Direction Clear Wid | of Travel th of Door in Inches | | |
| | Metal Buildings (Roof) (with R-5 thermal Blocks): R-1 | 3 + R-13 | FE | | inguisher (Wall N | /lount) | |
| | Metal Building (walls): R-19 | | FEC | Fire Exti | inguisher & Cabi | net | |
| | Metal Frame (Walls): R-13+R-3.8ci. | | | | ator & Cabinet w | | |
| | Glass: U < 0.60 (Table 502.3) SHGC: PF<0.25 = U-0.25 (Table 502.3) | | | | Hold Open / Re Connect to Fire A | | |
| | | | | | Have Electric L | | (1) |
| | Insulated GL; Impact Rated | | [| CR Emerge | ncy Push Button | | \smile |
| | RATED SEPARATIONS (IBC Table 601, 602, 508.3.3 | , | | of Door | A.(: | | |
| | | separated) | - | Egress V | VVINDOW | | |
| | Primary Structural Frame Bearing Walls (Exterior) | 0 | - | Exit Ligh | nt n of Travel | | |
| | Bearing Walls (Interior) | 0 | | | | | TO |
| D | Non-bearing Walls and Partitions (Exterior) | 0 | | XX' Egress | Travel Distance | | 000 |
| | Non-bearing Walls and Partitions (Interior) | 0 | 4 | | | | OCCUF |
| | Floor Construction and Assoc Members | 0 | - | | | | |
| | Roof Construction and Assoc Members | 0 | - | | | | В |
| | Corridor Fire Rating (B, S-1)(IBC Table 1018.1) | 0 Hour | - | | | | |
| | | | - | | | | |
| | | | | | | | S- |
| | OPENING PROTECTION: Exit Access Corridors (B, S-1) | 2 Hour | - | | | | |
| | | | - | | | | TOTAL |
| | | | | I | | | TOTAL |
| | 1 | | | | | | 2 |
| | | | | | | | |

E3 226 (34") ⁻ LIFE SAFETY PLAN SCALE: 1/8" = 1'-0"

| OCCUDANCY | OCC. LOAD | | WATER | CLOSETS | | L | AVATOF | RIES | DRINKING | FOUNTAINS | SERVICE |
|-------------------|--|-----------------|-------|-----------------|-------|-----------------|--------|-------|---------------|-----------|---------|
| OCCUPANCY | | RATIO | MEN | RATIO | WOMEN | RATIO | MEN | WOMEN | RATIO | TOTAL | SINKS |
| В | 26 TOTAL MALE (26/2)= 13 | 1 PER 25 <50 | 1.0 | 1 PER 25 <50 | 1.0 | 1 PER 40 <80 | 1.0 | 1.0 | 1 PER 100 | 1.0 | 1.0 |
| FEMALE (26/2)= 13 | | | | 1 PER 50 >50 | 0.0 | 1 PER 80 >80 | 0.0 | 0.0 | | | |
| S-1 | 35 TOTAL MALE (35/2)= 18 FEMALE (35/2)= 18 | 1 PER 100 | 1.0 | 1 PER 100 | 1.0 | 1 PER 100 | 1.0 | 1.0 | 1 PER 1000 | 1.0 | 1.0 |
| TOTAL REQUIRED | | 2 2 | | | | | 2 | 2 | 1 | 2 | 2 |
| TOTAL PROV | IDED | 1 + 1 URINAL 2 | | | 2 | | 2 | 2 | | 2 | |



| ROOF | DRAIN |
|------|-------|
| RUUF | DRAIN |

| LOCATION | | | VI | ERTICAL LEAD |
|-----------------------|-----------|----------------------|------------------------------|----------------------|
| LOCATION | | QUANTITY PROVIDED | CAPACITY PER EACH (IN/HR) | CAPACITY PROVIDED |
| WEST OF ROOF RIDGE | 4 SQ. IN. | 5 | 4,600 | 23,000 |
| EAST OF ROOF RIDGE | 4 SQ. IN. | 5 | 4,600 | 23,000 |

MECHANICAL GENERAL NOTES

- ALL PIPING AND DUCTS IN FINISHED ROOMS OR SPACES SHALL BE CONCEALED IN A FURRED CHASE OR ABOVE A HARD SUSPENDED CEILING.
- THE FIRST FIGURE OF DUCT SIZE INDICATES DIMENSION OF FACE SHOWN OR INDICATED. DUCT 2. SIZED ARE NET INSIDE DIMENSIONS.
- ACCESS PANELS IN HARD SUSPENDED CEILINGS ARE REQUIRED FOR ALL VALVES, TRAPS, DAMPERS, CLEANOUTS, CONTROLS, ETC. COORDINATE LOCATION OF PANELS WITH MECHANICAL INSTALLATION AND DEMONSTRATE ACCESS TO EQUIPMENT SERVED.
- TOTAL STATIC PRESSURE NOTES IN THE SCHEDULES INCLUDED DUCT SYSTEM, TERMINAL UNITS, FILTERS, COILS, ETC. LOSS FOR FILTERS SHALL BE FOR FILTERS AT 50% LOADING.
- ALL DUCT AND PIPE ROUTING AND CONSTRUCTION SHOWN ON THE DRAWINGS IS DIAGRAMMATIC IN NATURE AND MAY NOT BE SHOWN IN EXACT LOCATIONS OR WITH ALL ANCILLARY ITEMS REQUIRED FOR A COMPLETE AND OPERATING SYSTEM. CONTRACTOR SHALL COORDINATE ROUTING OF ALL DUCTWORK AND PIPING PER TYPICAL CONSTRUCTION PRACTICE IN THE MOST EFFICIENT WAY POSSIBLE WHILE ADHERING AS CLOSELY TO THE DRAWINGS AS POSSIBLE.
- CONTRACTOR IS RESPONSIBLE FOR COORDINATING ALL INSTALLATION WITH THE WORK OF OTHER TRADES. FIELD MODIFICATIONS SUCH AS OFFSETS IN PIPING OR DUCTWORK NEEDED DUE TO OBSTRUCTIONS OR INTERFERENCES SHALL BE PROVIDED AT NO ADDITIONAL COST.
- ALL WORK SHALL BE PERFORMED IN A NEAT AND WORKMANLIKE MANNER WITHIN STANDARD OF CARE FOR PROFESSION. ALL LABOR, MATERIAL, TOOLS, PERMITS, INSPECTIONS, TESTING, CERTIFICATION, ETC. REQUIRED FOR A COMPLETE AND SATISFACTORY INSTALLATION TO DESIGN INTENT SHALL BE FURNISHED BY CONTRACTOR. PROVIDE, AT NO ADDITIONAL COST, INCLUDING INCIDENTAL ITEMS NOT SHOWN WHEN REQUIRED FOR TYPICAL COMPLETION OF WORK.
- DRAWINGS NOT BEARING THE STAMP OR SEAL AND SIGNATURE OF A REGISTERED PROFESSIONAL ENGINEER SHALL NOT BE USED FOR BIDDING OR CONSTRUCTION PURPOSES UNLESS EXPRESSLY APPROVED IN WRITING BY THE ARCHITECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL DRAWINGS AND SPECIFICATIONS BEING USED FOR BIDDING AND CONSTRUCTION PURPOSES ARE OF THE LATEST REVISION AVAILABLE AND ALL ADDENDUM DOCUMENTS HAVE BEEN INCORPORATED EITHER BY REVISION RELEASE OF DRAWINGS/SPECIFICATIONS OR ATTACHMENT OF SKETCHES OR OTHER ADDENDUM INFORMATION.
- THE MECHANICAL CONTRACTOR SHALL FURNISH AND INSTALL NEW PRODUCTS OF 9. ESTABLISHED AND REPUTABLE MANUFACTURERS. NO EQUIPMENT SUBSTITUTIONS SHALL BE MADE THAT WOULD LEAVE INADEQUATE OPERATING OR SERVICE SPACE. EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDED INSTALLATION PROCEDURES AND IN AN ARRANGEMENT THAT WILL GIVE THE GREATEST PRACTICAL EASE OF OPERATION AND SERVICE TO THE OWNER.
- 10. ALL EQUIPMENT WHICH IS INDICATED TO BE FURNISHED AND/OR INSTALLED BY OTHERS OR BY OWNER IS INCLUDED FOR REFERENCE ONLY UNLESS NOTED OTHERWISE. DESIGN OF MECHANICAL SYSTEMS IN THESE AREAS IS BASED ON INFORMATION AVAILABLE AT THE TIME OF DESIGN. CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING AND VERIFYING INSTALLATION REQUIREMENTS OF THIS EQUIPMENT WITH THE APPLICABLE SUPPLIER OR THE OWNER. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER.
- IT IS THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO PAY FOR ALL NECESSARY 11. PERMITS AND APPROVALS FOR THIS INSTALLATION.
- ACCESS PANELS IN DUCTWORK AND CEILINGS SHALL BE PROVIDED WHERE REQUIRED FOR 12. OPERATION, BALANCING OR MAINTENANCE OF ALL MECHANICAL EQUIPMENT. ACCESS PANELS SHALL BE CONVENIENTLY LOCATED WITH REFERENCE TO THE FINISHED BUILDING. COORDINATE LOCATION OF ACCESS PANELS WITH ARCHITECT.
- 13. DUCT CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE SMACNA HVAC DUCT CONSTRUCTION STANDARD CLASS A.
- COORDINATE DIFFUSER, GRILLE AND REGISTER LOCATIONS WITH ARCHITECTURAL 14. REFLECTED CEILING PLANS AND EQUIPMENT OF ALL TRADES.
- 15. VERIFY FINISH WITH ARCHITECT PRIOR TO PURCHASING GRILLES, REGISTERS, DIFFUSERS, LOUVERS AND OTHER AIR DISTRIBUTION DEVICES.
- 16. LOCATE THERMOSTATS AT 48" ABOVE FINISHED FLOOR UNLESS NOTED OTHERWISE. COORDINATE LOCATIONS WITH OTHER EQUIPMENT, FURNITURE, AND DOOR SWINGS.
- 17. ALL EQUIPMENT, DUCTWORK, ETC., SHALL BE SUPPORTED AS DETAILED AND/OR SPECIFIED. PROVIDE ADDITIONAL SUPPORTS AS REQUIRED TO PROVIDE A VIBRATION-FREE, RIGID INSTALLATION.
- 18. DUCTWORK DIMENSIONS SHOWN ON DRAWINGS ARE INSIDE CLEAR DIMENSIONS. DIMENSIONS MAY BE CHANGED SO LONG AS THE NET FREE FACE AREA IS MAINTAINED.
- 19. DAMPERS AND INSIDES OF DUCTS VISIBLE THROUGH GRILLES, REGISTERS AND DIFFUSERS SHALL BE PAINTED FLAT BLACK.
- 20. PROVIDE AND INSTALL SMOOTH TURN RADIUS ELBOWS IN ALL RECTANGULAR 90° ELBOWS AND TEES, UNLESS NOTED OTHERWISE.
- EXHAUST DUCTS SHALL TERMINATE IN ACCORDANCE WITH ASHRAE 170-2013 AND BE 21. EQUIPPED WITH A BACKDRAFT DAMPER.
- CONTRACTOR SHALL PROVIDE ALL AIR TEMPERATURE CONTROLS INCLUDING WIRING, 22. THERMOSTATS AND ALL MISCELLANEOUS APPURTENANCES TO MEET THE INTENT OF THESE DOCUMENTS.
- 23. PENETRATIONS OF WALLS OR FLOORS FOR THE PASSAGE OF PIPING, DUCTWORK, OR OTHER EQUIPMENT SHALL BE PROPERLY SEALED AFTER INSTALLATION OF ITEMS AND EQUIPMENT.
- PIPING, DUCTWORK, LEAK PROTECTION APPARATUS, OR OTHER EQUIPMENT FOREIGN TO 24. ELECTRICAL SWITCHBOARDS, PANELBOARDS, DISTRIBUTION BOARDS, OR MOTOR CONTROL CENTERS SHALL NOT BE INSTALLED WITHIN THE REQUIRED SPACE FOR WORKING CLEARANCES OR DEDICATED SPACES OF THE ELECTRICAL EQUIPMENT, EXTENDING IN FRONT OF AND FROM FLOOR TO STRUCTURAL CEILING WITH A WIDTH AND DEPTH OF THE ELECTRICAL EQUIPMENT IN ACCORDANCE WITH NEC-110.26.

2


ROUND DUCT DOWN

 $\bigcirc \square \bigcirc$

| | LEG | GEND | |
|------------|---|-------------|---|
| SYMBOL | DESCRIPTION | SYMBOL | DESCRIPTION |
| | NEW EQUIPMENT | | CONCENTRIC REDUCER |
| | NEW DUCT/PIPING | | ECCENTRIC REDUCER |
| // | THERMOSTAT WIRE | \square | RECT. AND/OR ROUND DUCT 90° 1X RADIUS ELBOW |
| T | THERMOSTAT | \subseteq | RECT. AND/OR ROUND DUCT 90° 1.5X RADIUS ELBOW |
| $\sqrt{1}$ | REVISION DELTA | | RECT. AND/OR ROUND DUCT 45° 1X RADIUS ELBOW |
| <u> </u> | MANUAL VOLUME DAMPER | | |
| | STREAMLINE CONNECTION (RECT. TO ROUND) | | RECT. ELBOW (WITH TURNING VANES) |
| | STREAMLINE CONNECTION (RECT. TO RECT.) | | RECT. ELBOW (WITHOUT TURNING VANES) |
| | STREAMLINE CONNECTION WITH MANUAL VOLUME DAMPER (RECT. TO ROUND) | \sim | SINGLE LINE CONTINUATION |
| 811111113 | FLEXIBLE DUCT | — /\ | AIR FLOW ARROW |
| RISE | | | FLOW ARROW |
| FALL | DUCT ELEVATION CHANGE (RISE) | AP | ACCESS PANEL |
| | DUCT ELEVATION CHANGE (FALL) | δ AP S | ACCESS PANEL IN ROUND OR OVAL DUCT |
| | SIDE WALL GRILLE | SA | SUPPLY AIR DUCT |
| [X]####] | GRILLE DESIGNATION (GRILLE SCHEDULE DESIGNATION / CFM AIRFLOW) | RA | RETURN AIR DUCT |
| | SUPPLY DIFFUSER | EA | EXHAUST AIR DUCT |
| | RETURN GRILLE | CFM | CUBIC FEET PER MINUTE |
| | EXHAUST GRILLE | Ø | ROUND DIAMETER |
| \bowtie | SUPPLY RECTANGULAR DUCT UP | — D — | CONDENSATE DRAIN |
| | RETURN RECTANGULAR DUCT UP EXHAUST RECTANGULAR DUCT UP | | REFRIGERANT SUCTION AND LIQUID |
| | SUPPLY RECTANGULAR DUCT DOWN | | |
| | RETURN RECTANGULAR DUCT DOWN | | |
| \square | EXHAUST RECTANGULAR DUCT DOWN | | |
| oli is | ROUND DUCT UP | | |
| | | | |

3


| HANGAR REPLACEMENT Image: Marcham and Marcham an |
|--|
| |
| |
| |



| 5 | |
|---|--|
| GENERAL NOTES | Michael Baker |
| 1. SLEEVE AND SEAL ALL PIPING THROUGH WALLS. | INTERNATIONAL 1501 LBJ FREEWAY, |
| 2. SIZE REFRIGERANT PIPING PER MANUFACTURER'S RECOMMENDATIONS. | SUITE 650 DALLAS, TX 75234 |
| | OF AUT |
| | INSIGHT ENGINEERING, PLLC No. 3523 |
| | No. 3523 |
| | |
| | STATE OF |
| KEYED NOTES | REGISTERED PROPESSIONAL |
| $\langle 1 \rangle$ 8"X8" OSA DUCT DOWN FROM INTAKE VENT (<u>IV-1</u>) | ENGINEER No. 19764 |
| ON ROOF. INTAKE VENT (<u>IV-1</u>) SHALL BE A MINIMUM OF 10'-0" AWAY FROM FLUE DUCT ON ROOF. | 02-05-2021 |
| (2) ROUTE 1-1/2" CONDENSATE PIPE DOWN FROM FURNACE (F-1), LOW TO FLOOR/WALL, THRU EXTERIOR WALL, TURN PIPE DOWN AND | |
| TERMINATE 6" ABOVE GRADE. PROVIDE WITH INSECT SCREEN AT END OF CONDENSATE DRAIN PIPE. | |
| 3 HVLS FAN CONTROLLER | ZO |
| | DESCRIPTION |
| | DESO |
| | DES |
| | |
| | Щ |
| | DATE |
| | |
| | |
| | |
| | |
| | |
| | × |
| | HANGAR REPLACEMENT 3901 LINDBURG DRIVE JONESBORO, AR 72401 FLOOR PLAN - HVAC DUCTWORK |
| | DRIV 724 UCT |
| | AC D |
| | HV DBU |
| | HANGAR REPLACEMENT 3901 LINDBURG DRIVE JONESBORO, AR 72401 OOR PLAN - HVAC DUCTWO |
| | ANG 3901 ONE ONE |
| | ECO CONT |
| | |
| | |
| | |
| | |
| | Project Number: |
| | 181261 Date: 02-05-2021 |
| Ω <i>Α</i> ' Ω" &' Ω" 46' Ω" | Scale: AS NOTED |
| 0 4' - 0" 8' - 0" 16' - 0" SCALE: 0' - 0 1/8" = 1' - 0" | Sheet # M101 |
| | IVIIUI © Baker 2018 |

© Baker 2018

CONSTRUCTION





MANUAL DAMPER WITH


STAND-OFF BRACKET


MANUAL DAMPER WITH


STAND-OFF BRACKET


QUADRANT INDICATOR AND


QUADRANT INDICATOR AND















RECTANGULAR TO RECTANGULAR











| 0 | |
|---|--|
| Ζ | |

А

В

С

D

1

| COND | ENSING UNITS A | ND DIRECT | EXPANSIO | | S | | | | | | | ELECTR | RICAL | | | |
|-------------|------------------------------------|-----------------------------|---------------------|---------------------------|------------------------------|---------------------------|-----------------------------|--------------------------------|-------------|--|----------------|--------|-------|-----|-----|--|
| DESIGNATION | REFERENCE PRODUCT | NO. OF CONDENSOR FANS | REFRIGERANT TYPE | TOTAL COOLING (MBH) | SENSIBLE COOLING (MBH) | TOTAL AIRFLOW (CFM) | OUTSIDE AIRFLOW (CFM) | AIR EDB / EWB (DEGREE F) | | AMBIENT AIR TEMPERATURE (DEGREE F) | MINIMUM EER | VOLTS | PHASE | MCA | MOP | REMARKS |
| CU-1 | TRANE: 4TXCD008DS3 + 4TTR4060L1 | 1 | R-410A | 55.8 | 42.1 | 1425 | 270 | 80 / 67 | 58.0 / 56.8 | 95 | 11.7 | 230 | 1 | 31 | 50 | INSTALL PER MANUFACTURER'S GUARD FOR CONDENSING UNIT. |

3

| GAS F | IRED DUCT FURN | ACE | | | | | | | | | | | |
|-------------|----------------------|-------------|---------------------------|-----------------------------|-------------------------|-------------------------------|----------------------------|---|------------------|-----------------|-------|-------|--|
| DESIGNATION | REFERENCE PRODUCT | SERVES | AIR FLOW RATE (CFM) | OUTSIDE AIRFLOW (CFM) | TEMP RISE (DEGREE F) | NATURAL GAS INPUT (MBH) | HEATING OUTPUT (MBH) | ASSOCIATED DX/COIL CONDENSING UNIT | FLUE DIAMETER | WEIGHT (LBS) | VOLTS | PHASE | REMARKS |
| F-1 | TRANE: S9X1C080U5PSB | OFFICE AREA | 1425 | 270 | 40 | 80 | 78 | CU-1 | 4 | 160 | 120 | 1 | INSTALL AND MOUNT DUCT MOUNTED FURNACE PER MANUFACTURER'S INSTRUCTIONS. |

| EXHAU | IST FANS | | | | | | | | | | | |
|-------------|---------------------|-----------------|---------------|--------|----------|---------------|-------------------------|-------|---------------|-------|--------|--|
| | REFERENCE | 7/85 | | DRIVE | ROTATION | AIR FLOW RATE | STATIC | SONES | MOTOR SIZE | ELEC | TRICAL | DEMARKO |
| DESIGNATION | PRODUCT | TYPE | SERVES | DRIVE | (RPM) | (CFM) | PRESSURE (IN. WATER) | SONES | BHP | VOLTS | PHASE | REMARKS |
| EF-1 | GREENHECK: SPB70 | CEILING | 113 JAN | DIRECT | 675 | 35 | 0.2 | 1 | 0.1 | 120 | 1 | FAN SHALL OPERATE CONTINUOUSLY DURING OCCUPIED HOURS. INS MANUFACTURER'S INSTRUCTIONS |
| EF-2 | GREENHECK: SPB110 | CEILING | 107 MENS RR | DIRECT | 950 | 100 | 0.2 | 1.5 | 0.1 | 120 | 1 | INTERLOCK FAN WITH LIGHTSWITCH. INSTALL PERMANUFACTURER'S |
| EF-3 | GREENHECK: SPB70 | CEILING | 106 WOMENS RR | DIRECT | 950 | 100 | 0.2 | 1 | 0.1 | 120 | 1 | INTERLOCK FAN WITH LIGHTSWITCH. INSTALL PERMANUFACTURER'S |
| EF-4 | GREENHECK: SPB69 | CEILING | 110 JAN | DIRECT | 675 | 35 | 0.2 | 1 | 0.1 | 120 | 1 | FAN SHALL OPERATE CONTINUOUSLY DURING OCCUPIED HOURS. INS MANUFACTURER'S INSTRUCTIONS |
| EF-5 | GREENHECK: SBE-2L30 | WALL MOUNTED | HANGAR | BELT | 450 | 10,000 | 0.25 | 20 | 1.3 | 240 | 1 | FAN SHALL BE INTERLOCKED WITH LOUVERS. PROVIDE WALL COLLA INSTALL PER MANUFACTURER'S INSTRUCTIONS. PROVIDE MOTOR STA DISCONNECT. ON/OFF WALL SWITCH SHALL BE PROVIDED. FAN SHA SUMMER TIME, WHEN WELDER IS ON, AND WHEN A PLAN IS ENTERIN |

| INTAK | E VENTS | | | | | | | | | |
|-------------|----------------------|--------|---------|--------------------|-------------------|-----------------------------|----------|---------------------------------|--------|---|
| DESIGNATION | REFERENCE PRODUCT | SERVES | TYPE | LENGTH (INCHES) | WIDTH (INCHES) | THROAT VELOCITY (FPM) | AIR FLOW | PRESSURE DROP (IN. WATER) | FINISH | REMARKS |
| IV-1 | GREENHECK: GRSI-8 | AH-1 | GRAVITY | 8 | 8 | 700 | 300 | 0.1 | | PROVIDE MANUFACTURER'S ROOF CURB AND INSECT SCREEN. INSTALL PER MANUFACTURER'S INSTRUCTIONS. |

| RADIA | NT HEATERS - G | SAS | | | | | | |
|-------------|---|------|-------|----------|-------|-------|-----|---|
| DESIGNATION | SIGNATION REFERENCE PRODUCT TUBE LENGTH WEIGHT INPUT ELECTRICAL | | | REMARKS | | | | |
| DESIGNATION | REFERENCE PRODUCT | (FT) | (LBS) | (BTU/HR) | VOLTS | PHASE | HP | KEMARKS |
| H-1,2,3 | MODINE: IPT-150-S-01-11 | 60 | 65 | 160 | 120 | 1 | 0.3 | PROVIDE STRAIGHT TUBE. INSTALL PER MANUFACTURER'S INSTRUCTIONS |

| AIR DE | VICES | | | | | | | | |
|-------------|----------------------|-----------------|-----------------------------|----------------------------------|--------------------|---------------------|-----------|--------|---|
| DESIGNATION | REFERENCE PRODUCT | CONFIGURATION | MAXIMUM AIRFLOW (CFM) | TOTAL PRESSURE (IN. WATER) | NECK SIZE (IN.) | PANEL SIZE (IN.) | MAX. N.C. | FINISH | REMARKS |
| А | TITUS: OMNI AA | LAY-IN PLAQUE | 225 | 0.099 | 6 | 24 x 24 | 30 | WHITE | |
| В | TITUS: OMNI AA | LAY-IN PLAQUE | 350 | 0.112 | 8 | 24 x 24 | 30 | WHITE | |
| С | TITUS: 300FL | LAY-IN | 100 | 0.1 | 6 x 6 | 8 x 8 | 30 | WHITE | PROVIDE 22.5 DEGREE DEFLECTION. |
| | | | | | | | | | |
| 1 | TITUS: 50F | LAY-IN EGGCRATE | 300 | 0.095 | 8" | 24 x 24 | 30 | WHITE | 1/2" x 1/2" x 1/2" ALUMINUM CORE. PROVIDE FILTER. USE SRG ADAPTER. |
| 2 | TITUS: 50F | LAY-IN EGGCRATE | 475 | 0.095 | 10" | 24 x 24 | 30 | WHITE | 1/2" x 1/2" x 1/2" ALUMINUM CORE. PROVIDE FILTER. USE SRG ADAPTER. |
| 3 | TITUS: 350RL | LAY-IN | 350 | 0.1 | 10 x 10 | 12 x 12 | 30 | WHITE | PROVIDE 22.5 DEGREE DEFLECTION. |

| LOUVE | RS | | | | | | | | |
|-------------|-----------------------|-------------------------------|-------------------|--------------------|-------------------|------------------------------|---------------------------------|--------|--|
| DESIGNATION | REFERENCE PRODUCT | TYPE | WIDTH (INCHES) | HEIGHT (INCHES) | DEPTH (INCHES) | MAXIMUM AIR FLOW (CFM) | PRESSURE DROP (IN. WATER) | FINISH | REMARKS |
| L-1,2 | GREENHECK: EAD-634 | INTAKE COMB. DAMPER/LOUVER | 72 | 40 | 6 | 5000 | 0.03 | | PROVIDE MANUFACTURER'S BIRD AND INSECT SCREEN. PAINT TO MATCH ADJACENT SURFACE. |
| L-3 | GREENHECK: EDJ-401 | EXHAUST STATIONARY | 18 | 12 | 6 | 270 | 0.06 | | PROVIDE MANUFACTURER'S BIRD AND INSECT SCREEN. PAINT TO MATCH ADJACENT SURFACE. |

| HIGH | HIGH VOLUME, LOW SPEED (HVLS) FANS | | | | | | | | | | | |
|-------------|------------------------------------|-----|-----------------|----------|------------------|-----------------|--|--|--|--|--|--|
| DESIGNATION | REFERENCE PRODUCT | RPM | BLADE LENGTH | MOTOR HP | VOLTS / PHASE | WEIGHT (LBS) | REMARKS | | | | | |
| HVLS-1,2 | GREENHECK: DC-5-8 | 185 | 4 | 1/4 | 120 / 1 | 86 | PROVIDE MULTI FAN CONTROLLER, INSTALL FAN AND CONTROLLER PER MANUFACTURER'S INSTRUCTIONS. | | | | | |

2

3

4

| Ĺ | | |
|---|--|--|
| | | |
| | | |

4

5

1

ER'S INSTRUCTIONS. PROVIDE HAIL

S. INSTALL PER

RER'S INSTRUCTIONS

JRER'S INSTRUCTIONS RS. INSTALL PER

Collar and Bird Screen. Or Starter and Electrical An Shall Operate During the Ntering/exiting the Hangar.

| HANGAR REPLACEMENT 301 LINDBURG DRIVE 3001 LINDBURG DRIVE 3001 LINDBURG DRIVE JONESBORO, AR 72401 NOI BATE DATE NOI DATE DESCRIPTION REVISIONS REVISIONS | INT 1501 SUITE DALL | AS, TX | A T EEW 7523 FAU SIGHT ERING, . 352 | AS REE DIA AS | D N | AL |
|--|------------------------------|---------------------|--|------------------------|----------------------|-----------|
| | SEAL | 02-0 | 05-2.0 | 021 | DESCRIPTION | REVISIONS |
| HANGAR REPLACEMENT 3901 LINDBURG DRIVE JONESBORO, AR 72401 MECHANICAL SCHEDULES | | | | | | |
| | HANGAR REPLACEMENT | JONESBORO, AR 72401 | | | MECHANICAL SCHEDULES | |

| | PLUMBING GENERAL NO |
|-----|--|
| 1. | ALL PIPING IN FINISHED ROOMS OR SPACES SHALL BE CONCEALE ABOVE A HARD SUSPENDED CEILING. |
| 2. | ACCESS PANELS IN HARD SUSPENDED CEILINGS ARE REQUIRED F LEANOUTS, CONTROLS, ETC. COORDINATE LOCATION OF PANELS INSTALLATION AND DEMONSTRATE ACCESS TO EQUIPMENT SERV |
| 3. | ALL PIPE ROUTING AND CONSTRUCTION SHOWN ON THE DRAWIN NATURE AND MAY NOT BE SHOWN IN EXACT LOCATIONS OR WITH REQUIRED FOR A COMPLETE AND OPERATING SYSTEM. CONTRAC ROUTING OF ALL PIPING PER TYPICAL CONSTRUCTION PRACTICE POSSIBLE WHILE ADHERING AS CLOSELY TO THE DRAWINGS AS P RESPONSIBLE FOR COORDINATING ALL INSTALLATION WITH THE V FIELD MODIFICATIONS SUCH AS OFFSETS IN PIPING NEEDED DUE INTERFERENCES SHALL BE PROVIDED AT NO ADDITIONAL COST. |
| 4. | ALL WORK SHALL BE PERFORMED IN A NEAT AND WORKMANLIKE OF CARE FOR PROFESSION. ALL LABOR, MATERIAL, TOOLS, PERM CERTIFICATION, ETC. REQUIRED FOR A COMPLETE AND SATISFAC DESIGN INTENT SHALL BE FURNISHED BY CONTRACTOR. PROVIDE INCLUDING INCIDENTAL ITEMS NOT SHOWN WHEN REQUIRED FOF WORK. |
| 5. | DRAWINGS NOT BEARING THE STAMP OR SEAL AND SIGNATURE OF PROFESSIONAL ENGINEER SHALL NOT BE USED FOR BIDDING OR UNLESS EXPRESSLY APPROVED IN WRITING BY THE ARCHITECT. RESPONSIBLE FOR ENSURING THAT ALL DRAWINGS AND SPECIFIC BIDDING AND CONSTRUCTION PURPOSES ARE OF THE LATEST RE ADDENDUM DOCUMENTS HAVE BEEN INCORPORATED EITHER BY DRAWINGS/SPECIFICATIONS OR ATTACHMENT OF SKETCHES OR INFORMATION. |
| 6. | THE PLUMBING CONTRACTOR SHALL FURNISH AND INSTALL NEW AND REPUTABLE MANUFACTURERS. NO EQUIPMENT SUBSTITUTION WOULD LEAVE INADEQUATE OPERATING OR SERVICE SPACE. EQ INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMEN PROCEDURES AND IN AN ARRANGEMENT THAT WILL GIVE THE GR OPERATION AND SERVICE TO THE OWNER. |
| 7. | ALL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE REQU APPLICABLE CODES AND REGULATIONS INCLUDING BUT NOT LIMIT CITY, STATE, AND LOCAL ORDINANCES. ALL PLUMBING MATERIALS PROCEDURES, AND SYSTEM LAYOUTS SHALL BE APPROVED BY A HAVING JURISDICTION. THE CONTRACTOR SHALL PROVIDE ALL MA NECESSARY TO COMPLY WITH THESE RULES, REGULATIONS, AND CODES REPRESENT THE MINIMUM ACCEPTABLE REQUIREMENTS, DRAWINGS AND/OR SPECIFICATIONS INDICATE MATERIALS OR CO STRINGENT THAT CODE REQUIREMENTS, THE DRAWINGS AND/OF GOVERN. |
| 8. | IT IS THE RESPONSIBILITY OF THE PLUMBING CONTRACTOR TO PAPERMITS AND APPROVALS FOR THIS INSTALLATION. |
| 9. | ALL DOMESTIC WATER PIPING SHALL CONFORM TO THE REQUIRE CODE AND BE FREE FROM ALL DEFECTS AND BE PROPERLY IDEN |
| 10. | STERILIZE THE ENTIRE WATER DISTRIBUTION SYSTEM PER THE REAL AUTHORITY HAVING JURISDICTION. |
| 11. | DOMESTIC WATER SYSTEM, WASTE, SOIL AND VENT SYSTEM SHA AUTHORITY HAVING JURISDICTION. TEST AND OBTAIN APPROVAL PIPING FROM ADMINISTRATIVE AUTHORITY HAVING JURISDICTION |
| 12. | PLUMBING CONTRACTOR SHALL PROVIDE INITIAL START UP OF AL PLUMBING WORK. |
| 13. | ALL EXPOSED PIPING BELOW LAVATORY'S DESIGNATED AS HAND INSULATED. |
| 14. | ALL NON-DRAINAGE PIPING SHALL BE RUN LEVEL AND GENERALL UNNECESSARY BENDS, ARRANGED TO CONFORM TO THE BUILDIN SUIT THE NECESSITIES OF CLEARANCES FOR OTHER MECHANICA DRAINAGE OUTLETS IN AREAS OF PIPING WHICH WOULD BE UNDF MAINTENANCE OR REPAIRS. |
| 15. | ALL EQUIPMENT, PIPING, ETC., SHALL BE SUPPORTED AS DETAILE PROVIDE ADDITIONAL SUPPORTS AS REQUIRED TO PROVIDE A VIE INSTALLATION. |
| 16. | PENETRATIONS OF WALLS OR FLOORS FOR THE PASSAGE OF PIP SHALL BE PROPERLY SEALED AFTER INSTALLATION OF ITEMS ANI |
| 17. | PROVIDE UNIONS OR FLANGES AT PIPING CONNECTIONS TO EQUI DISASSEMBLY FOR MAINTENANCE. ARRANGE PIPING TO ALLOW F REMOVAL. |
| 18. | PROVIDE ESCUTCHEONS FOR EXPOSED PIPING PENETRATIONS IN |
| 19. | PIPING, LEAK PROTECTION APPARATUS, OR OTHER EQUIPMENT F SWITCHBOARDS, PANELBOARDS, DISTRIBUTION BOARDS, OR MO SHALL NOT BE INSTALLED WITHIN THE REQUIRED SPACE FOR WO DEDICATED SPACES OF THE ELECTRICAL EQUIPMENT, EXTENDING FLOOR TO STRUCTURAL CEILING WITH A WIDTH AND DEPTH OF TI IN ACCORDANCE WITH NEC-110.26. |

Α

В

С

D

1

3

OTES

ALED IN A FURRED CHASE OR

ED FOR ALL VALVES, TRAPS, ELS WITH MECHANICAL ERVED.

WINGS IS DIAGRAMMATIC IN VITH ALL ANCILLARY ITEMS RACTOR SHALL COORDINATE ICE IN THE MOST EFFICIENT WAY AS POSSIBLE.CONTRACTOR IS HE WORK OF OTHER TRADES. DUE TO OBSTRUCTIONS OR

IKE MANNER WITHIN STANDARD ERMITS, INSPECTIONS, TESTING, FACTORY INSTALLATION TO VIDE, AT NO ADDITIONAL COST, FOR TYPICAL COMPLETION OF

RE OF A REGISTERED OR CONSTRUCTION PURPOSES CT. THE CONTRACTOR SHALL BE CIFICATIONS BEING USED FOR FREVISION AVAILABLE AND ALL BY REVISION RELEASE OF OR OTHER ADDENDUM

EW PRODUCTS OF ESTABLISHED UTIONS SHALL BE MADE THAT EQUIPMENT SHALL BE MENDED INSTALLATION GREATEST PRACTICAL EASE OF

EQUIREMENTS OF ALL IMITED TO CAVHS, NATIONAL, IALS, INSTALLATION BY ALL APPLICABLE AUTHORITIES L MATERIALS AND LABOR AND ORDINANCES. THESE ITS, THEREFORE, WHERE CONSTRUCTION MORE D/OR SPECIFICATIONS SHALL

O PAY FOR ALL NECESSARY

JIREMENTS OF THE ANSI SAFETY DENTIFIED.

E REQUIREMENTS OF THE LOCAL

SHALL ALL BE TESTED PER LOCAL VAL ON ALL UNDERGROUND TON PRIOR TO COVERING WORK. F ALL SYSTEMS INCLUDED IN THE

NDICAPPED SHALL BE TOTALLY

ALLY FREE OF TRAPS AND LDING REQUIREMENTS AND TO IICAL WORK. PROVIDE VALVED NDRAINABLE DURING

AILED AND/OR SPECIFIED. A VIBRATION-FREE, RIGID


PIPING OR OTHER EQUIPMENT AND EQUIPMENT.


QUIPMENT TO ALLOW W PULL SPACE FOR EQUIPMENT

IS INTO FINISHED ROOMS.

NT FOREIGN TO ELECTRICAL MOTOR CONTROL CENTERS WORKING CLEARANCES OR DING IN FRONT OF AND FROM OF THE ELECTRICAL EQUIPMENT

| LEGEND | | | | | | | |
|--|----------------------------|--|---|--|--|--|--|
| SYMBOL | DESCRIPTION | SYMBOL | DESCRIPTION | | | | |
| | NEW FIXTURE / EQUIPMENT. | | BALL VALVE | | | | |
| | EXISTING PIPING TO REMAIN. | | GATE VALVE | | | | |
| `````````````````````````````````````` | NEW PIPING | | CHECK VALVE | | | | |
| }—SS—→ | SANITARY SEWER (SS) | | PRESSURE REDUCING VALVE | | | | |
| | VENT (V) | | VALVE AT PIPE RISER | | | | |
| · | COLD WATER (CW) | \rightarrow | ELBOW, TURNED UP | | | | |
| <u>ک</u> ے۔۔۔ | HOT WATER (HW) | $\subset + \rightarrow$ | ELBOW, TURNED DOWN | | | | |
| VTR | VENT THRU ROOF | X-+ | RISE OR DROP IN PIPE | | | | |
| СО | CLEANOUT PLUG | \sim | TEE, OUTLET UP | | | | |
| FCO | FLOOR CLEANOUT | | | | | | |
| WCO | WALL CLEANOUT | | TEE, OUTLET DOWN | | | | |
| COTG | CLEANOUT TO GRADE | $\underset{\sim}{\overset{+}{\leftarrow}}$ | TEE, SIDE CONNECTION | | | | |
| | | ++ | PIPE ELBOW 90° | | | | |
| 1 P301 | RISER DESIGNATION | \sim | PIPE ELBOW 45° | | | | |
| | | | CAPPED OUTLET | | | | |
| \bigotimes | CONNECT TO EXISTING. | | CAPPED PIPE | | | | |
| \diamond | POINT OF DEMOLITION. | | CONCENTRIC REDUCER | | | | |
| \bigwedge | REVISION DELTA | | ECCENTRIC REDUCER | | | | |
| | | <u>P-1</u> | PLUMBING FIXTURE / EQUIPMENT DESIGNATION | | | | |
| | | FD | FLOOR DRAIN | | | | |





1

3

4


| | 5 GENERAL NOTES | Michael Baker |
|--------------------|--|---|
| 1. | PIPE SIZES SHOWN ON SANITARY SEWER AND VENT RISER DIAGRAM ON SHEET P201 - PLUMBING RISER DIAGRAMS. | I N T E R N A T I O N A L 1501 LBJ FREEWAY, SUITE 650 DALLAS, TX 75234 |
| | | Consultant |
| | | NO. DATE DESCRIPTION REVISIONS |
| | | HANGAR REPLACEMENT 3901 LINDBURG DRIVE JONESBORO, AR 72401 FLOOR PLAN - SANTARY SEWER AND VENT |
| | | Project Number: 181261 Date: 02-05-2021 |
| PLAN NORTH N | 0 4' - 0" 8' - 0" 16' - 0" SCALE: 0' - 0 1/8" = 1' - 0" | Scale: AS NOTED |


© Baker 2018


ភ


CONST




















| PLUM | IBING FIXTURE | SCHEDULE | | | | | | | |
|--------------|---------------------------|---|--|--------|--------|---------|------|----------|--|
| DESIGNATION | FIXTURE TYPE | BASIS | OF DESIGN | PIPE | CON | NECTION | SIZE | TRAP | DESCRIPTION |
| DESIGNATION | | MANUFACTURER AND MODEL | ACCESSORIES | COLD | нот | WASTE | VENT | | DESCRIPTION |
| <u>WC-1</u> | WATER CLOSET | AMERICAN STANDARD "MADERA 16-1/2" #3043.001, ZURN Z6000 FLUSH VALVE | CENTOCO #1500STSCCSS HEAVY DUTY OPEN FRONT LESS COVER SEAT, ZURN Z8802-XL-Q-PC QUARTER TURN STOP | 1" | - | 4" | 2" | INTEGRAT | ADA COMPLIANT, 1.6 GPF, FLOOR MOUNTED, VITREOUS CHINA, M OPEN FRONT SEAT, SELF SUSTAINING, LESS COVER |
| LAV-1 | LAVATORY ADA | AMERICAN STANDARD "TROPIC OVA" #0405.008EC.050, T&S BRASS #B-2701 FAUCET | ZURN #Z8746-PC STRAINER, ZURN #Z8802-XL-LRLK-PC-CE STOPS, ZURN Z78700-PC TRAP, LEONARD #170A-LP-CP THERMOSTATIC MIXING VALVE | 1/2" | 1/2" | 2" | 2" | 1-1/4" | ADA COMPLIANT, 20-1/2"x17-1/2", COUNTER TOP, WHITE VITREOU CHROME PLATED OPEN GRID DRAIN STRAINER, CHROME PLATED S AERATOR, MANUAL, SINGLE LEVER DECK MOUNT, LEAD FREE, CHR |
| <u>UR-1</u> | URINAL ADA | AMERICAN STANDARD "WASHBROOK" #6590.001, DELANEY "SABER" #S451-0.5-T.106 | ZURN Z-1221 CARRIER | 3/4" | - | 2" | 2" | INTEGRAT | URINAL - ADA COMPLIANT, 14-1/8"x18-7/8"x45"H, WALL MOUNTE SPUD, WASHOUT ACTION, FLUSH VALVE - 0.5 GPF, MASHAERATOR |
| <u>EWC-1</u> | ELECTRIC WATER COOLER | ELKAY LZSTL8SC | ZURN Z-1225BL CARRIER | 1/2" | - | 2" | 2" | | ELECTRIC WATER COOLER, 8 GPH OF 50 DEG. F DRINKING WATER A WATER, PUSHBAR ACTIVATION, STAINLESS STEEL CABINET, STAIN FLEXIBLE ANTI-MICROBIAL BUBBLER, UNIT SHALL MEET ADA GUID |
| <u>SH-1</u> | EMERGENCY SHOWER | GUARDIAN G1662SSH | GUARDIAN G3600LF THERMOSTATIC MIXING VALVE | 1-1/4" | 1-1/4" | - | - | - | ADA COMPLIANT SHOWER SAFETY STATION, PLASTIC SHOWER HE. CAST ALUMINUM FLAG HANDLE AND FLOOR FLANGE |
| <u>SS-1</u> | SERVICE SINK | STERN WILLIAMS SB-900 SERVICE SINK, T&S BRASS B- 0665-BSTR FAUCET | T-35 HOSE AND WALL HOOK, T-40 MOP HANGER | 1/2" | 1/2" | 3" | 2" | 3" | SERVICE SINK- 24"x24"x12" FLOOR MOUNTED, PRE-CAST TERRAZO PLATED LEAD FREE, 6" WRIST BLADE CONTROLS, 3/4" HOSE THREA SPRING CHECK VALVES, UPPER SUPPORT ROD |
| <u>FPWH</u> | FREEZE PROOF HOSE BIBB | ZURN Z-1300 ECOLOTROL FREEZE PROOF WALL HYDRANT | - | 3/4" | - | - | - | - | FREEZE PROOF HOSE BIBB WITH STAINLESS STEEL BOX AND COVE |
| <u>НВ</u> | WALL MOUNTED HOSE BIBB | WOODFURD MODEL 84 WITH KEY LOCK | PROVIDE TEE KEY | 3/4" | - | - | - | - | ANTI SIPHON VACUUM BREAKER , 3/4" INLET AND OUTLET, PACKI FINISH TO BE CHROME PLATED. PROVIDE LOOSE TEE KEY WITH EA |

| PLUM | PLUMBING EQUIPMENT SCHEDULE | | | | | | | | | | |
|--------------|----------------------------------|------------------|---|----------------------|------------------------------|--------|---|--|--|--|--|
| DESIGNATION | EQUIPMENT | BASIS OF DESIGN | PIPING CONNECTIONS | NATURAL GAS INPUT | ELECTRIC (VOLT / PH / HZ) | POWER | REMARKS | | | | |
| <u>WH-1,</u> | NATURAL GAS TANK WATER HEATER | AOMSITH: XCR-30R | 3/4" CW, 3/4" HW, 1/2" GAS, 4" VENT, 1/2" CONDENSATE | 35,500 | 120V/1/60 | - | NATURAL GAS TANK WATER HEATER -36 GPH @ 90°F, TANK TYPE, HIGH TEMP ENAMEL TANK LINING, MAGNESIUM ANODE ROD RIGIDLY SUPPORTED, 150 PSI WORKING PRESSURE RATING, HIGH LIMIT CONTROL, CSA/ASME RATED T&P RELIEF VALVE, UL SEAL OF CERTIFICATION, COMPLETELY FACTORY ASSEMBLED. 6 YEAR WARRANTY. | | | | |
| <u>ET-1</u> | EXPANSION TANK | ZURN WTTA-5 | 3/4" | - | - | - | | | | | |
| <u>GP-1</u> | GRINDER STATION PUMP STATION | LIBERTY 248 LSG | 1-1/4" | - | 208/1 | 15 AMP | 2 HP, PROVIDE WITH ON/OFF FLOAT SWITCH, IN NEMA 4X OUTDOOR ALARM WITH VISUAL AND AUDIBLE ALARM | | | | |

| PLUMBI | PLUMBING SPECIALITIES SCHEDULE | | | | | | | | | |
|--------------|--------------------------------|---|----------|--------|--|--|--|--|--|--|
| DESIGNATION | FIXTURE | DESCRIPTION | SIZE | OUTLET | | | | | | |
| WCO | WALL CLEAN OUT | WADE 8304 WITH ROUND CHROME COVER PLATE AND FRAME, COUNTERSUNK SCREWS | AS NOTED | - | | | | | | |
| FCO | FLOOR CLEANOUT | WADE 6000-1 CAST IRON, GASKETED HUB OUTLET, THREADED ADJUSTABLE HOUSING, BRONZE PLUG, NICKEL BRONZE SCORIATED TOP, VANDAL-PROOF SCREWS. | AS NOTED | - | | | | | | |
| <u>FD-1</u> | FLOOR DRAIN | ZURN ZN-415-S6" WITH CAST IRON BODY AND NICKEL BRONZE STRAINER. | AS NOTED | - | | | | | | |
| <u>FS-1</u> | FLOOR SINK | ZURN ZN-1901-2-32 WITH CAST IRON BODY AND NICKEL BRONZE FRAME AND 1/2" GRATE | AS NOTED | - | | | | | | |
| <u>RPZ-1</u> | BACKFLOW PREVENTER | WILKINS 975XL2 REDUCED PRESSURE ASSEMBLY WITH BRONZE WYE TYPE STRAINER AND AIR GAP | 1" | - | | | | | | |
| <u>0I-1</u> | OIL AND SOLID INTERCEPTOR | ZURN OMC500 - OIL INTERCEPTOR. INSTALL PER MANUFACTURER'S RECOMMENDATION. PROVIDE H20 TRAFFIC LOADING COVER COVER, EXTENSION COLLAR | 500 GAL | 4" | | | | | | |
| | WATER HAMMER ARRESTORS | ZURN Z1700 WATER HAMMER ARRESTOR, SIZED IN ACCORDANCE WITH PDI-WH201 AND ASSE-1010. BELLOWS AND CASING SHALL BE CONSTRUCTED OF STAINLESS STEEL, MAXIMUM WORKING PRESSURE OF 125 PSIG. | AS NOTED | - | | | | | | |

В

Α

С

D

1

2

3

| 4 |
|---|
|---|

3

4

ON

A, MANUAL FLUSHVALVE, ELONGATED BOWL, SEAT -

REOUS CHINA, BACK OVERFLOW, CENTER HOLE ONLY, TED SUPPLY STOPS AND TRAP, FAUCET - 0.5 GPM CHROME PLATED THERMOSTATIC MIXING VALVE

NTED, VITREOUS CHINA, 3/4" EXPOSED TOP TOR SELF-CLEANING BYPASS DIAPHRAGM


TER AT 90 DEG. F AMBIENT AND 80 DEG. F INLET AINLESS STEEL BASIN WITH INTEGRAL DRAIN, GUIDELINES

HEAD, STAINLESS STEEL BOWL, POWDER-COATED

AZO, STAINLESS STEEL CAPS, FAUCET - CHROME IREADED OUTLET, COMPRESSION CARTRIDGES WITH

OVER

CKING NUT SECURED WITH LOCK NUT. EXTERIOR H EACH HOSE BIBB.



STRUCTURAL DESIGN CRITERIA

| | DESIGN SUMMARY: THE STRUCTURAL DESIGN OF THE MAINTENANCE HANGAI ENGINEERED METAL BUILDING (PEMB) STRUCTURE THAT IS DE OTHERS. THERE IS AN EXISTING SLAB AND FOUNDATION SYST UTILIZED TO SUPPORT THE NEW PEMB. THE FOUNDATION REA WILL BE VERIFIED BASED ON THE PEMB FINAL STAMPED DRAW BEGINS. THE EXISTING SLAB IS EXPECTED TO BE RE-USED FOF THE NEW BUILDING IS TALLER THAN THE PREVIOUS BUILDING, A EXISTING FOUNDATIONS WILL NEED TO BE STRENGTHENED TO | SIGNED AND PROVIDED BY EM IN PLACE THAT WILL BE CTIONS ARE APPROXIMATED AND INGS BEFORE CONSTRUCTION R THE NEW BUILDING. HOWEVER, AND THEREFORE MOST OF THE | А. В. | SF 1. RE MI 1. 2. 3. |
|---|--|--|----------|--|
| A | DESIGN CODE: 2012 ARKANSAS FIRE PREVENTION CODE (BASE BUILDING CODE) | D ON THE 2012 INTERNATIONAL | | 4. O\ |
| | ALSO REFERENCES ASCE 7-10 RISK CATEGORY: II GRAVITY LOADS DEAD LOAD = MATERIAL WEIGHT PLUS COLLATERA | L LOAD BY PEMB | C. | EA 1. T⊢ 2. |
| | LIVE LOADS TYPICAL ROOF LIVE LOAD | 20 PSF | D. | CC |
| | SNOW DRIFT SHALL BE CONSIDERED FOR THE NEW STRUCTUR | PG= 10 PSF RE PER ASCE 7-10. | | 1. 2. 3. 4. 5. 6. 7. 8. |
| В | NOMINAL WIND SPEED IMPORTANCE FACTOR EXPOSURE CATEGORY SEISMIC: SOIL SITE CLASS IMPORTANCE FACTOR MAPPED SPECTRAL RESPONSE ACCELERATION PARAMETERS MCE/R SPECTRAL RESPONSE ACCELERATION PARAMETERS DESIGN SPECTRAL RESPONSE ACCELERATION PARAMETERS | Vult= 115 MPH Vasd=89 MPH Iw=1.0 C D Ie=1.0 SS=1.57 S1=0.547 SMS=1.57 SM1=0.821 SDS=1.047 SD1=0.547 D | E. | C (1. 2. 3. 4. 5. |
| | | | | |

SPECIAL INSPECTIONS:

REPORTS SHALL BE FURNISHED.

2

MISCELLANEOUS:

CONTRACTOR SHALL COMPLY WITH ALL OSHA SAFETY STANDARDS DURING CONSTRUCTION.

CONTRACTOR SHALL LOCATE ALL EXISTING UTILITIES PRIOR TO CONSTRUCTION. ALL UNDERGROUND UTILITIES MAY NOT BE SHOWN ON THE DRAWINGS.

CONTRACTOR SHALL COORDINATE WORK FROM ALL DISCIPLINES AS REQUIRED. ANY CONFLICTS OR CONTRADICTIONS BETWEEN DIFFERENT DETAILS WITHIN THE DRAWINGS OR SPECIFICATIONS SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE OWNER'S REPRESENTATIVE FOR CLARIFICATION/RESOLUTION.

- 3

EARTHWORK:

THE STATE OF ARKANSAS.

CONCRETE AND REINFORCING:

- ALL CONCRETE AND REINFORCEMENT SHALL CONFORM TO THE LATEST ACI CODE.
- ALL REINFORCING BARS SHALL BE A-615 GRADE 60 STEEL.
- LAP ALL REINFORCING BARS 48 BAR DIAMETERS MIN.
- ALL CONCRETE SHALL HAVE A COMPRESSIVE STRENGTH AT 28 DAYS (f"c) OF 3500 PSI.
- MAXIMUM AGGREGATE SIZE IN FOOTINGS SHALL BE 1 1/2", MAXIMUM.
- CONCRETE EXPOSED TO WEATHER SHALL HAVE 5.5% AIR ENTRAINMENT.

CONCRETE MASONRY:

- REQUIRED MASONRY NET AREA COMPRESSIVE STRENGTH fm = 2000 PSI.
- TYPE M OR S MORTAR SHALL BE USED THAT CONFORMS TO ASTM C270.

STRUCTURAL GENERAL NOTES

ALL SPECIAL INSPECTIONS AND TESTS REQUIRED IN ACCORDANCE WITH CHAPTER 17 OF THE INTERNATIONAL BUILDING CODE SHALL BE PERFORMED BY A QUALIFIED INSPECTOR AND

FOUNDATIONS ARE DESIGNED BASED ON AN ALLOWABLE BEARING CAPACITY OF 2000 PSF. THE BEARING CAPACITY SHALL BE VERIFIED BY A GEOTECHNICAL ENGINEER LICENSED IN

COMPACT SOIL UNDER FOOTING TO 98% STANDARD COMPACTION IN ACCORDANCE WITH ASTM D698.


PLACE AND CURE CONCRETE IN ACCORDANCE TO ACI 305R AND 306R FOR HIGH AND LOW AIR TEMPERATURES AT PLACEMENT, RESPECTIVELY. THE CONCRETE FOUNDATION HAS BEEN DESIGNED IN ACCORDANCE WITH ACT 1100, 1991 OF THE STATE OF ARKANSAS.

CONCRETE MASONRY MATERIALS AND CONSTRUCTION METHODS SHALL CONFORM TO THE LATEST ACI-530.

GROUT SHALL CONFORM TO ASTM C476 WITH A MINIMUM 28-DAY COMPRESSIVE STRENGTH OF 2000 PSI AND SHALL BE PLACED WITH A MECHANICAL VIBRATOR.

THE HARDENED CMU WALL STRUCTURES SHALL BE FULLY GROUTED AND GROUTING PROCEDURE SHALL COMPLY WITH THE ACI 530.

| HANGAR REPLACEMENT 3901 LINDBERGH DRIVE 3901 LINDBERGH DRIVE JONESBORO, AR 72401 GENERAL NOTES Revisions Revisions | SU DA = = SI 311 JOI PH | JITE ALL N C | م م م م ۱ | 0 TX N N TINC CO, A VO-21 | 752 E STOI RKA 9-34 TE O ANSA STER | | RT RI Æ. | H A N G |
|--|--|--------------------|--------------|---|--|-----|----------------|---------------|
| REVISIONS | | an non | | No. | ★ ★ 12969 VW. | ANF | | • |
| | | | | | | | DESCRIPTION | REVISIONS |
| HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 GENERAL NOTES | | | | | | | | |
| | | | | JONESBORO, AR 72401 | | | GENERAL NOTES | |



1

3

4

| FOOTING SCHEDULE | | | | | | |
|-------------------|-------------------------------|--|--|--|--|--|
| LxWxD | REINFORCING | | | | | |
| " x 6'-0' x 2'-0" | 7 - #6 EACH WAY, TOP & BOTTOM | | | | | |
| " x 7'-0' x 2'-0" | 8 - #6 EACH WAY, TOP & BOTTOM | | | | | |
| " x 7'-0' x 1'-6" | 8 - #6 EACH WAY, TOP & BOTTOM | | | | | |
| | | | | | | |

INDICATES NEW CONCRETE

| INDICATES | EXISTING | CONCRETE | TO REMAIN |
|---------------|----------|----------|-----------|
| | | | |

DEMO EXISTING SLAB AS REQUIRED FOR NEW FOOTING AND NEW CONCRETE FILL. DEMO EXISTING CONCRETE COLUMN PEDESTAL AND EXISTING

 NEW 5/" CONCRETE SLAB w/ AIR-ENTRAINMENT (5%±) w/12"x12" TURNDOWN & W.W.R. 4x4-W2.9xW2.9
 (OCCURS IN 3 LOCATIONS, COORDINATE WITH ARCH)

| | Michael Baker INTERNATIONAL 1501 LBJ FREEWAY, SUITE 650 DALLAS, TX 75234 | | | | | | | | |
|--|--|--|--|--|--|--|--------------------------|-----------|--|
| | Consultant REGISTERED REGIST | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | DESCRIPTION | REVISIONS | |
| | | | | | | | NO. DATE | | |
| | HANGAR REPLACEMENT 3901 LINDBERGH DRIVE JONESBORO, AR 72401 | | | | | | FOUNDATION AND SLAB PLAN | | |
| | Project Number: 181261 Date: 02-05-2021 Scale: AS NOTED Sheet # S-101 | | | | | | | | |



© Baker 2021

